

Industrial Marathon® Low Voltage Motor Price List

August 2026
India

Industrial Motors

Commercial &
Appliance Motors

Automation

Digital &
Systems

Energy

Transmission &
Distribution

Coatings



TABLE OF CONTENTS

(Click on each page title below to navigate the page.)

	PAGES
CASH EXTRAS FOR NON-STANDARD FEATURES	3 - 4
TERRAMAX[®] SCA SERIES (IE2) SQUIRREL CAGE MOTORS	5
TERRAMAX[®] TCA SERIES (IE3) SQUIRREL CAGE MOTORS	6
TERRAMAX[®] TCA SERIES (IE3) UL CERTIFIED SQUIRREL CAGE MOTORS	7
FLAME PROOF (IE2) GAS GROUP I, IIA IIB SQUIRREL CAGE MOTORS	8 - 9
FLAME PROOF (IE3) GAS GROUP I, IIA IIB SQUIRREL CAGE MOTORS	10
FLAME PROOF (IE2) GAS GROUP IIC SQUIRREL CAGE MOTORS	11
CRANE DUTY (KS) SLIPRING MOTORS	12
MARATHON FIREFIGHTING (IE2) MOTORS	13
TERRAMAX[®] SMOKE SPILL (IE2 -250^o C) SCS SERIES MOTOR	14
TERRAMAX[®] SMOKE SPILL (IE3 -250^o C) TCS SERIES MOTOR	15
TERRAMAX[®] SMOKE SPILL (IE2 -300^o C) SCS SERIES MOTOR	16
TERRAMAX[®] SMOKE SPILL (IE3 -300^o C) TCS SERIES MOTOR	17
TERRAMAX[®] SMOKE SPILL (IE2 -400^o C) SCS SERIES MOTOR	18
TERRAMAX[®] SMOKE SPILL (IE3 -400^o C) TCS SERIES MOTOR	19
TERRAMAX[®] CRANE DUTY (IE2) SCV SERIES SQUIRREL CAGE MOTORS	20
TERRAMAX[®] CRANE DUTY (IE3) TCV SERIES SQUIRREL CAGE MOTORS	21
TERRAMAX[®] EX'td' DUST PROOF - IIIC MOTOR TCT SERIES (ATEX/IECEX CERTIFIED)	22
TERRAMAX[®] EX'ec' NON SPARKING MOTORS TCN SERIES (ATEX/IECEX CERTIFIED)	23
TERRAMAX[®] STANDARD BRAKE MOTOR	24
TERRAMAX[®] CRANE DUTY SCV BRAKE MOTOR	25
TERRAMAX[®] CRANE DUTY TCV BRAKE MOTOR	26

CASH EXTRAS FOR NON-STANDARD FEATURES

FRAME SIZE : 80 TO 355

Sl.No.	Special Features	Extra Price															
1	Shaft Extension Double cylindrical/ single taper (1:10) Double taper (1:10)	5% 10%															
2	Mounting Standard flange and face mounting Upto 160 frame Frame 180 and above	3% 5%															
3	Winding Treatment Power house treatment VPI treatment Epoxy gel coat on winding overhang	5% 5% 3%															
4	Painting (External) Epoxy standard paint shade Epoxy non-standard paint shade Non Epoxy Non-standard Shade Paint Thickness Paint thickness above 50 micron upto 150 micron Paint thickness above 150 micron upto 215 micron Paint thickness above 215 micron upto 300 micron	3% 5% 5% (Max. Rs.7,000/-) 4% 6% 10%															
5	Space Heater Upto frame 160 From 180 to 355 frame Thermister 3 nos. 6 nos.	RS 1200/- Rs 2650/- Rs 2,150/- Rs 4,300/-															
6	Non-Standard Voltage and Frequency Voltage 220-550 with frequency 50 Hz or 60 Hz Dual voltage	3% 5%															
7	Non Std. RV/RA for slipring motors (contact Marathon Electric Motors (India) Ltd for confirmation.)	5%															
8	Vibration Level (IS-12075) Normal class Precision class A,B,C	No extra On request															
9	Testing charges per motor <table> <tr> <td>Frame size:</td><td>Routine test:</td><td>Type test:</td></tr> <tr> <td>upto 132</td><td>Rs 1200</td><td>Rs 5000</td></tr> <tr> <td>160-225 Frame</td><td>Rs 2400</td><td>Rs 7500</td></tr> <tr> <td>250-280</td><td>Rs 3600</td><td>Rs 10000/-</td></tr> <tr> <td>315-355</td><td>Rs 3600</td><td>Rs 15000/-</td></tr> </table>	Frame size:	Routine test:	Type test:	upto 132	Rs 1200	Rs 5000	160-225 Frame	Rs 2400	Rs 7500	250-280	Rs 3600	Rs 10000/-	315-355	Rs 3600	Rs 15000/-	
Frame size:	Routine test:	Type test:															
upto 132	Rs 1200	Rs 5000															
160-225 Frame	Rs 2400	Rs 7500															
250-280	Rs 3600	Rs 10000/-															
315-355	Rs 3600	Rs 15000/-															
10	IP-56	5%															
11	Class "H"	10%															
12	Cable gland 80-132 160-225 250-355	Non-FLP / FLP Rs 800 / Rs 1500 Rs 2,000 / Rs 2500 Rs 2,500 / Rs 4500															
13	RTD (TerraMAX series frame 200-355) 3 nos. simplex 6 nos. simplex 3 nos. duplex 6 nos. duplex Note: For lower frames, contact Marathon Electric Motors (India) Ltd.	Rs 4000/- Rs 8000/- Rs 8000/- Rs 16000/-															
14	BTD frame (TerraMAX series frame 160-355) 2 nos. simplex 2 nos. duplex	Rs 7500/- Rs 12000/-															
15	FLP - for Gas Group - I, Cable Sealing Box arrangement KF112M - KF132M KF160M - KF225M KF250M - KF315L	Rs 1,700/- Rs 2000/- Rs 3,600/-															
16	Fault level terminal box (50 kA for 0.25 sec) Frame size 280 and above	Rs 50,000/-															
17	Roller bearing on DE side Frame Size: Frame 132 Frame 160-200 Frame 225-250 Frame 280-315 Frame 355	Rs 1,500/- Rs 2,000/- Rs 3,500/- Rs 6,000/- Rs 9,000/-															

CASH EXTRAS FOR NON-STANDARD FEATURES

FRAME SIZE : 80 TO 355

Sl.No.	Special Features	Extra Price
18	One size higher terminal box for TerraMAX motors range Frame size: 160-200 225-315	4% 3%
19	Insulated Bearing housing on NDE side (applicable for TCV/SCV 280 - TCV/SCV 355 frame only) Frame Size 280 315 355 VWF driven motor frame size 280 & above will be provided with insulated bearing housing at NDE side for both variable torque and constant torque application	Rs 10,000/- Rs 12,000/- Rs 14,000/-
20	Seaworthy / Export packing	7.5% (Max. Rs.15,000/-)
21	Forced cooling (IC416) arrangement (For force cooling of lower frames - refer to Marathon Electric Motors (India) Ltd) 100-132 160-180 200-225 250 280 315 355 Note: For TerraMAX series and force cooling of lower frames - contact Marathon Electric Motors (India) Ltd.	Rs. 7,500 Rs. 8,000 Rs. 18,500 Rs. 27,000/- Rs. 33,000/- Rs. 36,500/- Rs. 44,500/-
22	Documentation charges (technical/commercial) Documents for approval/submission RTF	Rs 1,200/ - per rating Rs 5,000/ - per rating
23	VWF driven motor (SCV/TCV) Upto 132 160-250 280-355	8% 8% 8%
24	Tacho Mounting arrangement (for Hollow Shaft Encoder)	7.5% (Min Rs 3,000/-, Max Rs 7,500/-)
25	Insulated bearing charges 250-280 315 355	Rs. 31,000/- Rs. 31,000/- Rs. 40,000/-
26	Brake mounting arrangement (Brake price extra)	15%
27	Metal Fan 80-132 160-225 250-280 315-355	Rs. 500/- Rs. 900/- Rs. 1600/- Rs. 3000/-

Notes:

1. Tests strictly as per IS/IEC®* and for any other test like noise level, vibration level, overspeed, ultrasonic test on shaft, etc., will be advised on request.
2. Extra charges imposed by outside inspection agencies will be recovered from Customer at actuals.
3. For other than 415v / 50Hz motors please refer to factory.

Special Notes:

1. All % (percentage) figures are to be loaded on list price.
2. All Rs (Rupees) figures are to be loaded on net price.
3. For any other special features please contact Marathon Electric Motors (India) Ltd. Contact information can be found on last page.

*The following trademarks are owned by their respective owners: ATEX is a trademark of European Union;
IEC and IECEx are trademarks of International Electrotechnical Commission;
*For PESO/DGMS certified motors: Please contact the factory.

TERRAMAX® SCA SERIES (IE2) SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC®* 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55 (up to IP66 on request)

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	21919
80M	0.55	21919
80M	0.75	21919
80M	1.1	23816
90S	1.5	27620
90L	2.2	35111
100L	3.7	44939
132S	5.5	74029
132S	7.5	81206
160M	9.3	137024
160M	11	151212
160L	15	159143
160L	18.5	199739
180M	22	229692
200L	30	334093
200L	37	387216
225M	45	509868
250M	55	670798
280S	75	900162
280M	90	1014246
315S	110	1308337
315SM	125	1532034
315M	132	1570624
315SM	160	1778028
315L	180	1871843
315L	200	1981521
315L	225	2283089
355M	250	2338359
355M	275	2404430
355L	315	2574129
355L	355	3252555
355L	375	3390509

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	21919
80M	0.55	21919
80M	0.75	22247
90S	1.1	28988
90L	1.5	33328
100L	2.2	40077
100L	3	50583
112M	3.7	53095
112M	4	67014
132S	5.5	72033
132M	7.5	85248
132M	9.3	109298
160M	9.3	134576
160M	11	139107
160L	15	175301
180M	18.5	223123
180L	22	252653
200L	30	343763
225S	37	384427
225M	45	455353
250M	55	640278
280S	75	826241
280M	90	962367
315S	110	1111888
315M	125	1237152
315M	132	1302904
315L	160	1632066
315L	180	1735832
315L	200	1791681
355SM	225	2278606
355SM	250	2417697
355SM	275	2469161
355L	315	2743857
355L	355	3597939
355L	375	3631527

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90S	0.75	28022
90L	1.1	30747
100L	1.5	43879
112M	2.2	47551
112M	3	66941
132S	3.7	77419
132M	5.5	93490
160M	7.5	136490
160M	9.3	159018
160L	11	167943
180L	15	224576
200L	18.5	310225
200L	22	339294
225M	30	477450
250M	37	612806
280S	45	834274
280M	55	958102
315S	75	1078561
315M	90	1318853
315SM	110	1436394
315L	125	1714793
315L	132	1756686
315L	160	1912299
355M	180	2259440
355SM	200	2418984
355L	225	2491634
355L	250	2664061
355L	275	3097228
355L	315	3834088

**GST as applicable.

TB Position upto 225 frame, Top as standard,

TB Position from 250 to 355, RHS/LHS as standard, (Top on request)

*IEC is a trademark of International Electrotechnical Commission.

TERRAMAX® TCA SERIES (IE3) SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC® 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55 (up to IP66 on request)

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	23471
80M	0.55	23471
80M	0.75	24245
80M	1.1	26408
90S	1.5	30248
90L	2.2	38860
100L	3	54480
100L	3.7	56114
132S	5.5	78651
132S	7.5	81796
160M	9.3	144394
160M	11	152936
160M	15	167438
160L	18.5	213988
180M	22	238693
200L	30	359859
200L	37	426831
225M	45	562385
250M	55	704166
280S	75	954095
280M	90	1100586
315S	110	1409530
315M	125	1578628
315M	132	1645340
315L	160	1845529
315L	180	1942800
315L	200	2082587
355M	225	2383644
355M	250	2510541
355M	275	2542244
355L	315	2784091
355L	355	3473602
355L	375	3638174

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	24875
80M	0.55	24875
80M	0.75	25950
90S	1.1	31595
90L	1.5	36779
100L	2.2	43793
100L	3	53146
112M	3.7	56792
132S	5.5	80443
132M	7.5	95060
160M	9.3	148285
132M	9.3	111951
160M	11	153397
160L	15	191490
180M	18.5	234381
180L	22	256687
200L	30	354149
225S	37	442987
225M	45	536979
250M	55	656929
280S	75	867393
280M	90	1010338
315S	110	1179191
315M	125	1312063
315M	132	1381732
315L	160	1739159
315L	180	2010808
315L	200	2094851
355M	225	2486089
355M	250	2651066
355L	275	2672872
355L	315	2999370
355L	355	3709215
355L	375	3761670
355L	400	3832645

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90S	0.75	33640
90L	1.1	36779
100L	1.5	56198
112M	2.2	59605
132S	3.7	87873
132M	5.5	107423
160M	7.5	157669
160L	9.3	171808
160L	11	194115
180L	15	258840
200L	18.5	339003
200L	22	364202
225M	30	521532
250M	37	658714
280S	45	896746
280M	55	1006352
315S	75	1132933
315M	90	1385339
315SM	110	1508867
315L	125	1891271
315L	132	1893478
315L	160	1963031
355M	180	2637910
355M	200	2750768
355L	225	2986646
355L	250	3102728
355L	275	3507543
355L	315	4033675

**GST as applicable.

TB Position upto 225 frame, Top as standard,

TB Position from 250 to 355, RHS/LHS as standard, (Top on request)

TERRAMAX® TCA SERIES (IE3) UL CERTIFIED SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
(Other voltage / frequency combination on request)
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC®* 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55
- Certification : UL Certified

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	43432
80M	0.55	43432
80M	0.75	44865
80M	1.1	48867
90S	1.5	55973
90L	2.2	71909
100L	3	89488
100L	3.7	100916
132S	5.5	145542
132S	7.5	150607
160M	9.3	259678
160M	11	275043
160M	15	308292
160L	18.5	395977
180M	22	439489
200L	30	647177
200L	37	785894
225M	45	1083645
250M	55	1389144
280S	75	2026972
280M	90	2338194
315S	110	2924904
315M	125	3353792
315M	132	3513063
315L	160	3920824
315L	180	4127475
315L	200	4446657
355M	225	5064047
355M	250	5360406
355M	275	5428098
355L	315	5944479
355L	355	7379661
355L	375	7768082

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	46031
80M	0.55	46031
80M	0.75	47779
90S	1.1	58175
90L	1.5	67719
100L	2.2	80634
100L	3	96528
112M	3.7	102136
132S	5.5	148115
132M	7.5	175026
160M	9.3	273028
132M	9.3	207425
160M	11	282440
160L	15	344379
180M	18.5	421513
180L	22	461629
200L	30	636906
225S	37	853577
225M	45	1034690
250M	55	1265817
280S	75	1799919
280M	90	2096546
315S	110	2446929
315M	125	2787477
315M	132	2867219
315L	160	3694841
315L	180	4293396
315L	200	4472842
355M	225	5281694
355M	250	5632187
355L	275	5707008
355L	315	6404134
355L	355	7880223
355L	375	8031766
355L	400	8183309

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90S	0.75	61940
90L	1.1	67719
100L	1.5	103993
112M	2.2	109747
132S	3.7	161796
132M	5.5	198785
160M	7.5	283554
160L	9.3	308981
160L	11	349099
180L	15	476585
200L	18.5	609666
200L	22	670581
225M	30	1004926
250M	37	1299476
280S	45	1860829
280M	55	2088273
315S	75	2350941
315M	90	2874705
315SM	110	3205583
315L	125	3924561
315L	132	3929140
315L	160	4073469
355M	180	5473907
355M	200	5844003
355L	225	6197564
355L	250	6438443
355L	275	7278472
355L	315	8139329

**GST as applicable.

TB Position upto 225 frame, Top as standard, (LHS/RHS on request)

TB Position from 250 to 355, RHS/LHS as standard, (Top on request)

FLAME PROOF (IE2) GAS GROUP I, IIA IIB SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10% (550 volts for Gas Group I)
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC[®]* 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55 (up to IP66 on request)
- Enclosure : IS/IEC:60079-1
- Suitable for : Gas groups I, IIA & IIB, Zone 1, 2

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	41614
80	0.55	46580
80	0.75	47963
90	1.1	56109
90	1.5	57336
100	2.2	75305
112	3.7	100076
132	5.5	141236
132	7.5	155958
160L	9.3	276052
160L	11	281686
160L	15	310704
180L	18.5	352832
180L	22	418585
200L	30	563473
225M	37	729746
225M	45	926377
250M	55	1185794
280M	75	1457522
280M	90	1576060
315M	110	1746655
315M	125	2039427
315M	132	2070941
315L	150	2248940
315L	160	2347862
315L	180	2814924

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	40916
80	0.55	45181
80	0.75	46950
90	1.1	57378
90	1.5	60903
100	2.2	77409
112	3.7	98037
132	5.5	134830
132	7.5	153562
160L	9.3	238123
160L	11	242982
160L	15	295496
180L	18.5	335484
180L	22	398812
200L	30	535069
225M	37	666560
225M	45	842862
250M	55	1079596
280M	75	1323063
280M	90	1348714
315M	110	1610170
315M	125	1789425
315M	132	1948694
315L	150	2017386
315L	160	2046317
315L	180	2449395
315L	200	2793410

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

FLAME PROOF (IE2) GAS GROUP I, IIA IIB SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10% (550 volts for Gas Group I)
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC[®]* 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55 (up to IP66 on request)
- Enclosure : IS/IEC:60079-1
- Suitable for : Gas groups I, IIA & IIB, Zone 1, 2

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	47478
80	0.55	51087
90	0.75	59447
90	1.1	61230
100	1.5	88608
112	2.2	102945
132M	3.7	136385
132M	5.5	165259
160L	7.5	261714
160L	9.3	294483
160L	11	306595
180L	15	409954
200L	18.5	509860
200L	22	553059
225M	30	867229
250M	37	1113435
280M	45	1293119
280M	55	1394807
315M	75	1635493
315M	90	1917864
315M	110	2102640
315L	125	2390376
315L	132	2548702
355M	150	2665656
355M	160	3071573

8 POLE, 750 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90L	0.37	57036
90L	0.55	61716
100L	0.75	74670
100L	1.1	86838
112M	1.5	104172
132M	2.2	137669
160L	3.7	222667
160L	5.5	261643
160L	7.5	319135
180L	11	427331
200L	15	577611
225M	18.5	717049
225M	22	943710
250M	30	1158987
280M	37	1487310
280M	45	1518881
315M	55	1850657
315M	75	2167523
315L	90	2372514
315L	110	2774650
355M	132	3768381
355M	160	4113374
355L	180	4378752
355L	200	4776821
355L	250	8492126

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

FLAME PROOF (IE3) GAS GROUP I, IIA IIB SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS
U

SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10% (550 volts for Gas Group I)
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC[®]* 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55 (up to IP66 on request)
- Enclosure : IS/IEC:60079-1
- Suitable for : Gas groups I, IIA & IIB, Zone 1, 2

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	43213
80	0.55	47634
80	0.75	49533
90	1.1	58962
90	1.5	64212
100	2.2	81646
112	3.7	103431
132	5.5	142206
132	7.5	161964
160L	9.3	252070
160L	11	256235
160L	15	311632
180L	18.5	353816
180L	22	420540
200L	30	564214
225M	37	734881
225M	45	929230
250M	55	1138472
280M	75	1395178
280M	90	1422199
315M	110	1697979
315M	125	2027683
315M	132	2142643
315L	150	2152116
315L	160	2193905
315L	180	2576122
315L	200	3071430
355M	225	5537132
355M	250	5679109

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	50103
80	0.55	51487
90	0.75	52942
90	1.1	64541
100	1.5	93415
112	2.2	108552
132M	3.7	143803
132M	5.5	174219
160L	7.5	271543
160L	9.3	308864
160L	11	323273
180L	15	425333
200L	18.5	528892
200L	22	573702
225M	30	914507
250M	37	1174180
280M	45	1363664
280M	55	1470875
315M	75	1724728
315M	90	1989552
315M	110	2211406
315L	125	2554925
315L	132	2680521
355M	150	3208298
355M	160	3377156
355M	180	4675801
355L	200	4806097
355L	225	5272709
355L	250	5785981

8 POLE, 750 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90L	0.37	62740
90L	0.55	67888
100L	0.75	82136
100L	1.1	95523
112M	1.5	114590
132M	2.2	151436
160L	3.7	244934
160L	5.5	287806
160L	7.5	351049
180L	11	470063
200L	15	635372
225M	18.5	788753
225M	22	1038081
250M	30	1274886
280M	37	1636040
280M	45	1670769
315M	55	2035722
315M	75	2384276
315L	90	2609766
315L	110	3052115
355M	132	3633470
355M	160	4086836
355L	180	4145219
355L	200	4232794
355L	250	4524710

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

FLAME PROOF (IE2) GAS GROUP IIC SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class F with temperature rise limited to class B
- Ambient : 50°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : IS 12615:2018 or IEC[®]* 60034 - 30 -1 (2014)
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP55 (up to IP66 on request)
- Enclosure : IS/IEC:60079-1
- Suitable for : Gas groups IIC, Zone 1, 2

4 POLE, 1500 RPM			
Item Code	Frame Size	Kilowatt	Price** per item (₹)
As Applicable	80	0.37	51145
As Applicable	80	0.55	56476
As Applicable	80	0.75	58688
As Applicable	90	1.1	71723
As Applicable	90	1.5	76129
As Applicable	100	2.2	96761
As Applicable	112	3.7	122547
As Applicable	132	5.5	168538
As Applicable	132	7.5	191952
As Applicable	160L	9.3	297653
As Applicable	160L	11	303728
As Applicable	160L	15	369370

6 POLE, 1000 RPM			
Item Code	Frame Size	Kilowatt	Price** per item (₹)
As Applicable	80	0.37	59347
As Applicable	80	0.55	63859
As Applicable	90	0.75	74309
As Applicable	90	1.1	76538
As Applicable	100	1.5	110760
As Applicable	112	2.2	128682
As Applicable	132M	3.7	170482
As Applicable	132M	5.5	206574
As Applicable	160L	7.5	327142
As Applicable	160L	9.3	368104
As Applicable	160L	11	383244

**GST as applicable.

CRANE DUTY (KS) SLIPRING MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class F with temperature rise limited to class B
- Ambient : 47°C (up to 315 Fr. / For 355 Fr. it is 40°C)
- Cooling : IC411
- Duty : S3, CDF: 40%, Starts/hr: 6
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting : Horizontal foot mounted (B3)
- Performance : Conforming to IS/IEC:60034-1
- Frame dimensions : Conforming to IS 1231
- Protection : IP55

6 POLE, 1000 RPM			
Item Code	Frame Size	Kilowatt	Price** per item (₹)
AL08D1630MFAFTOAOO	KS112M	2	132162
AL08D2130MFAFTOAOO	KS132MA	3	174020
AL08D2330MFAFTOAOO	KS132MC	5.1	207845
AL08D2430MFAFTOAOO	KS160M	7	235864
AL08D2930MFAFTOAOO	KS160L	10	291759
AL08D3530MFAFTOAOO	KS180L	15	477240
AL08D4030MFAFTOAOO	KS200L	23	627417
AL08D4630MFAFTOAOO	KS225SA	25	738284
AL08D4730MFAFTOAOO	KS225SB	28.5	775952
AL08D4930MFAFTOAOO	KS225MA	30	911076
AL08D5230MFAFTOAOO	KS225MB	36	957559
AL08D5330MFAFTOAOO	KS250S	44	1196890
AL08D5630MFAFTOAOO	KS250M	50.2	1444511
As Applicable	KS280S	63	1588974
As Applicable	KS280M1	76	1857188
As Applicable	KS280M2	76	1857188
As Applicable	KS315SA	102	2220270
As Applicable	KS315SB	106	2263382
As Applicable	KS315MA	120	2395194
As Applicable	KS315MB	134	2517397
As Applicable	KS355S	145	2883947
As Applicable	KS355M	170	2979373
As Applicable	KS355LA	200	3523806
As Applicable	KS355LB	225	3557094

8 POLE, 750 RPM			
Item Code	Frame Size	Kilowatt	Price** per item (₹)
AL08D2140MFAFTOAOO	KS132MA	2.2	238843
AL08D2340MFAFTOAOO	KS132MC	3.7	263214
AL08D2440MFAFTOAOO	KS160M	5.2	271985
AL08D2940MFAFTOAOO	KS160L	7.5	338708
AL08D3540MFAFTOAOO	KS180L	11.5	494221
AL08D4040MFAFTOAOO	KS200L	15.5	643850
AL08D4640MFAFTOAOO	KS225SA	20	796402
AL08D4740MFAFTOAOO	KS225SB	23	837035
AL08D4940MFAFTOAOO	KS225MA	25	957559
AL08D5240MFAFTOAOO	KS225MB	28.5	976152
AL08D5440MFAFTOAOO	KS250SA	30	1109292
As Applicable	KS250SB	37	1165889
AL08D5840MFAFTOAOO	KS250MB	43	1451884
As Applicable	KS280SA	51	1543236
As Applicable	KS280SB	54	1621973
As Applicable	KS280MA	64.5	1680630
As Applicable	KS280MB	69	1766377
As Applicable	KS315S	80	2368863
As Applicable	KS315MA	100	2571109
As Applicable	KS355SA	125	2763734
As Applicable	KS355SB	140	3095434
As Applicable	KS355M	160	3374169
As Applicable	KS355L	200	3487352

10 POLE, 600 RPM			
Item Code	Frame Size	Kilowatt	Price** per item (₹)
As Applicable	KS225S	16.7	785456
As Applicable	KS225M	22	920400
As Applicable	KS250SA	23	1119321
As Applicable	KS250SB	25	1176429
As Applicable	KS250M	28.5	1199273
As Applicable	KS280SA	40	1668868
As Applicable	KS280SB	46	1754015
As Applicable	KS280MA	50	1825884
As Applicable	KS280MB	57	1919041
As Applicable	KS315SA	60	2324553
As Applicable	KS315SB	67	2443153
As Applicable	KS315MA	75	2559901
As Applicable	KS355SA	88	2962322
As Applicable	KS355SB	100	3179614
As Applicable	KS355MA	100	3338595
As Applicable	KS355MB	125	3473675
As Applicable	KS355LA	125	3647360
As Applicable	KS355LB	160	3764631

**GST as applicable.

TERRAMAX® SCF SERIES (IE2) FIREFIGHTING MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class F with temperature rise limited to class F
- Ambient : 45°C
- Altitude : Less than 1000 MTR above M.S.L.
- Mounting : Horizontal foot mounted (B3)
- Performance : Conforming to IS 15999-1
- Frame dimensions : Conforming to IS 1231
- Protection : IP-55

2 POLE, 3000 RPM			
Item Code	Frame Size	Kilowatt	Price** per item (₹)
As Applicable	112M	5.5	58596
As Applicable	112M	7.5	80570
As Applicable	132M	9.3	115207
As Applicable	132M	11	128167
As Applicable	132M	15	164800
As Applicable	160L	22	201611
As Applicable	180L	30	273615
As Applicable	180L	37	360020
As Applicable	200L	45	413720
As Applicable	200L	55	527850
As Applicable	225M	55	556641
As Applicable	225M	60	584914
As Applicable	250M	75	684778
As Applicable	250M	90	898772
As Applicable	250M	110	1191229

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] SMOKE SPILL (IE2 - 250[°]C) SCS SERIES MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

■ Frame material/Enclosure	: Cast iron / Totally enclosed non ventilated (TENV)
■ Power supply	: AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
■ Insulation	: CLASS 'H'
■ Ambient	: 45°C
■ Cooling	: IC418 (AIR-OVER-MOTOR) / IC411
■ Duty	: S1
■ Altitude	: Less than 1000 mtr. Above M.S.L.
■ Mounting	: Horizontal foot mounted (B3)
■ Performance	: IS 12615:2018 OR IEC 60034 - 30 -1 (2014)
■ Protection	: IP-55
■ Temperature rise under normal running	: Limited to Class 'B' (on load with AFF)
■ Thermal capacity under abnormal condition	: 250°C for 2 hours
■ Specifications	: BS EN:12101-3

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	27016
80	0.55	27016
80	0.75	27016
80	1.1	29392
90	1.5	33771
90	2.2	43231
100	3.7	53730
132	5.5	91777
132	7.5	99381
160	9.3	171280
160	11	180423
160	15	194303
160	18.5	244066
180	22	274191
200	30	398784
200	37	484139
225	45	662828
250	55	872037

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	27665
80	0.55	27665
80	0.75	28039
90	1.1	34678
90	1.5	42051
100	2.2	50100
100	3	57883
112	3.7	63464
112	4	77020
132	5.5	88191
132	7.5	104191
132	9.3	115318
160	9.3	168221
160	11	169915
160	15	209718
180	18.5	268345
180	22	293935
200	30	401722
225	37	499755
225	45	591959
250	55	832361

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	33885
80	0.55	33885
90	0.75	33885
90	1.1	37169
100	1.5	53571
112	2.2	57085
132	3.7	88825
132	5.5	109274
160	7.5	174350
160	9.3	197866
160	11	214557
180	15	268085
200	18.5	379168
200	22	408270
225	30	620685
250	37	662868

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] SMOKE SPILL (IE3 - 250°C) TCS SERIES MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

■ Frame material/Enclosure	: Cast iron / Totally enclosed non ventilated (TENV)
■ Power supply	: AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
■ Insulation	: CLASS 'H'
■ Ambient	: 45°C
■ Cooling	: IC418 (AIR-OVER-MOTOR) / IC411
■ Duty	: S1
■ Altitude	: Less than 1000 mtr. Above M.S.L.
■ Mounting	: Horizontal foot mounted (B3)
■ Performance	: IS 12615:2018 OR IEC 60034 - 30 -1 (2014)
■ Protection	: IP-55
■ Temperature rise under normal running	: Limited to Class 'B' (on load with AFF)
■ Thermal capacity under abnormal condition	: 250°C for 2 hours
■ Specifications	: BS EN:12101-3

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	29741
80	0.75	29741
80	1.1	32438
90	1.5	37169
90	2.2	47622
100	3	65137
100	3.7	67091
132	5.5	97046
132	7.5	100103
160	9.3	172287
160	11	186724
160	15	209297
160	18.5	268827
180	22	298367
200	30	439363
200	37	533538

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	32387
80	0.75	32387
90	1.1	37795
90	1.5	45953
100	2.2	54745
112	3.7	66308
132	5.5	98487
132	7.5	118951
160	9.3	185356
160	11	191746
160	15	233798
180	18.5	286162
180	22	313396
200	30	432390
225	37	575882

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	40283
90	0.75	40283
90	1.1	44030
100	1.5	68959
112	2.2	71554
132	3.7	100821
132	5.5	126190
160	7.5	192503
160	9.3	209765
160	11	237001
180	15	323550
200	18.5	413898
200	22	455251
225	30	677992
250	37	856328

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] SMOKE SPILL (IE2 - 300°C) SCS SERIES MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

■ Frame material/Enclosure	: Cast iron / Totally enclosed non ventilated (TENV)
■ Power supply	: AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
■ Insulation	: CLASS 'H'
■ Ambient	: 45°C
■ Cooling	: IC418 (AIR-OVER-MOTOR) / IC411
■ Duty	: S1
■ Altitude	: Less than 1000 mtr. Above M.S.L.
■ Mounting	: Horizontal foot mounted (B3)
■ Performance	: IS 12615:2018 OR IEC 60034 - 30 -1 (2014)
■ Protection	: IP-55
■ Temperature rise under normal running	: Limited to Class 'B' (on load with AFF)
■ Thermal capacity under abnormal condition	: 300°C for 2 hours
■ Specifications	: BS EN:12101-3

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	27540
80	0.55	27540
80	0.75	27540
80	1.1	29963
90	1.5	34426
90	2.2	44071
100	3.7	54773
132	5.5	89228
132	7.5	101310
160	9.3	174606
160	11	183926
160	15	198076
160	18.5	248805
180	22	279515
200	30	406527
200	37	493540
225	45	675698
250	55	888970

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	28202
80	0.55	28202
80	0.75	28583
90	1.1	35351
90	1.5	42867
100	2.2	51073
100	3	60801
112	3.7	64697
112	4	80101
132	5.5	89903
132	7.5	106214
132	9.3	126445
160	9.3	171487
160	11	173214
160	15	213791
180	18.5	273555
180	22	299643
200	30	409522
225	37	509459
225	45	603453
250	55	848524

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	34543
80	0.55	34543
90	0.75	34543
90	1.1	37890
100	1.5	54612
112	2.2	58193
132	3.7	90550
132	5.5	111396
160	7.5	177736
160	9.3	201708
160	11	218723
180	15	273291
200	18.5	386530
200	22	416198
225	30	632738
250	37	662868

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] SMOKE SPILL (IE3 - 300°C) TCS SERIES MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

■ Frame material/Enclosure	: Cast iron / Totally enclosed non ventilated (TENV)
■ Power supply	: AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
■ Insulation	: CLASS 'H'
■ Ambient	: 45°C
■ Cooling	: IC418 (AIR-OVER-MOTOR) / IC411
■ Duty	: S1
■ Altitude	: Less than 1000 mtr. Above M.S.L.
■ Mounting	: Horizontal foot mounted (B3)
■ Performance	: IS 12615:2018 OR IEC 60034 - 30 -1 (2014)
■ Protection	: IP-55
■ Temperature rise under normal running	: Limited to Class 'B' (on load with AFF)
■ Thermal capacity under abnormal condition	: 300°C for 2 hours
■ Specifications	: BS EN:12101-3

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	30319
80	0.75	30319
80	1.1	33068
90	1.5	37890
90	2.2	48547
100	3	67091
100	3.7	68394
132	5.5	94350
132	7.5	102046
160	9.3	175632
160	11	190349
160	15	213361
160	18.5	274047
180	22	304161
200	30	447894
200	37	543898

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	33016
80	0.75	33016
90	1.1	38529
90	1.5	46846
100	2.2	55808
112	3.7	67596
132	5.5	100399
132	7.5	121260
160	9.3	188955
160	11	195469
160	15	238337
180	18.5	291718
180	22	319481
200	30	440786
225	37	587065

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	41066
90	0.75	41066
90	1.1	44885
100	1.5	70298
112	2.2	72944
132	3.7	102778
132	5.5	128641
160	7.5	196241
160	9.3	213838
160	11	241603
180	15	329832
200	18.5	421935
200	22	464091
225	30	691157
250	37	872956

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] SMOKE SPILL (IE2 - 400°C) SCS SERIES MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

■ Frame material/Enclosure	: Cast iron / Totally enclosed non ventilated (TENV)
■ Power supply	: AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
■ Insulation	: CLASS 'H'
■ Ambient	: 45°C
■ Cooling	: IC418 (AIR-OVER-MOTOR) / IC411
■ Duty	: S1
■ Altitude	: Less than 1000 mtr. Above M.S.L.
■ Mounting	: Horizontal foot mounted (B3)
■ Performance	: IS 12615:2018 OR IEC 60034 - 30 -1 (2014)
■ Protection	: IP-55
■ Temperature rise under normal running	: Limited to Class 'B' (on load with AFF)
■ Thermal capacity under abnormal condition	: 400°C for 2 hours
■ Specifications	: BS EN:12101-3

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	34402
80	0.55	34402
80	0.75	34402
80	1.1	37380
90	1.5	44193
90	2.2	55107
100	3.7	71902
132	5.5	116191
132	7.5	129930
160	9.3	219238
160	11	241940
160	15	254629
160	18.5	319582
180	22	367507
200	30	534549
200	37	619546
225	45	815788
250	55	1073276

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	34402
80	0.55	34402
80	0.75	34918
90	1.1	46381
90	1.5	52309
100	2.2	64124
100	3	74085
112	3.7	84953
112	4	98149
132	5.5	115253
132	7.5	136397
132	9.3	174878
160	9.3	215321
160	11	222571
160	15	280481
180	18.5	350197
180	22	404245
200	30	550020
225	37	615083
225	45	728564
250	55	1024445

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.37	39170
80	0.55	39460
90	0.75	43982
90	1.1	48258
100	1.5	70206
112	2.2	76082
132	3.7	123870
132	5.5	149584
160	7.5	218385
160	9.3	259300
160	11	268708
180	15	359322
200	18.5	496359
200	22	542871
225	30	763921
250	37	980489

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] SMOKE SPILL (IE3 - 400°C) TCS SERIES MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

■ Frame material/Enclosure	: Cast iron / Totally enclosed non ventilated (TENV)
■ Power supply	: AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
■ Insulation	: CLASS 'H'
■ Ambient	: 45°C
■ Cooling	: IC418 (AIR-OVER-MOTOR) / IC411
■ Duty	: S1
■ Altitude	: Less than 1000 mtr. Above M.S.L.
■ Mounting	: Horizontal foot mounted (B3)
■ Performance	: IS 12615:2018 OR IEC 60034 - 30 -1 (2014)
■ Protection	: IP-55
■ Temperature rise under normal running	: Limited to Class 'B' (on load with AFF)
■ Thermal capacity under abnormal condition	: 400°C for 2 hours
■ Specifications	: BS EN:12101-3

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	36663
80	0.75	37873
80	1.1	41251
90	1.5	47250
90	2.2	60702
100	3	85425
100	3.7	89783
132	5.5	122860
132	7.5	130874
160	9.3	231030
160	11	244698
160	15	267901
160	18.5	334267
180	22	381909
200	30	575775
200	37	682930

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	38857
80	0.75	41520
90	1.1	50552
90	1.5	58847
100	2.2	70068
112	3.7	90867
132	5.5	128709
132	7.5	152096
160	9.3	237256
160	11	245435
160	15	306385
180	18.5	375009
180	22	410700
200	30	566638
225	37	708778

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80	0.55	44341
90	0.75	53824
90	1.1	58847
100	1.5	87786
112	2.2	95368
132	3.7	140597
132	5.5	167804
160	7.5	252271
160	9.3	274893
160	11	310584
180	15	414144
200	18.5	542405
200	22	582723
225	30	834452
250	37	1053942

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] CRANE DUTY (IE2) SCV SERIES SQUIRREL CAGE MOTORS

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS
U

SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled squirrel cage, crane duty
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class 'F' with temperature rise limited to class 'B'
- Ambient : 50°C
- Altitude : Less than 1000 mtr. Above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : Conforming to IS/IEC:60034-1
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP-55
- Drive : VVVF / DOL
- Duty : S4
- CDF & Start/Hr : 40%, 150 S/Hr

4 POLE, 1500 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.75	29830
80M	0.85	30409
80M	1.10	31356
80M	1.16	31965
90S	1.50	32848
90S	1.69	33486
90L	2.20	35934
90L	2.32	36631
100L	3.70	48414
100L	4.65	49354
112M	5.50	60655
112M	5.61	61832
112M	6.05	63305
132S	7.50	83491
132S	8.43	85112
132M	9.30	106052
132M	11.50	167750
132M	14.29	176137
160M	15.00	182554
160M	15.98	186099
160L	18.50	196399
160L	22.50	274824
180M	27.00	280160
180L	27.00	295671
180L	32.17	301412
200L	37.00	390664
200L	43.11	507226
225S	50.14	532587

6 POLE, 1000 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.55	27759
80M	0.75	28288
90S	1.1	29081
90S	1.2	30403
90L	1.5	31908
90L	1.7	33358
100L	2.2	45093
100L	2.3	47143
112M	3.7	48867
112M	4.6	73297
132S	5.5	79560
132S	5.7	83176
132M	7.5	96077
132M	8.5	100444
160M	9.3	140266
160M	10.7	146642
160L	11	162673
160L	14	172589
160L	15	177296
160L	15.8	180434
180L	18.5	225422
180L	22	235668

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] CRANE DUTY (IE3) TCV SERIES SQUIRREL CAGE MOTORS

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron / Totally enclosed fan cooled squirrel cage, crane duty
- Power supply : AC 3 Phase, 415 volts +/- 10%, 50 hz +/- 5%, combined variation 10%
- Insulation : Class 'F' with temperature rise limited to class 'B'
- Ambient : 50°C
- Altitude : Less than 1000 mtr. Above M.S.L.
- Mounting (Std.) : Horizontal foot mounted (B3) - Other mountings on request
- Performance : Conforming to IS/IEC:60034-1
- Frame dimensions : Conforming to IS 1231 / IS 2223
- Protection : IP-55
- Drive : VVVF / DOL
- Duty : S4
- CDF & Start/Hr : 40%, 150 S/Hr

4 POLE, 1500 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.75	34304
80M	0.85	34970
80M	1.10	36060
80M	1.16	37142
90S	1.50	37775
90S	1.69	38508
90L	2.20	41324
90L	2.32	42126
100L	3.70	55676
100L	4.65	56757
112M	5.50	69753
112M	5.61	71107
112M	6.05	72800
132S	7.50	96014
132S	8.43	97879
132M	9.30	121960
132M	11.50	128058
132M	14.29	134461
160M	15.00	209937
160M	15.98	214014
160L	18.50	225859
160L	22.50	316047
180M	27.00	322184
180L	27.00	340021
180L	32.17	346624
200L	37.00	449263
200L	43.11	583309
225S	50.14	612475

6 POLE, 1000 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.55	36355
80M	0.75	37191
90S	1.1	38938
90S	1.2	39694
90L	1.5	45089
90L	1.7	45965
100L	2.2	58771
100L	2.3	59913
112M	3.7	70029
112M	4.6	71389
132S	5.5	102875
132S	5.7	104873
132M	7.5	114546
132M	8.5	116770
160M	9.3	187786
160M	10.7	191432
160L	11	232849
160L	14	237370
160L	15	242009
160L	15.8	242973
180L	18.5	337918
180L	22	347983

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

TERRAMAX® EX'TD' DUST PROOF - IIIC MOTOR TCT SERIES (ATEX / IECEx CERTIFIED)

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron with integrally cast feet
- Power supply : Available for voltages between 200 V to 720 V and frequency 50 or 60 Hz
- Insulation : Class 'F' with temperature rise limited to class 'B'
- Ambient : -20 to 50°C (higher ambient on request)
- Altitude : Less than 1000 mtr. Above M.S.L.
- Mounting : Horizontal foot mounted (B3)
- Standards : Confirms to IEC 60034-1, IS IEC:60079-7, IEC60079-31, IEC60079-15
- Frame dimensions : Conforming to IS : 1231
- Protection : IP 66
- Zone : 21 & 22
- Certification : Ex 'tb' IIIC T135 Db & Ex 'tc' IIIC T135 Dc

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	33810
80M	0.55	33810
80M	0.75	34925
80M	1.1	38041
90S	1.5	43573
90L	2.2	55978
100L	3	75996
100L	3.7	78560
132S	5.5	113300
132S	7.5	117242
160M	9.3	202150
160M	11	214111
160M	15	239994
160L	18.5	308254
180M	22	342127
200L	30	503804
200L	37	611790
225M	45	787340
250M	55	1009306
280S	75	1367535
280M	90	1577507
315S	110	1973342
315M	125	2262700
315M	132	2370154
315L	160	2645258
315L	180	2784679
315L	200	3000021
355M	225	3416556
355M	250	3616501
355M	275	3662170
355L	315	4010556
355L	355	4978829
355L	375	5240885

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	35833
80M	0.55	35833
80M	0.75	37194
90S	1.1	45287
90L	1.5	52717
100L	2.2	62770
100L	3	77851
112M	3.7	79509
132S	5.5	115301
132M	7.5	136252
160M	9.3	212543
160M	11	219869
160L	15	268087
180M	18.5	328133
180L	22	359362
200L	30	495808
225S	37	620181
225M	45	751770
250M	55	919701
280S	75	1214350
280M	90	1414475
315S	110	1650867
315M	125	1880625
315M	132	1934424
315L	160	2492794
315L	180	2896621
315L	200	3017689
355M	225	3563396
355M	250	3799862
355L	275	3850341
355L	315	4320671
355L	355	5316543
355L	375	5418784
355L	400	5521025

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90S	0.75	48217
90L	1.1	52717
100L	1.5	80955
112M	2.2	85434
132S	3.7	125953
132M	5.5	154747
160M	7.5	220736
160L	9.3	240530
160L	11	271762
180L	15	371005
200L	18.5	474604
200L	22	522024
225M	30	730145
250M	37	944156
280S	45	1255444
280M	55	1408893
315S	75	1586107
315M	90	1939475
315SM	110	2162707
315L	125	2647779
315L	132	2650869
315L	160	2748243
355M	180	3693075
355M	200	3942768
355L	225	4181304
355L	250	4343819
355L	275	4910560
355L	315	5013844

**GST as applicable.

please contact Marathon Electric Motors (India) Ltd.

TERRAMAX® EX'EC' NON SPARKING MOTORS TCN SERIES (ATEX / IECEX CERTIFIED)

marathon
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Frame material / Enclosure : Cast iron with integrally cast feet
- Power supply : Available for voltages between 200 V to 720 V and frequency 50 or 60 Hz
- Insulation : Class 'F' with temperature rise limited to class 'B'
- Ambient : -20 to 50°C (higher ambient on request)
- Altitude : Less than 1000 mtr. Above M.S.L.
- Mounting : Horizontal foot mounted (B3)
- Standards : Confirms to IEC 60034-1, IS IEC:60079-7
- Frame dimensions : Conforming to IS : 1231
- Protection : IP 55 (Higher IP on request)
- Zone : 2
- Certification : Ex 'ec' IIC T3 Gc

2 POLE, 3000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	27772
80M	0.55	27772
80M	0.75	28688
80M	1.1	31248
90S	1.5	35793
90L	2.2	45983
100L	3	62426
100L	3.7	64531
132S	5.5	93067
132S	7.5	96306
160M	9.3	166052
160M	11	175877
160M	15	197138
160L	18.5	253209
180M	22	281033
200L	30	413839
200L	37	502542
225M	45	646743
250M	55	829072
280S	75	1123333
280M	90	1295810
315S	110	1620959
315M	125	1858646
315M	132	1946913
315L	160	2172890
315L	180	2287415
315L	200	2464304
355M	225	2806457
355M	250	2970697
355M	275	3008211
355L	315	3294385
355L	355	4089753
355L	375	4305012

4 POLE, 1500 RPM		
Frame Size	Kilowatt	Price** per item (₹)
80M	0.37	29434
80M	0.55	29434
80M	0.75	30552
90S	1.1	37200
90L	1.5	43303
100L	2.2	51562
100L	3	63950
112M	3.7	65312
132S	5.5	94712
132M	7.5	111921
160M	9.3	174588
160M	11	180607
160L	15	220214
180M	18.5	269537
180L	22	295190
200L	30	407271
225S	37	509434
225M	45	617527
250M	55	755469
280S	75	997501
280M	90	1161890
315S	110	1356070
315M	125	1544799
315M	132	1588991
315L	160	2047653
315L	180	2379367
315L	200	2478815
355M	225	2927075
355M	250	3121316
355L	275	3162780
355L	315	3549122
355L	355	4367160
355L	375	4451144
355L	400	4535128

6 POLE, 1000 RPM		
Frame Size	Kilowatt	Price** per item (₹)
90S	0.75	39607
90L	1.1	43303
100L	1.5	66499
112M	2.2	70179
132S	3.7	103461
132M	5.5	127113
160M	7.5	181319
160L	9.3	197579
160L	11	223232
180L	15	304754
200L	18.5	389852
200L	22	428804
225M	30	599763
250M	37	775556
280S	45	1031258
280M	55	1157305
315S	75	1302873
315M	90	1593140
315SM	110	1776510
315L	125	2174961
315L	132	2177500
315L	160	2257485
355M	180	3033597
355M	200	3163384
355L	225	3434643
355L	250	3568137
355L	275	4033675
355L	315	4638726

**GST as applicable.

please contact Marathon Electric Motors (India) Ltd.

TERRAMAX[®] STANDARD BRAKE MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

CONTENTS



SPECIFICATIONS

- Brake Torque : 10 to 150 (Based on the frame size & rating)
- Brake Size : 10 to 18 (Based on the frame size & rating)
- Barke Rectifier (I/P | O/P) : AC IN 415V DC OUT 190 V
- Ambient : 50°C (higher ambient on request)
- Insulation : Class F with class B temperature rise
- Standards : Meets efficiency requirement as per IS:12615-2018 – IE2 and IE3 efficiency at Equiv. S1 Duty in case of line operated motors
- Starting Method : Suitable for DOL & VFD starting.

4 POLE, 1500 RPM			
Frame Size	KW	Brake Size (Torque)	Final Price** per item (₹)
80M	0.37	8 (10Nm)	51612
80M	0.55	8 (10Nm)	51612
80M	0.75	8 (10Nm)	51771
90S	1.1	10 (16Nm)	67309
90L	1.5	10 (16Nm)	69556
100L	2.2	12 (32Nm)	83482
100L	3	12 (32Nm)	85311
112M	3.7	14 (60Nm)	96126
112M	4	14 (60Nm)	115724
132S	5.5	16 (100Nm)	130572
132M	7.5	16 (100Nm)	141128
132M	9.3	16 (100Nm)	169036
160M	9.3	18 (150Nm)	219734
160M	11	18 (150Nm)	225776
160L	15	18 (150Nm)	287599

6 POLE, 1000 RPM			
Frame Size	KW	Brake Size (Torque)	Final Price** per item (₹)
80M	0.37	8 (10Nm)	52837
80M	0.55	8 (10Nm)	53427
90S	0.75	10 (16Nm)	68922
90L	1.1	10 (16Nm)	71485
100L	1.5	12 (32Nm)	84604
112M	2.2	14 (60Nm)	94354
112M	3	14 (60Nm)	131868
132S	3.7	16 (100Nm)	134863
132M	5.5	16 (100Nm)	142683
160M	7.5	18 (150Nm)	229477
160M	9.3	18 (150Nm)	284819
160L	11	18 (150Nm)	292423

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

Brake as per Marathon's approved vendor. For EMCO add 5% extra on LP

TERRAMAX[®] CRANE DUTY SCV BRAKE MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

- Brake Torque : 10 to 150 (Based on the frame size & rating)
- Brake Size : 10 to 18 (Based on the frame size & rating)
- Brake Rectifier (I/P | O/P) : AC IN 415V DC OUT 190 V
- Ambient : 50°C (higher ambient on request)
- Insulation : Class F with class B temperature rise
- Standards : Meets efficiency requirement as per IS:12615-2018 – IE2
- Starting Method : Suitable for DOL & VFD starting.
- Duty : S1
- CDR & Start/HR : 40%, 150 S/Hr

4 POLE, 1500 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.37	59354
80M	0.55	59354
80M	0.75	59537
90S	1.10	77406
90L	1.50	79989
100L	2.20	96004
100L	3.00	98107
112M	3.70	110545
112M	4.00	133083
132S	5.50	150158
132M	7.50	162297
132M	9.30	194392
160M	9.30	252694
160M	11.00	259642
160L	15.00	330738

6 POLE, 1000 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.37	60762
80M	0.55	61441
90S	0.75	79261
90L	1.10	82208
100L	1.50	97295
112M	2.20	108507
112M	3.00	151648
132S	3.70	155093
132M	5.50	164085
160M	7.50	263898
160M	9.30	327541
160L	11.00	336287

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

Brake as per Marathon's approved vendor. For EMCO add 5% extra on LP.

For higher output crane duty rating combination,
please connect with engineering for suitable brake size selection.

TERRAMAX[®] CRANE DUTY TCV BRAKE MOTOR

marathon[™]
WEG Group

LVMP 113 : 07-08-2026

SPECIFICATIONS

- Brake Torque : 10 to 150 (Based on the frame size & rating)
- Brake Size : 10 to 18 (Based on the frame size & rating)
- Brake Rectifier (I/P | O/P) : AC IN 415V DC OUT 190 V
- Ambient : 50°C (higher ambient on request)
- Insulation : Class F with class B temperature rise
- Standards : Meets efficiency requirement as per IS:12615-2018 – IE3 efficiency
- Starting Method : Suitable for DOL & VFD starting.
- Duty : S1
- CDR & Start/HR : 40%, 150 S/Hr

4 POLE, 1500 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.37	68257
80M	0.55	68257
80M	0.75	68467
90S	1.10	89017
90L	1.50	91988
100L	2.20	110404
100L	3.00	112824
112M	3.70	127126
112M	4.00	153045
132S	5.50	172682
132M	7.50	186641
132M	9.30	223551
160M	9.30	290598
160M	11.00	298589
160L	15.00	380349

6 POLE, 1000 RPM		
Frame Size	KW	Final Price** per item (₹)
80M	0.37	69877
80M	0.55	70657
90S	0.75	91150
90L	1.10	94539
100L	1.50	111889
112M	2.20	124783
112M	3.00	174395
132S	3.70	178356
132M	5.50	188698
160M	7.50	303483
160M	9.30	376673
160L	11.00	386730

**GST as applicable.

NOTE: For higher ratings, please contact Marathon Electric Motors (India) Ltd.

Brake as per Marathon's approved vendor. For EMCO add 5% extra on LP.

For higher output crane duty rating combination,
please connect with engineering for suitable brake size selection.

TERMS AND CONDITIONS OF SALE

Standard Terms and Conditions of Sale [Click](#)

Additional Terms and Conditions

- *This price list is effective from 07/08/2026.*
- *This version LVMP 113 : 07-08-2026 supersede all earlier versions.*
- *All prices are subject to change without notice.*
- *All prices are Ex-works.*
- *Prices are exclusive of GST which will be charged extra at actuals.*
- *Insurance against loss or damage in transit, if required, will be extra at customer's cost.*
- *General frame sizes are subject to change since improvements are made from time to time.*

For more information please contact us.

Phone: +91 33 4403 0501

Email: Contact.Marathon@weg.net

The scope of WEG Group solutions
is not limited to products and solutions
presented in this catalogue.

To see our portfolio, contact us.

**For WEG's worldwide
operations visit our website**



www.weg.net

www.marathonelectric.in

marathon™
WEG Group



Kolkata Plant

1, Taratala Road, Kolkata,
West Bengal, 700024

Phone:

033-44030501/033-44030502

Ahmedabad Plant

B1/A, Gallops Industrial Park, Rajoda,
Ahmedabad, Gujarat, 382220

Email: Contact.Marathon@weg.net | serviceamd@weg.net

Website: www.marathonelectric.in

Cod: 50144509 | Rev: 01 | Date (m/y): 08/2026.

The values shown are subject to change without prior notice.
The information contained is reference values.