




Pump Curve



Overview

- Heavy duty cast iron submersible water pump
- High maximum submersion depth due to mechanical seal resistant to high pressure.
- Semi-open impeller made of high chrome alloy matched with ductile iron wear plate achieves superior durability.
- Effective motor cooling due to discharge channel cast as part of the motor housing.
- Thermally protected motor when used with approved control panel
- Approved control panel recommended
- Available with bare end or plug

Applications



- Mine & quarry dewatering
- Lagoon transfer
- Washplant feed
- Reservoir & pond dewatering
- Water discharge

About Audex

Audex are respected manufacturers of industrial submersible and vac-prime self-priming dewatering pumps. Our pumps have been specifically developed for use in the toughest and most abrasive of applications and environments. Trusted by operators of quarries, mines and recycling facilities, Audex pumps represent quality and reliability giving you superior performance and reduced downtime. Pumps that suit your application better because they have been designed with your industry in mind.

Specification

Model	AS 8-7500 TC
Discharge Size	8" / 200mm
Volts / Phases / Hertz	575 / 3 / 60
Motor Power	100HP / 75kW
Shaft Speed	3450 RPM
Max Head	255ft / 78m
Max Flow Capacity	1532 gpm / 5800 lpm
Strainer Hole Size	25/32" / 20mm
Solids Passage	25/32" / 20mm
Max Water Temperature	104°F / 40°C
Cable Length	66ft / 20m
Cable Type	Servoflex 584
FLA / LRA	94.1 / 565
Recommended Generator Size	450kW
Electrical Tolerance	+/- 10% V
Net Weight (N.W)	1940 lbs / 880kg
Gross Weight (G.W)	2050 lbs / 930kg
Unit Dimensions	71.4 x 24.4 x 35.8" / 1815 x 620 x 910mm
Product Code	



Materials of Construction

Upper cover	Cast iron
Motor body	Cast iron
Outer casing	Steel
Volute	Cast iron
Impeller	High chrome
Inlet plate	Ductile iron
Strainer	Steel
Shaft	304 Stainless Steel
Mechanical seal	TC/SiC//SiC/SiC

Dimensions

D	21.6"	550mm
H1	50.3"	1280mm
W1	7.87"	200mm
N.W	1940 lbs	880kg
G.W	2050 lbs	930kg
Dimensions	71.4 x 24.4 x 35.8"	1815 x 620 x 910mm

C.W.L Continuous running water level