

INTERIOR

ARCHITECTURAL FILM

STRADA

Decorative - Lines — Interior Application, Depoli From Outside

The Strada decorative film, featuring bands, allows you to effectively partitions.

- 90% UV rejection with engineered light control
- Retains 54% visible light transmission
- Engineered and certified for professional interior installation
- 90% UV rejection helps protect interiors and furnishings from fading
- Depoli finish, engineered for interior application

Key Strengths



90%

UV Rejection



54%

Visible Light Transmission



5 years

Warranty



M1

Fire Resistance

Why Choose STRADA?

Decorative - Lines — engineered for professional interior application.

ADVANTAGES

- 90% UV protection
- Improved visual comfort
- Depoli finish
- 54% visible light transmission retained
- Professional interior installation

PERFORMANCE KEY — SINGLE 3MM, FILM APPLIED

90%

UV Rejection

54%

Visible Light Transmission

5 years

Warranty

M1

Fire Resistance

CHARACTERISTICS



Warranty
5 years



Fire Resistance Rating
M1



Storage (recommended conditions)
3 years



REACH / RoHS
Compliant



Widths Available
152 cm



Installation Type
Interior



Color From the Outside
Depoli



Length
30,5 m



Product Carbon Footprint (LCA)
1.56 kgCO2e/m²

CONSTRUCTION — PET, 40 µm

1. High optical quality polyester with printed design
2. PS adhesive, polymerizes with glass within 15 days
3. Protection PET release liner, disposable after installation

GLAZING RECOMMENDATIONS

Vertical situation, standard glazed surface up to 2.5 m².

Clear Single Pane	✓ Yes
Tinted Single Pane	✓ Yes
Reflective Tinted Single Pane	✓ Yes
Clear Double Pane	✓ Yes
Tinted Double Pane	✓ Yes
Reflective Tinted Double Pane	✓ Yes
Gas-Filled Double Pane - Low E	✓ Yes
Stadip Ext. Clear Double Pane	✓ Yes
Stadip Int. Clear Double Pane	✓ Yes

✓ Yes ! Caution × Not recommended

Advice based on glazed surface area up to 2.5 m² — contact us for confirmation or a thermal shock analysis on larger or atypical glazing.

INSTALLATION & MAINTENANCE

Use Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Learn more about FNX and our product catalog.



THERMAL COMFORT



UV PROTECTION



GLARE REDUCTION



ENERGY PERFORMANCE



SUPERIOR AESTHETICS



PROFESSIONAL INSTALL