



OLA ATF II D

Automatic transmission fluid

Specification:

GM Dexron II D

Description:

OLA ATF II D is a high performance fluid for automatic transmissions vehicles specifying dexron II D. It is also used as a hydraulic fluid in unique applications.

Applications:

- OLA ATF II D is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying dexron IID level performance as well as the related power steering systems.
- OLA ATF II D is also suitable for Off-highway transmissions power steering and other hydraulic systems requiring a dexron II D or allison C-4 fluid and Industrial hydraulic systems.

Features and benefits:

OLA ATF II D is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antioxidants, and defoamers providing outstanding performance:

- Good thermal and oxidation stability.
- Good anti-wear properties.
- Meets the wear requirement to promote longer transmission life.

- Excellent low-temperature fluidity.
- Effective foam control properties.
- Compatible with all common seal materials used in type IID transmissions.

Typical properties:

	Test Method	ATF IID
Viscosity @ 40°C-cSt	ASTM D 445	37
Viscosity @ 100°C-cSt	ASTM D 445	7
Viscosity Index	ASTM D 2270	153
Pour point °C	ASTM D 97	-44
Flash Point °C	ASTM D 92	200
Density @ 15°C - kg/l	ASTM D 4052	0.870

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.