



CONTABLUE

Rival - Garud

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Formal

UPPER
Grain Leather

LEATHER THICKNESS
2mm

LINING
Mesh

COLOUR
Black

INSOCKS
Soft EVA/PU

OUTER SOLE
PU DD/PUR

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 22 KV



Chemical
Resistant Sole



Chemical
Resistant Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival-Welder

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Genuine
Leather

**LEATHER
THICKNESS**
2mm

LINING
Special Mesh

COLOUR
Black

INSOCKS
EVA/PU

OUTER SOLE
PU DD/PUR*

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



**12 MONTHS SOLE BONDING &
BREAK WARRANTY**



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Sport

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Sporty

UPPER
Grain
Leather

**LEATHER
THICKNESS**
2mm

LINING
Grey Spacer

COLOUR
Black

MIDSOLE
PU Grey colour

OUTER SOLE
PU Black colour

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



**12 MONTHS SOLE BONDING &
BREAK WARRANTY**



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Slipon

Specifications



RISE
Low Ankle

DESIGN
Slipon

UPPER
Genuine
Leather

**LEATHER
THICKNESS**
1.8-2mm

LINING
Non-woven

COLOUR
Black

INSOCKS
EVA/PU

OUTER SOLE
PU DD

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



**12 MONTHS SOLE BONDING &
BREAK WARRANTY**



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Protector

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Low Ankle

UPPER
Grain Leather

LEATHER THICKNESS
2mm

LINING
Mesh

COLOUR
Black

INSOCKS
EVA/PU

OUTER SOLE
PU DD

OPTIONAL
Metal free

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 18 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Kavach

Specifications

TECHNOLOGY

Direct Injection

DESIGN

Sporty

UPPER

Grain
Leather

LEATHER THICKNESS

2mm

LINING

Mesh

COLOUR

Black

INSOCKS

Soft EVA/PU

OUTER SOLE

PU Black colour

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 22 KV



Chemical
Resistant Sole



Chemical
Resistant Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Fury

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Grain Leather

LEATHER THICKNESS
2mm

LINING
Mesh

COLOUR
Black

INSOCKS
Foam/PU

OUTER SOLE
PU SD/DD

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Brogue

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Formal

UPPER
Grain Leather

LEATHER THICKNESS
2mm

LINING
Mesh

COLOUR
Black

INSOCKS
Soft EVA

OUTER SOLE
PU DD/PUR

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical Resistant
Sole



Chemical Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Angel

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Low Ankle

UPPER
Grain Leather

LEATHER THICKNESS
2mm

TYPE
Female

COLOUR
Black

INSOCKS
Foam/PU

OUTER SOLE
PU SD/ DD

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival - Denver

Specifications



TECHNOLOGY

Direct Injection

DESIGN

Regular

UPPER

Grain
Leather

LEATHER THICKNESS

2mm

LINING

Grey Spacer

COLOUR

Black

INSOCKS

Soft EVA/PU

OUTER SOLE

PU Black colour

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 22 KV



Chemical
Resistant Sole



Chemical
Resistant Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival Bolt-A

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Grain
Leather

LEATHER THICKNESS
2mm

LINING
Mesh

COLOUR
Black

INSOCKS
Foam/PU

OUTER SOLE
PU SD/DD

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival BA 201-BR

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Grain
Leather

LEATHER THICKNESS
2mm

LINING
Sweat Absorbent
Mesh

COLOUR
Brown

INSOCKS
Foam/PU

OUTER SOLE
PU SD/DD/PUR

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival B 402-E

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Semi-aniline
finished

**LEATHER
THICKNESS**
2mm, 5% fat

UPPER PROPERTY
Water resistant

COLOUR
Black

CONSTRUCTION
Strobel

OUTER SOLE
PUR

TYPE
Metal free
Electrical

TOE
200J



**12 MONTHS SOLE BONDING &
BREAK WARRANTY**



IS 15298/ ISO 20345 APPROVED

Safety Features



Heat Resistant
upto 300° C



Shock Proof
Max 18 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival B 402

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Semi-aniline
finished

**LEATHER
THICKNESS**
2mm, 5% fat

UPPER PROPERTY
Water resistant

COLOUR
Brown

CONSTRUCTION
Strobel

OUTER SOLE
PUR

INSOCKS
Moulded EVA

TOE
200J



**12 MONTHS SOLE BONDING &
BREAK WARRANTY**



IS 15298/ ISO 20345 APPROVED

Safety Features



Heat Resistant
upto 300° C



Shock Proof
Anti-static



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival BA 201-BLC

Specifications



TECHNOLOGY
Direct Injection

DESIGN
Ankle

UPPER
Grain Leather
CG Print

LEATHER THICKNESS
2mm

LINING
Sweat Absorbent
Mesh

COLOUR
Black

INSOCKS
Foam/PU

OUTER SOLE
PU SD/DD/PUR

OPTIONAL
ESD, ESR,
Steel Mid Plate

TOE
200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival B 201-BLC

Specifications



TECHNOLOGY

Direct Injection

DESIGN

Low Ankle

UPPER

Grain Leather
CG Print

LEATHER THICKNESS

2mm

LINING

Sweat Absorbent
Mesh

COLOUR

Black

INSOCKS

Foam/PU

OUTER SOLE

PU SD/DD/PUR

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival B 201-BRC

Specifications



TECHNOLOGY

Direct Injection

DESIGN

Low Ankle

UPPER

Grain Leather
CG Print

LEATHER THICKNESS

2mm

LINING

Sweat Absorbent
Mesh

COLOUR

Brown

INSOCKS

Foam/PU

OUTER SOLE

PU SD/DD/PUR

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival B 201-BRC

Specifications



TECHNOLOGY

Direct Injection

DESIGN

Low Ankle

UPPER

Grain
Leather

LEATHER THICKNESS

2mm

LINING

Sweat Absorbent
Mesh

COLOUR

Brown

INSOCKS

Foam/PU

OUTER SOLE

PU SD/DD/PUR

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival Panther

Specifications



TECHNOLOGY

Direct Injection

DESIGN

Low Ankle

UPPER

Genuine
Leather

LEATHER THICKNESS

2mm

LINING

Sweat Absorbent
Mesh

COLOUR

Black

INSOCKS

EVA/Foam/PU

OUTER SOLE

PU DD

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



**12 MONTHS SOLE BONDING &
BREAK WARRANTY**



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Battler Eva

Specifications

**TYPE**

Female

DESIGN

Low Ankle

UPPERGenuine
Leather**LEATHER
THICKNESS**

1.8-2mm

CLOSINGTwo strap
velcrow**COLOUR**

Black

INSOCKS

EVA/Foam/PU

OUTER SOLE

PU SD/ DD

LININGPink Sweat
Absorbent**TOE**

200J

**12 MONTHS SOLE BONDING &
BREAK WARRANTY****IS 15298/ ISO 20345 APPROVED**

Safety Features

Temp Resistant
<120° CShock Proof
Max 15 KVChemical
Resistant
SoleChemical
Resistant
UpperComposite /
Steel ToeEnergy Absorbing
HeelSlip Resistant
SoleOil Resistant
Upper

*PU with nitrite rubber



CONTABLUE

Rival Bolt

Specifications



TECHNOLOGY

Direct Injection

DESIGN

Low Ankle

UPPER

Grain
Leather

LEATHER THICKNESS

2mm

LINING

Mesh

COLOUR

Black

INSOCKS

Foam/PU

OUTER SOLE

PU SD/DD

OPTIONAL

ESD, ESR,
Steel Mid Plate

TOE

200J



12 MONTHS SOLE BONDING & BREAK WARRANTY



IS 15298/ ISO 20345 APPROVED

Safety Features



Temp Resistant
<120° C



Shock Proof
Max 15 KV



Chemical
Resistant
Sole



Chemical
Resistant
Upper



Composite /
Steel Toe



Energy Absorbing
Heel



Slip Resistant
Sole



Oil Resistant
Upper

*PU with nitrite rubber