

The following illustrates the steps necessary to install the Illuminated Marquee for all Ice Cooled Drop-In Dispensers

Installation

1. Turn Key Switch OFF.

⚠ WARNING

Unplug the power cord from the electrical outlet to prevent possible electrical shock or personal injury.

2. Unplug power cord from electrical outlet.
3. Remove existing tower cap (save screws for reinstallation), cup rest, drip tray, and splash plate from tower body.
4. Locate key lock switch wire harness that connects to the transformer harness (See drawing below for reference).
5. Disconnect these two (2) wire harnesses.
6. Connect wire harness (PN 52-1472) to the two (2) harnesses that were disconnected.
7. Route the longest section of the wire harness along the side and over the top of the foam manifold.
8. Remove protective cover from adhesive tape which is attached to the marquee.
9. Attach marquee, by sliding the marquee's sheet metal return over the notch at each end of the tower body return.

NOTE

Keep adhesive tape away from tower body until tower is in its final position.

10. Run marquee connector through slot located in the back of tower body (see drawing below for reference).
11. Plug marquee connector to wire harness (PN 52-1472).
12. Install new tower cap. Secure with the two (2) screws removed in Step 3.
13. Plug power cord into electrical outlet.
14. Marquee should illuminate without key switch being turned on.
15. If marquee does not illuminate, then check wire harness connections (see Steps 4 - 7).
16. Install splash plate, drip tray, and cup rest to tower body.
17. Turn key lock switch back to the ON position.

