

INTERIOR

ARCHITECTURAL FILM

AZUR BLUE C

Coloured - Transparent — Interior Application, Blue From Outside

Applied to clear glass, the transparent tint to the glass without diminishing perfect way to enliven any interior screens, etc.) with a touch of colour.

- 99% UV rejection with engineered light control
- Retains 44–27% visible light transmission
- Engineered and certified for professional interior installation
- 99% UV rejection helps protect interiors and furnishings from fading
- Blue finish, engineered for interior application

Key Strengths



99%

UV Rejection



44–27

Visible Light Transmission



5 years

Warranty



M1

Fire Resistance

Why Choose AZUR BLUE C?

Coloured - Transparent — engineered for professional interior application.

ADVANTAGES

- 99% UV protection
- Blue finish
- Professional interior installation
- Improved visual comfort
- 44-27% visible light transmission retained

PERFORMANCE KEY — SINGLE 3MM, FILM APPLIED

99%

UV Rejection

44-27

Visible Light Transmission

5 years

Warranty

M1

Fire Resistance

CHARACTERISTICS



Warranty
5 years



Fire Resistance Rating
M1



Storage (recommended conditions)
3 years



REACH / RoHS
Compliant



Widths Available
152 cm



Installation Type
Interior



Color From the Outside
Blue



Length
30.5 m



Product Carbon Footprint (LCA)
1.56 kgCO₂e/m²

CONSTRUCTION — PET, 40 µm

1. Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
2. High optical quality dyed polyester
3. PS adhesive, polymerizes with glass within 15 days
4. Protection PET release liner, disposable after installation

GLAZING RECOMMENDATIONS

Vertical situation, standard glazed surface up to 2.5 m².

Clear Single Pane	! Caution
Tinted Single Pane	! Caution
Reflective Tinted Single Pane	! Caution
Clear Double Pane	! Caution
Tinted Double Pane	! Caution
Reflective Tinted Double Pane	! Caution
Gas-Filled Double Pane - Low E	! Caution
Stadip Ext. Clear Double Pane	! Caution
Stadip Int. Clear Double Pane	! Caution

✓ Yes ! Caution × Not recommended

Advice based on glazed surface area up to 2.5 m² — contact us for confirmation or a thermal shock analysis on larger or atypical glazing.

INSTALLATION & MAINTENANCE

Use Slide On (600-FO2) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Learn more about FNX and our product catalog.



THERMAL COMFORT



UV PROTECTION



GLARE REDUCTION



ENERGY PERFORMANCE



SUPERIOR AESTHETICS



PROFESSIONAL INSTALL