

3M Science.
Applied to Life.™

A photograph of two workers in a warehouse. They are wearing yellow hard hats, blue long-sleeved shirts, and high-visibility yellow safety vests. One worker is handing a cardboard box to the other. The background is filled with stacks of cardboard boxes. A large black diagonal shape is overlaid on the bottom right of the image, containing the title and other text.

3M Packaging Solutions Guide

Right tapes.
Right system.
Right partner.

Industrial Specialties Division - Packaging
September 2024


At 3M, we never forget our success was sealed by a roll of tape.

A single inventive way of solving a customer's problem more than ~100 years ago led to a breakthrough that became known as "Scotch® Tape"; an invention that changed the world. Today, the curious minds at 3M continue to maintain the legacy of the original Scotch® Tape by meeting customer needs everyday and never compromising on performance.

Reliable performance proven over time has formed a bond of trust with Scotch® Tape. This is why it remains the number one brand for packaging, bundling, reinforcing solutions and more. At 3M, we stake our reputation on delivering the very best, most reliable tapes every day so you can trust Scotch® Tape to protect your reputation, as well.

You can double down on dependability by combining Scotch® Box Sealing Tapes with 3M-Matic™ Case Sealers. With nearly a half-century of experience in building case sealing equipment, 3M delivers the "total package" in packaging systems.

In a world where so many unexpected events can impact your results, Scotch® Tapes and 3M packaging solutions have got you covered — with dependable, high quality products and systems to meet your ever-changing requirements.



Right tapes. Right system. Right partner.

3M Packaging Solutions



Packaging Equipment and Dispensers

3M-Matic™ Case Sealers Selection Overview	6-7
3M-Matic™ Adjustable Case Sealers	8-9
3M-Matic™ Random Case Sealers	10
3M™ AccuGlide™ Taping Head Technology	11-12
Customized 3M-Matic™ Equipment	12
Non-RSC Closure Solutions.....	13
3M-Matic™ Case Sealers Replacement Parts and Accessories	14
Scotch® and Tartan™ Manual Tape Dispensers.....	15-17
3M Systems Tape Agreement	18-19



Box Sealing Tapes

Scotch® Box Sealing Tapes Overview	21
Box Sealing Tape Selector	22
Scotch® and Tartan™ Box Sealing Tapes.....	23
Scotch® Plus+ Series Tapes	24
Scotch® Custom Printed Box Sealing Tapes.....	25
Scotch® Cold Temperature Tape.....	26
3M™ Water Activated Tapes.....	27
Scotch® Security Tapes	27
Scotch® Specialty Box Sealing Tapes	25
Light Duty Packaging Tapes	28-29
Scotch® Performance Paper Box Sealing Tape 570	40



Custom Packing Solutions

3M™ Carry Handles.....	31-32
Scotch Multipack Tapes.....	33
3M™ Tape Pads	34
3M™ Hang Tabs.....	34
Scotch® Pouch Tapes.....	35
Label Protection Tapes	36
3M™ Packing List Envelopes	37



Sustainable Solutions

PACR (Padded Automatable Curbside Recyclable Mailer Material).....	40
Scotch® Performance Paper Box Sealing Tape 570	40


Glossary	39-40
-----------------------	-------

Numerical Index	41
------------------------------	----

Product Name Index	42-43
---------------------------------	-------

3M-Matic
Case Sealing Systems

ERECTING & PACKING




Case erectors
Ergo packs

Throughput & speed

3M™ AccuGlide™ Tape
Head Technology


3M-Matic
Case Sealing Systems

Consistency
Security
Protection



SEALING

Semi-automatic
Hand applied




Scotch

Recycled
corrugate?
No problem!

Scotch


Protection
Control
Security



BUNDLING

L-CLIP CLOSURE

PACKING STATIONS



Labeling
Ease of use


Document attachment
Label protection
Patching

Tech support
Before & after
the sale

Scotch 3M

The Total Package

Pack it. Close it. Move it. Sell it. Use it.





Packaging Equipment & Dispensers

How do you get your packages securely sealed, out the door and into the hands of your customers in the fastest, most efficient manner? It starts with 3M-Matic™ Case Sealers. For 55 years, packaging facilities everywhere have relied on these productivity-enhancing solutions for consistent, efficient case sealing, day after day.



55TH
3M-Matic™
Case Sealers
ANNIVERSARY CELEBRATION
Consistent. Reliable. Tough.
3M



3M-Matic™
Case Sealing Systems

3M-Matic™ Case Sealer

Things to Consider When Selecting a Case Sealer

1

**Do you pre-form your boxes?
What style box do you use?**

- RSC (Regular Slotted Carton)
- FPF (Five Panel Fold)
- Full overlap

3

What closure method do you use?

- RGT (Reinforced Gum Tape)
- Pressure-sensitive box sealing tape
- Glue
- Staples

2

**How many boxes do you
seal per day?**

4

**Do you seal your boxes
in uniform or random
production runs?**

3M-Matic™ Case Sealers Selection Overview



38

For Sealing Uniform Size Boxes

Manually Adjustable, Semi-Automatic



8000af

210

Up to 40 cs/min
Up to 85 lbs
Side belt drives

*Available with 3 inch taping head.

Manually Adjustable, Semi-Automatic

Affordable for Low Volume



2000a*

211

Up to 40 cs/min
Up to 85 lbs
Bottom belt drive



7000a Pro

195

Up to 40 cs/min
Up to 85 lbs
Top/bottom belt drives



8000a

191

Up to 40 cs/min
Up to 85 lbs
Side belt drives

*Available with 3 inch taping head.

Manually Adjustable, Semi-Automatic

Affordable for Low Volume



8000ab*

211

Up to 40 cs/min
Up to 85 lbs
Bottom belt drive



8000asb

195

Up to 40 cs/min
Up to 85 lbs
Top/bottom belt drives



700a-s

191

Up to 40 cs/min
Up to 85 lbs
Side belt drives







3M-Matic™ Case Sealers Selection Overview





39

For Sealing Various Size Boxes

 <p>8000r[†] Up to 10 cs/min Up to 200 lbs</p>	 <p>800rks[†] Up to 10 cs/min Up to 200 lbs Top/bottom side belt drives</p>	 <p>7000r Pro* Up to 24 cs/min Up to 85 lbs Top/bottom belt drives</p>	 <p>7000r HS Pro* Up to 28 cs/min Up to 60 lbs Top/bottom belt drives</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

*Available with 3 inch taping head.
†Comes standard with 3 inch taping head.

Non-RSC Box	
 <p>S867 3M-Matic™ L-Clip Applicator S867 is a semi-automatic unit that applies 4.5 inch L-Clips of Scotch® Filament Tapes and Scotch® Box Sealing Tapes at up to 50 clips/min.</p>	 <p>S867 II 3M-Matic™ Dual L-Clip Applicator S867 II applies two 4.5 inch L-Clips of Scotch® Filament or Reinforced Strapping Tape on the same edge at up to 50 clips/min.</p>

3M-Matic Helpline: 1-800-328-1390

When you have a question, simply call the toll-free helpline, open to take your calls Monday through Friday, 8:00am to 4:30pm Eastern Standard Time. Messages will be taken 24 hours a day for next working day response.

Belt Drive Key
2 = Bottom belt drives
7 = Top and bottom belt drives
8 = Side belt drives

Box Type
a = Adjustable, for batch runs
r = Random, for mixed runs


Additional Capability
b = Bottom only
f = Flap folding
ks = King size
sb = Small box

3M-Matic™ Adjustable Case Sealers



Gain productivity with quick height and width adjustments.

With quick manual adjustment, these rugged units reliably and accurately seal runs of the same size cartons for a variety of markets: food and beverage, medical devices, pharmaceutical, electronics, retail, manufacturing and distribution centers to name a few.



3M-Matic™ Adjustable Case Sealer 700a-s

has advanced features to seal uniform cases at up to 30 per minute. Dual masts with dual lead screws for stability and uniform height adjustments. Adjustable top and bottom belt drive system for reliable conveyance of heavier or tall/light boxes. Compression rollers position each box for precise tape sealing. Stainless construction for corrosive environments.

3M-Matic™ Case Sealer 2000a Now with 3M™ AccuGlide™ NPH+ Taping Head, is an adjustable bottom belt drive case sealer to dependably seal uniform

3M-Matic™ Adjustable Case Sealer 7000a Pro is an adjustable top and bottom belt drive to dependably seal uniform cases at up to 40 per minute.

Bottom Belt Drive Systems

Machine	Drive System	Box Size Capacity (inches)						Power Requirements		Operating Rate (cs/min)	Belt-Drive Speed (ft/min (m/s))	Taping Head	Comments
		Minimum			Maximum			Electrical	Air				
		L	W	H	L	W	H						
2000a	Bottom	6.0	6.5	4.5 [3.75]	N/L	21.5	24.5 [28.5]	115VAC 60Hz 1.9A 220W	No Air	Up to 40	100 (0,5)	3M™ AccuGlide™ NPH+ Taping Head	Semi-Automatic Adjustable
2000a3			7.5									3" 3M™ AccuGlide™ 3	

Standard size capabilities are listed above. If additional sizes can be met, they are indicated by [Taping Head] or [Machine Configuration]. Changing the taping head or machine configuration will allow for enhanced box height range indicated in the chart above. Please refer to the Instructions and Parts List or 3M representative for more detail.


Top and Bottom Belt Drive Systems

Machine	Drive System	Box Size Capacity (inches)						Power Requirements		Operating Rate (cs/min)	Belt-Drive Speed (ft/min (m/s))	Taping Head	Comments
		Minimum			Maximum			Electrical	Air				
		L	W	H	L	W	H						
700a-s	Top and Bottom	6.0	6.0	4.75	N/L	21.5	24.5	115VAC 60Hz 3.8A 440W	No Air	Up to 30	78 (0,4)	2" 3M™ AccuGlide™ 2+ Stainless Steel	For Corrosive Environment
7000a Pro	Top and Bottom	6.0	6.5	4.75	N/L	26.5	28.0	115VAC 60Hz 3.8A 440W	No Air	Up to 40	100 (0,5)	2" 3M™ AccuGlide™ 3	Extended size capabilities are possible, please contact 3M
7000a3 Pro												3" 3M™ AccuGlide™ 3	

Standard size capabilities are listed above. If additional sizes can be met, they are indicated by [Taping Head] or [Machine Configuration]. Changing the taping head or machine configuration will allow for enhanced box height range indicated in the chart above. Please refer to the Instructions and Parts List or 3M representative for more detail.



3M-Matic™ Adjustable Case Sealers



8000af

210

3M-Matic™ Case Sealer 8000af is an automatic flap folding machine that seals both the top and bottom of a box without an operator.



8000a

191

3M-Matic™ Side Belt Adjustable Case Sealer 8000a is an adjustable side belt drive case sealer. Seals up to 40 cases per minute, using tape widths from 36mm to 48mm, and also 72mm tape.



8000asb

194

3M-Matic™ Case Sealer 8000asb with 3M™ AccuGlide™ NPH Taping Head is a manually adjustable side belt drive case sealer. Seals up to 30 cases per minute, using tape width of 36 - 48mm.



8000ab

44

3M-Matic™ Case Sealer 8000ab is an adjustable side belt drive case sealer. Applies bottom seal only at rates up to 40 cases per minute, using tape widths from 36mm to 48mm, and also 72mm tape.

Side Belt Drive Systems

Machine	Drive System	Box Size Capacity (inches)						Power Requirements		Operating Rate (cs/min)	Belt-Drive Speed (ft/min (m/s))	Taping Head	Comments
		Minimum			Maximum			Electrical	Air				
		L	W	H	L	W	H						
8000a	Side	6.0	4.5	4.75	N/L	21.5	28.5	115VAC 60Hz 3.8A 440W	No Air	Up to 40	100 (0.50)	2" 3M™ AccuGlide™ 3	Extended size capabilities are possible, please contact 3M
8000a3			5.5	4.75			28.5					3" 3M™ AccuGlide™ 3	
8000ab	Side	6.0	3.625	2.75	N/L	21.5	21.5	115V 60Hz 3.8A	No Air	Up to 30	100 (0.50)	3M™ AccuGlide™ NPH Taping Head	Bottom Taping Only
8000ab3	Side	6.0	4.5	2.75	N/L	21.5	N/L	115VAC 60Hz 3.8A 440W	No Air	Up to 40	100 (0.50)	3M™ AccuGlide™ NPH Taping Head	Bottom Taping Only
8000asb	Side	6.0	3.5	3.5	N/L	21.5	22.5	115V 60Hz 3.25A	No Air	Up to 40	100 (0.50)	3M™ AccuGlide™ NPH Taping Head	Bottom Taping Only
8000af	Side	6.0	4.75	4.5	30	21.5	28.5	115VAC 60Hz 3.8A 440W	2.5 SCFM @ 85 PSIG	Up to 40	100 (0.50)	2" 3M™ AccuGlide™ 3	Flap-Folding
8000af3			5.75									3" 3M™ AccuGlide™ 3	

Standard size capabilities are listed above. If additional sizes can be met, they are indicated by [Taping Head] or [Machine Configuration]. Changing the taping head or machine configuration will allow for enhanced box height range indicated in the chart above. Please refer to the Instructions and Parts List or 3M representative for more detail.

3M-Matic™ Random Case Sealers




Gain productivity with automatic height and width adjustments.

Adjusting automatically, these rugged units reliably and accurately seal runs of random size cartons for a variety of markets: food and beverage, medical devices, pharmaceuticals, electronics, retail, manufacturing and distribution centers. The 3M™ AccuGlide™ 2+ and 3 Taping Heads securely apply tape with low impact to protect even lightweight cases.



3M-Matic™ Random Case Sealer 7000r Pro is a semi-automatic random case sealer that automatically adjusts for case height and width and is capable of sealing 24 cases per minute, using tape widths from 36mm to 48mm wide.



3M-Matic™ Random Case Sealer 7000r High Speed Pro is a random size case sealer designed to automatically adjust to a variety of box sizes. It can seal up to 28 different case sizes per minute.



3M-Matic™ Case Sealer 8000r is a semi-automatic, random case sealer that automatically adjusts for case height and width. Top and bottom seal at rates up to 20 cases per minute.



3M-Matic™ Case Sealer 800rks is a random king size case sealer that automatically adjusts for case height and width and is capable of sealing up to 10 cases per minute, using tape widths from 48mm to 72mm wide.

Top and Bottom Belt Drive Systems

Machine	Drive System	Box Size Capacity (inches)						Power Requirements		Operating Rate (cs/min)	Belt-Drive Speed ft/min (m/s)	Taping Head	Comments
		Minimum			Maximum			Electrical	Air				
		L	W	H	L	W	H						
7000r Pro 7000r3 Pro	Top and Bottom	6.0	6.5	4.5	N/L	26.5	26.0	115VAC 60Hz 3.8A 440W	3.75 SCFM @ 85 PSIG	Up to 24	100 (0,5)	2" 3M™ AccuGlide™ 3 3" 3M™ AccuGlide™ 3	Extended size capabilities are possible, please contact 3M
7000r HS Pro 7000r3 HS Pro	Top and Bottom	7.0	7.0	3.5 2.7*	N/L	26.0	27.0 38.13*	115VAC 60Hz 9.5A 1140W	15 SCFM @ 90 PSIG	Up to 28	150 (0,76)	2" 3M™ AccuGlide™ V HSP Taping Head 3" 3M™ AccuGlide™ V HSP Taping Head	

*Requires special setup.

Side Belt Drive Systems


Machine	Drive System	Box Size Capacity (inches)						Power Requirements		Operating Rate (cs/min)	Belt-Drive Speed ft/min (m/s)	Taping Head	Comments
		Minimum			Maximum			Electrical	Air				
		L	W	H	L	W	H						
800rks	Side	15.0	6.0	12.0	N/L	30.0	50.0	208/240VAC 3Ph 60Hz 6.6A 1500W	6.25 SCFM @ 85 PSIG	Up to 10	78 (0,4)	3" 3M™ AccuGlide™ 2+	Random King Size
8000r 8000r3	Side	8.0	5.5	6.0	N/L	20.0	27.0	115V 60Hz 3.25A	6.2 SCFM @ 90 PSIG	Up to 20	100 (0,5)	3M™ AccuGlide™ V HSP Taping Head 3M™ AccuGlide™ V HSP Taping Head	Top and Bottom Sealing

Standard size capabilities are listed above. If additional sizes can be met, they are indicated by [Taping Head] or [Machine Configuration]. Changing the taping head or machine configuration will allow for enhanced box height range indicated in the chart above. Please refer to the Instructions and Parts List or 3M representative for more detail.

3M™ AccuGlide™ V HSP Taping Head

3M has a decades long history in case sealing and tape technology! We designed, engineered, and built our first 3M-Matic™ case sealer 55 years ago!

Our new 3M™ AccuGlide™ V High Speed Taping Head combines the best attributes from all our 3M™ AccuGlide™ taping heads into one!



Speed
Tested at 150 feet per minute, with the ability to run at multiple speeds.

Precision
Without compromising necessary tape adhesion, the 3M™ AccuGlide™ V HSP Taping Head will apply the precise pressure to adhere the tape without damaging the product in under-filled cases.

Versatility
The narrow design allows the taping head to be quickly dropped into most case sealers and case erectors on the market.

Durability
Reinforced key wear points and components for maximum durability. Rollers are more conformable for better wipe down. Side plates have been reinforced in key areas.

Flexibility
Variable spring positioning, easy one-way tension roller and tape tension adjustments to accept varying corrugate and production environments.

Tape Application
Full width blade for consistent tape cutting, a flap guide to prevent damage to the major flaps and better tape management for consistent tape leg lengths.

Changeover
The tape threading path is open for faster changeovers.

3M™ AccuGlide™ Taping Head Technology

3M taping heads for easy and accurate case sealing.

3M™ AccuGlide™ Taping Heads are a curvilinear design that applies tape securely with low impact that helps protect even lightweight cartons and contents. Since the combination of box sealing tape and taping head determines carton closure performance, 3M is continually improving both to meet your requirements for productivity and reliability.



3M™ AccuGlide™ 2+

Speeds up to 78 ft. per minute.
Stainless steel option available.



3M™ AccuGlide™ 3

Raising the speed limit to 100 ft. per minute for easy, consistent and accurate case sealing.



3M™ AccuGlide™ V

Speeds up to 78 ft. per minute.
Stainless steel option available.



3M™ AccuGlide™ NPH+ Taping Head

Featuring a narrow profile head and up to 120 fpm taping speed, the AccuGlide NPH+ can help streamline your operations, maximize your productivity and improve your quality—no matter what brand of case sealer you own.



3M™ AccuGlide™ LHB

A low height box taping head that exerts minimum force on case and utilizes shorter tape legs.


Customized 3M-Matic™ Equipment

Built around your product needs.

A leading player in case sealing equipment, 3M realizes it's not one size fits all. We have a unique capability to take an existing 3M-Matic™ Case Sealer and customize it to securely seal your unique cartons. Some of our capabilities include width and height modifications, accommodating lighter or heavy weight boxes, and integrating unique tape set ups.



Side Taping



Box Lift for Low Height Cases



Wide Roll Taping



Non-RSC Closure Solutions

A range of solutions can help increase throughput while decreasing packaging costs.

- Solutions for start-ups
- Automation for large companies

3M-Matic™ L-Clip Applicator S867 and S867II

To save cost and time, apply pre-fed 4.5-inch L-Clips of Scotch® Filament or Reinforced Strapping Tapes at up to 50 clips per minute to five panel fold, full overlap, telescoping, tuck fold and other non-standard packages. Dual head applies two clips simultaneously as close as 8 inches apart.



3M-Matic™ Dual L-Clip Applicator S867II

64




Scotch® Filament Tape Box Sealer S634

69



3M-Matic™ L-Clip Applicator S867 with optional U-Clip adapter.



65

66

67


Table Top L-Clip Applicators

Features	Box Sealer S634
Tape Type(s)	Filament Tape Light Duty Packaging Tape, Upper Scotch® Packaging Tape
Can L-Clip These Package Types	Corrugate
Applied Tape Length	4.5 inch (144mm)
Tape Width Options	0.375–1.5 inch (9.5–36mm)
Cutting Method	Serrated blade cuts tape as box passes L-Clip application mechanism

Great L-Clip Closure Solution for Non-RSC Box Styles




U-Clip Package



Telescoping Box




Custom Box



One Piece Box



F.O.L.



Five Panel Box

68

3M-Matic™ Case Sealers Replacement Parts and Accessories


Genuine 3M Parts to maintain optimal performance of 3M-Matic™ Case Sealers.

Engineered for rugged duty with steel construction and epoxy coated surfaces, 3M-Matic™ Case Sealers may have parts that wear and need occasional replacement. 3M maintains stock of a full range of replacement parts from typical wear parts such as blades, belts, and springs to safety labels to bushings and cylinders. With over 5,000 stocked SKUs, replacement parts are available for prompt delivery to your location whether you are doing preventive maintenance or rebuilding a 3M-Matic™ Case Sealer after years of service.

Regular preventive maintenance of your equipment and quality parts are keys to performance of both newer case sealers or models that have been running for 30 years.




For replacement parts contact: 1-800-344-9883
store.combi.com/cspd



Application Monitor

With top and bottom sensors, the case sealer mounted programmable logic controller alerts the operator when tape is not applied to the box or not cut, or when tape supply is low on the roll.



Low Tape Indicator Light Kit

An option for 3M-Matic™ Case Sealers. Indicates when tape is getting low.



3-Flap Folder

For increased productivity, easily attached flap folder assists operator in folding the minor (front) and two major (side) flaps of RSCs before taping.



Infeed/Exit Conveyor

Ball bearing steel rollers in a steel frame bolts to the 3M-Matic™ Case Sealer to provide a smooth transition in existing conveyor lines. Provides pack area surface at infeed. Available also in stainless steel.



Box Hold Down Attachment

Holds RSCs on the optional infeed conveyor to free the operator's hands for case filling.



Locking/Swivel Casters

When packaging operations need to be reconfigured or moved, 3M-Matic™ Case Sealers roll to the job on these heavy duty casters. Toe-operated lever locks case sealer in place.



Scotch® and Tartan™ Manual Tape Dispensers

Scotch® Box Sealing Tape Dispenser HR80/HR83

Portable, lightweight, easy to operate, hand-held dispenser with a retractable blade.



9

Scotch® Low Noise Box Sealing Tape Dispenser H150/H153


A hand-held, roll-on, pistol-grip dispenser designed to reduce the noise of tape unwind.



78

Tartan™ Box Sealing Hand Dispenser HR933

Tape dispenser with a retractable blade.



217

Scotch® Heavy-Duty Dispensers

Manual heavy-duty dispensers for use with 3M™ Narrow Width Film Tapes.



C22

C25

C23

88

218




Scotch® Box Sealing Tape Dispensers

Hand-held dispensers for use with specially formulated Scotch® Box Sealing Tapes.




Specialty Scotch® Tape Dispensers

Hand-held dispensers for use with Scotch® High Strength Filament Tapes.



Scotch® Bag Sealers

Applies tape in an adhesive-to-adhesive flag seal.



3M™ Electric Water Activated Tape Dispenser

Dispenser has a heated water reservoir that speeds tape activation. Dispenses a pre-set length of water-activated tape at the push of a button. (Manual version also available.)

Scotch® Label Protection Dispensers

Tabletop and portable dispensers designed specifically for 3M™ Label Protection and Pouch Tapes.

Scotch® Multi-Roll Dispenser

Dispenser for pull and tear of up to 6 inches total width of tapes. P56W offers weighted base. (P52/P52W also available for up to 2" total width tape.)

Scotch® Definite Length Dispensers

Dispensers that deliver a uniform length of 3M™ Narrow Width Tape and Scotch® Filament Tapes every time quickly and easily. (M82 and M900 are also available for wider tape dispensing.)



Scotch® and Tartan™ Manual Tape Dispensers

Easy dispensing for manufacturing, office, commercial and retail jobs.

All Scotch® and Tartan™ Manual Tape Dispensers for box sealing tapes, filament tapes, film tapes, label protection tapes and pouch tapes are application-designed to meet the needs of the customer. Select from a variety of hand-held and heavy duty pull-and-tear table top dispensers.

Product	Product Description	Max Tape Width
Hand-Held Box Sealing Tape Dispensers		
H122	Durable plastic dispenser with built-in brake for precise seals	48mm
H123	Lightweight, compact metal tape dispenser	72mm
H128	Heavy-duty durable metal tape dispenser	48mm
H150	Tape dispenser designed to reduce the noise of tape unwind during application	48mm
H153	Tape dispenser designed to reduce the noise of tape unwind during application	72mm
H180	Portable and easy to operate pistol grip dispenser	48mm
H183	Portable and easy to operate pistol grip dispenser	72mm
H190	Pistol grip dispenser features pull apart design	48mm
H192	Ergonomical tape dispenser with hand brake	48mm
H320	Ultra-light, economical, plastic tape dispenser	48mm
HB902	Economical, compact, and lightweight tape dispenser	48mm
HB903	Economical pistol grip tape dispenser	48mm
HR80	Portable, lightweight, easy to operate, dispenser with a retractable blade	48mm
HR83	Portable, lightweight, easy to operate, dispenser with a retractable blade	72mm
HR933	Tape dispenser with a retractable blade	72mm
H12	Portable, plastic dispenser features a hand brake to add tension to the tape roll	24mm
H121	Durable, metal dispenser allows operator to add tension for a tighter tape application	24mm
H128	Heavy-duty, metal dispenser commonly used to dispense tapes 8959 and 890	48mm
H131	Quick and easy one hand method to apply, cut, and buff the tape closures	18mm
H133	Quick and easy one hand method to apply, cut, and buff the tape closures	18mm
HB901	Economical and portable tape dispenser	24mm
Table Top Dispensers		
C22	Weighted dispenser for easy pull and cut tape dispensing	2 in
C23	Weighted dispenser for easy pull and cut tape dispensing	1 in
C25	Weighted dispenser for easy pull and cut tape dispensing	1 in
HB900	Weighted, slip-proof base for quick and easy one-handed operation	1 in
M82	Definite length dispenser handles multiple rolls of tape commonly dispensed with filament and light duty tapes	96mm
M96	Definite length dispenser — dispenses tape in lengths of 3/4 inch to 5 inch per stroke	1 in
M900	Durable, metal construction dispenses a uniform length of packaging tape from 1-1/2 inch to 16 inch	3 in
M920	Definite length dispenser — dispenses tape in lengths of 1/2 inch to 4 inch per stroke	1 in
P52	Mainline tabletop manual pull and cut dispenser with multiple roll capacity	2 in
P52W	Mainline tabletop manual pull and cut dispenser with multiple roll capacity (comes with weighted base)	2 in
P56	Mainline tabletop manual pull and cut dispenser with multiple roll capacity	6 in
P56W	Mainline tabletop manual pull and cut dispenser with multiple roll capacity (comes with weighted base)	6 in
P448	Metal dispenser that handles multiple rolls for easy dispensing	8 in
S634	Semi-automatically applies L-Clip of tape to a box using filament or light duty tapes	18mm
W100	Manually dispenses pre-set length of water-activated tapes	3 in
W200	Electronic dispenser — dispenses a pre-set length of water-activated tape at the push of a button	3 in
Specialty Tape Dispensers		
M707	Heavy duty metal dispenser with auxiliary holder and cutter for 3/4-inch rolls of tape — commonly used with tapes 821 and 823	4 in
M727	Metal construction provides easy dispensing of pouch tapes 824, 827 and 829	5 in
M797	Metal construction provides easy dispensing of pouch tape 827	6 in
P400	Bag sealer — applies tape in an adhesive-to-adhesive — flag seal (includes bag trimmer)	3/4 in

3M Systems Tape Agreement

When you switch to Scotch® packaging tape and sign up for a 3M Systems Tape Agreement, you can receive no charge equipment, parts or taping heads for your case sealers.*

* Terms & Conditions apply

Earn spare parts/tape heads

- Earn no-charge spare parts for your 3M-Matic™ Case Sealer when you purchase qualifying amounts of Scotch® Box Sealing Tape.
- Earn no-charge 3M™ AccuGlide™ Taping Heads for your 3M-Matic™ Case Sealer when you purchase qualifying amounts of Scotch® Box Sealing Tape.

Earn credit

- Earn credits towards a new 3M-Matic™ Case Sealer.

To learn more about the
3M Systems Tape Agreement,
visit: [3M.com/STA](https://www.3m.com/STA).



Contact your 3M packaging specialists for more details about these great offers.



Right tape. Right system. Right partner.

Take your packaging process to the next level.

Purchase qualifying amounts of Scotch® Box Sealing Tape and receive no charge equipment, parts or taping heads for your case sealers.

Core Products (371, 311+)			Premium Products (313, 315, 355, 371+, 373+, 375+)		
Offer type	Product	No Charge Quantity	Offer type	Product	No Charge Quantity
When you buy 1 pallet			When you buy 1 pallet		
3M-Matic™ Credit	\$250 USD / \$330 CAD Credit	1	3M-Matic™ Credit	\$1,000 USD / \$1,320 CAD Credit	1
Hand Dispensers	Case of Hand Dispensers	1	Hand Dispensers	Case of Hand Dispensers	2
Spare Parts Kit	3M™ AccuGlide™ or 3M-Matic™ SPK	1	Spare Parts Kit	3M™ AccuGlide™ or 3M-Matic™ SPK	1
When you buy 2 pallets			When you buy 2 pallets		
Taping Head	3M™ AccuGlide™ 2	1	Taping Head	3M™ AccuGlide™ 2	1
	3M™ AccuGlide™ 2+	1		3M™ AccuGlide™ 2+	1
	3M™ AccuGlide™ 3	1		3M™ AccuGlide™ 3	1
	3M™ AccuGlide™ NPH	1		3M™ AccuGlide™ 2+ SST	1
3M™ AccuGlide™ NPH+	1	3M™ AccuGlide™ NPH		1	
				3M™ AccuGlide™ NPH+	1
				3M™ AccuGlide™ NPH SST	1
When you buy 3 pallets			When you buy 2 pallets		
Specialty Taping Head	3M™ AccuGlide™ 2+ SST	1	Specialty Taping Head	3M™ AccuGlide™ 6W	1
	3M™ AccuGlide™ V HSP	1		3M™ AccuGlide™ V HSP	1
	3M™ AccuGlide™ NPH SST	1		3M™ AccuGlide™ HST (Black / Blue)	1
When you buy 4 pallets			When you buy 12 pallets		
Specialty Taping Head	3M™ AccuGlide™ 6W	1	Equipment (one machine per customer per calendar year)	2000a	1
	3M™ AccuGlide™ HST (Black / Blue)	1		7000a	1
When you buy 24 pallets				8000a	1
Equipment (one machine per customer per calendar year)	2000a	1		8000ab	
	7000a	1		8000asb	
	8000a	1		S867	1
	8000ab	1		S867-II	1
	8000asb	1	When you buy 18 pallets		
	S867	1	Equipment (one machine per customer per calendar year)	8000r	1
S867-II	1	7000r		1	
		8000af		1	
When you buy 32 pallets					
Equipment (one machine per customer per calendar year)	8000r	1			
	7000r	1			
	8000af	1			



Box Sealing Tapes

Delivering quality with tapes that keep production lines moving with less interruption and ensure packages are sealed on arrival.



The full job of a package is containment, protection and communication.

Technology that really delivers.

- Seal cartons reliably without the mess, dwell time and equipment maintenance of hot melt adhesive
- Two choices of pressure sensitive adhesive, each with a different combination of properties
- Backing choices for specific performance properties

3M eliminates 99% of organic solvents in production of Scotch® Box Sealing Tape.

Our Scotch® Recycled Corrugate Tape 3073 is made with an adhesive that contains over 10% bio-based content. All recycled corrugate tapes use recycled materials in the core to help with your sustainability goals.

Visit [3M.com/sustainability](https://www.3m.com/sustainability) for more goals.



Caring for the environment now and for the future.

Scotch® Box Sealing Tapes solve common package sealing problems:




Problem: Tabbing

Solution: Easy unwind and high initial adhesion of Scotch® Box Sealing Tapes reduce tabbing downtime and rework.




Problem: Tape popping

Solution: Initial adhesion and holding power of Scotch® Box Sealing Tapes ensure a secure sealing throughout a supply chain.



Problem: Unconventional box closure

Solution: Scotch® Box Sealing Tapes close securely without the holes, waste, appearance, sharp points and disposal of staples.



Problem: Temperature/Humidity

Solution: Scotch® Box Sealing Tapes resist moisture encountered in storage and shipping through the supply chain.

Tape Backing and Adhesive Selection Guide

Step 1 Select Tape Backing	Polyester	<ul style="list-style-type: none"> • Strongest backing • Excellent abrasion resistance • Moisture and chemical resistance 	<ul style="list-style-type: none"> • Highest temperature resistance • Transparency
	Polypropylene	<ul style="list-style-type: none"> • Strong backing • Good abrasion resistance • Good conformability 	<ul style="list-style-type: none"> • Most economical • Transparency
Step 2 Select Tape Adhesive	Synthetic Rubber	<ul style="list-style-type: none"> • Excellent holding power • Good initial adhesion above 40°F • Meets ASTM D-5486 government specification 	
	Acrylic	<ul style="list-style-type: none"> • Excellent initial adhesion over a broad temperature range • Extremely long performance life • High UV and chemical tolerance 	

Delivering service and support to help you select the right 3M product for your application. On-site consultation with experienced 3M engineers and sales specialists are standing by to help.

Box Sealing Tape Selector

Use this selector to help determine a box sealing tape that meets your packaging needs. **The suggestions provided by this method must be confirmed by testing.** Additional packaging and shipping factors should also be considered.

Circle the point value that best describes your operations		
	Point Value	Points
1. How much does the filled box weigh?		
a. 10 pounds	10	
b. 20 pounds	20	
c. 30 pounds	25	
d. 40 pounds	30	
e. 50 pounds	35	
f. 70 pounds	45	
g. 80 pounds	50	
h. 100 pounds	60	
2. What is the carton burst/ECT test?		
a. 150 SW/26	5	
b. 175 SW/29	10	
c. 200 SW/32	15	
d. 250 SW/40	20	
e. 275 SW/44	25	
f. 350 SW/55	30	
g. 200 DW/42	35	
h. 275 DW/48	40	
i. 350 DW/51	45	
3. What is the value of contents?		
a. <\$100	10	
b. \$100-\$1000	25	
c. >\$1000	40	
4. What is the method of shipment?		
a. Palletized and unitized	5	
b. Palletized but not unitized	15	
c. Single	30	
5. Type of carrier		
a. Company truck	5	
b. Commercial transport/LTL	15	
c. UPS/USPS/FEDEX	30	
Total Points		

Choose an effective closure...choose 3M		
205		
195		72mm
180		
165	72mm	
150		48mm
135		
120	48mm	
105		
90	72mm	42mm
75		
60	48mm	
45		36mm
	42mm	
35		
	36mm	
	Scotch® Box Sealing Tape Recommended for Testing	
Your Total Points	3071	373
	371	313
	371+	3073
	311+	355

These suggestions are based on experience, but there are factors which could alter the overall performance. **For example:**

Cartons with center seam gap greater than 3/4" or over packed/under packed cartons should be tested with 3" (72mm) wide tape

Hard-to-stick surfaces and Recycled Corrugate Boxes, test Scotch® Recycled Corrugate Tape 371+, 3071 and 3073

Box sealing tapes are available custom printed and with standard security messages

Applications when tape is applied under 40°F, test Scotch® Box Sealing Tape 311+, 373+ and 375+

If your package is unusual in size, shape, or load, try the 3M Technical Service Request (TSR) Program. Using the 3M TSR Program, a 3M representative will work with you on initial testing of a Scotch® Box Sealing Tape. One or two best options will be identified then a sample of your substrate is brought to the 3M Laboratories and tested for stress or other factors the product will encounter. The 3M test results will help you select the best box sealing tape for your manufacturing process and customer needs.



Scotch® and Tartan™ Box Sealing Tapes


Dependability for eCommerce, fulfillment, food and beverage, pharmaceuticals, electronics and more.

With choices of polyester or polypropylene backings and synthetic rubber or acrylic adhesives, you have dependability for a wide variety of box types, sizes, contents, handling situations and storage conditions.

- Reliability even with the stresses of over packed or under packed boxes
- Quick, easy application by hand, manual dispensers or 3M-Matic™ Case Sealers
- Choice of lengths, widths, backings, adhesives and colors to meet specific needs



Consistent quality of Scotch® Box Sealing Tapes means fewer interruptions on your packaging line.



Scotch® Box Sealing Tapes with polyester backing and synthetic rubber adhesive resist the moisture in storage and shipping.



Product	Tape Structure (Backing/Adhesive)	Tape Class	Adhesion to Steel oz/in (N/100mm)	Tensile Strength lbs/in (N/100mm)	Elongation at Break (%)	Backing Thickness mils (mm)	Total Thickness mils (mm)	Available Colors/Comments
ASTM Test Method			D-3330	D-3759	D-3759	D-3652	D-3652	
220								
Scotch® Box Sealing Tapes								
311+	Polypropylene/Acrylic	Medium Duty	38 (42)	25 (438)	125	1.1 (0.028)	2.05 (0.052)	Clear, Tan
371+	Polypropylene/Synthetic Rubber	Medium Duty	45 (49.3)	22 (385)	160	1.2 (0.030)	2.1 (0.053)	Clear or Custom Printed
373+		Heavy Duty	50 (54.9)	30 (525)	160	1.6 (0.041)	2.5 (0.060)	Clear or Custom Printed: Adhesive contains 10% renewable components
375+		Ultra-Heavy Duty	55 (60)	35 (613)	160	2.0 (0.051)	3.1 (0.079)	Clear, Tan or Custom Printed
Scotch® Performance Grade Box Sealing Tapes								
371	Polypropylene/Synthetic Rubber	Medium Duty	40 (44)	22 (385)	160	1.2 (0.030)	1.8 (0.046)	Clear, Tan, Blue, Green, Orange, Red, White, Yellow or Custom Printed
373		Heavy Duty	55 (55)	30 (525)	160	1.6 (0.041)	2.5 (0.064)	Clear, Tan, Blue, Green, Orange, Red, White, Yellow or Custom Printed
375		Ultra-Heavy Duty	55 (60)	35 (613)	160	2.0 (0.051)	3.1 (0.079)	Clear, Tan or Custom Printed
Scotch® Polyester Box Sealing tapes								
353	Polypropylene/Synthetic Rubber	Heavy Duty	45 (49)	25 (438)	110	1.0 (0.025)	1.9 (0.048)	Clear, Tan or Custom Printed
355		Ultra-Heavy Duty	78 (85)	67 (1174)	130	2.0 (0.051)	3.43 (0.087)	Clear, Tan or Custom Printed
351		Heavy Duty with Government Spec	78 (85)	67 (1174)	130	2.0 (0.051)	3.43 (0.087)	Clear, Tan or Custom Printed
Scotch® Utility Grade Box Sealing Tapes								
313	Polypropylene/Acrylic	Heavy Duty	32 (35)	35 (613)	125	1.6 (0.041)	2.55 (0.065)	Clear
315		Heavy Duty	38 (41.5)	23 (403)	200	2.3 (0.058)	3.5 (0.089)	Clear
Tartan™ Box Sealing Tapes								
302	Polypropylene/Acrylic	Medium Duty	14 (15)	18 (309)	110	1.0 (0.025)	1.7 (0.042)	Clear
305		Medium Duty	16 (18)	18 (309)	110	1.0 (0.025)	1.8 (0.045)	Clear

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Scotch® Plus+ Series Tapes



Adheres to substrates containing up to 100% recycled corrugate



High tack, performance grade and fast grab



Added strength and value allows use of a single strip to confidently seal boxes



Compatible with 3M-Matic™ Case sealing equipment



311+ Pallet Shipment

Medium Duty Heavy Duty Ultra-Heavy Duty

Engineered for everyday use and to perform when applied at cold temperatures

- Palletized shipments
- Performance-grade acrylic
- Everyday use
- Great value for the dollar

371+ Pallet Shipment

Medium Duty Heavy Duty Ultra-Heavy Duty

Designed to seal quickly and securely

- Palletized shipments
- Quick stick hot melt adhesive
- Available in custom printing

373+ Private Single Parcel Carrier

Medium Duty Heavy Duty Ultra-Heavy Duty

Developed to withstand the stresses over and under-packed of boxes

- High value palletized shipments
- Quick stick hot melt adhesive
- Box weight up to 80lbs*
- Private single-parcel carrier
- Available in custom printing

375+ 3-Party Carrier (Land, Sea, Air)

Medium Duty Heavy Duty Ultra-Heavy Duty

Created for ultimate strength in the toughest commutes

- Tough commute shipments
- Quick stick hot melt adhesive
- Box weight up to 100lbs*
- Third-party carrier
- Available in custom printing



High Tack Box Sealing Tapes Comparison Guide

Product	Tape Structure (Backing/Adhesive)	Tape Class	Adhesion to Steel oz/in (N/100mm)	Tensile Strength lbs/in (N/100mm)	Elongation at Break (%)	Backing Thickness mills (mm)	Total Thickness mills (mm)	Available Colors/Comments	Custom Printed	Underfill Box	Overfill Box	Recycled Corrugate	Rough Commutes	Compatible with 3M-Matic™ Equipment
ASTM Test Method			D-3330	D-3759	D-3759	D-3652	D-3652							
311+	Polypropylene/Acrylic	Medium Duty	38 (42)	25 (438)	125	1.1 (0.028)	2.05 (0.052)	Clear, Tan				●		●
371+	Polypropylene/Synthetic Rubber	Medium Duty	45 (49.3)	22 (385)	160	1.2 (0.030)	2.1 (0.053)	Clear, Tan or Custom Printed	●	●	●			●
373+		Heavy Duty	50 (54.9)	30 (525)	160	1.6 (0.041)	2.5 (0.060)	Clear, Tan or Custom Printed; made with 10% bio-based adhesive	●	●	●	●	●	●
375+		Ultra Heavy Duty	55 (60)	35 (613)	160	2.0 (0.051)	3.1 (0.079)	Clear, Tan or Custom Printed	●	●	●	●	●	●

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.



Scotch® Custom Printed Box Sealing Tapes

Let them know exactly who the package came from.

With every delivery, Scotch® Custom Printed Box Sealing Tape helps you differentiate your packages from the competitors. Whether you include your logo, tagline or other promotional messaging, your package will surely get noticed.

- Printed message won't rub off during transit
- Can be used to print handing instructions or labeling, replacing the need to carry large inventories of various printed cartons
- Adds security by discouraging tampering



Scotch® Box Sealing Tapes can be custom printed in up to 10 colors. Choose from the entire library of Pantone® Inks to match your logo brand or theme.

- Easily conforms around edges ✓
- Strong seal on rough surfaces ✓
- Holds through wide temperature variations ✓
- Resists moisture in storage and shipping ✓
- Resists nicks and abrasions ✓
- Ideal for food and beverage ✓
- Quick, easy application ✓

Product	Tape Structure (Backing/Adhesive)	Tape Class	Adhesion to Steel oz/in (N/100mm)	Tensile Strength lbs/in (N/100mm)	Elongation at Break (%)	Backing Thickness mils (mm)	Total Thickness mils (mm)	Available Colors/Comments
ASTM Test Method			D-3330	D-3759	D-3759	D-3652	D-3652	
371+CP	Polypropylene/ Synthetic Rubber	Medium Duty	45 (49.3)	22 (385)	160	1.2 (0.030)	2.1 (0.053)	Clear or Custom Printed
373+CP		Heavy Duty	50 (54.9)	30 (525)	160	1.6 (0.041)	2.5 (0.060)	Clear, Tan or Custom Printed: made with 10% bio-based adhesive
375+CP		Ultra-Heavy Duty	55 (60)	35 (613)	160	2.0 (0.051)	3.1 (0.079)	Clear, Tan or Custom Printed
371CP	Polypropylene/ Synthetic Rubber	Medium Duty	40 (44)	22 (385)	160	1.2 (0.030)	1.8 (0.046)	Clear, Tan, Blue, Green, Orange, Red, White, Yellow or Custom Printed
373CP								
3715CP								
353CP	Polyester/ Synthetic Rubber	Heavy Duty	45 (483)	25 (438)	110	1.1 (0.025)	1.9 (0.048)	Clear, Tan
355CP		Ultra-Heavy Duty	78 (85)	67 (1174)	130	2.0 (0.051)	3.43 (0.087)	Clear, Tan or Custom Printed


PANTONE® is the property of Pantone LLC.

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Scotch® Cold Temperature Tape

Extreme performance even in cold temperatures.

- Adheres to a variety of surfaces, including on corrugated boxes with over 70% recycled content.
- Can be applied at freezer and refrigeration temperatures of 20°F to 50°F (-6.6°C to 10°C).
- Once applied, performs well on fiberboard boxes subjected to temperatures below 32°F (0°C).
- Quick, easy application by hand, manual dispensers or 3M-Matic™ Case Sealers.
- Moistened adhesive interacts with porous surfaces to form a powerful, secure bond
- Tape forms a tamper-evident seal that shreds if an attempt is made to pull it off before delivery
- Paper construction is easy to handle, making it ideal for hand applications
- Boxes are sealed secure, yet easy to open without cutting tools
- Coreless rolls reduce waste and simplify roll changes



246



226



102

For box packing, sealing and storage below 40°F, Scotch® Box Sealing Tape 311+ seal with a rubber adhesive modified for reliability in the cold.

Product	Tape Structure (Backing/Adhesive)	Tape Class	Adhesion to Steel oz/in (N/100mm)	Tensile Strength lbs/in (N/100mm)	Elongation at Break (%)	Backing Thickness mils (mm)	Total Thickness mils (mm)	Available Colors/Comments
ASTM Test Method			D-3330	D-3759	D-3759	D-3652	D-3652	
311+	Polypropylene/Acrylic	Medium Duty	38 (42)	25 (438)	125	1.1 (0.028)	2.05 (0.052)	Clear

103



228



3M™ Water Activated Tapes



230

Simplify your packing operations with a proven solution.

3M™ Water Activated Tapes are an easy, economical answer to a wide variety of basic carton sealing challenges.

Product	Tape Structure (Backing/Adhesive)	Basis Weight	Caliper (mils)	Tensile Strength (lbs / in)	Tear Strength (grams)	Available Colors/Comments
ASTM Test Method		D-646	D-645	D-5803	D-1922	
Water Activated Tapes						
6141	Paper backing/gummed modified cornstarch based adhesive	35	3.5	30	72	Kraft (Tan) or Custom Printed
6142		60	5.5	44	125	
6143		90	7.5	58	200	
6144	Paper backing with filament reinforcement/gummed modified cornstarch based adhesive	23 / 23	4.9	45-50	N/A	Kraft (Tan) or Custom Printed
6145		23 / 23 (Kraft) 30 / 23 (White)	5.0 (Kraft) 7.3 (White)	52-57	N/A	Kraft (Tan), White or Custom Printed
6146		30 / 23	6.5	60-65	N/A	Kraft (Tan) or Custom Printed
6147		23 / 23 (Kraft)	8.5	60-65	N/A	Kraft (Tan) or Custom Printed

Product	Tape Structure (Backing/Adhesive)	Tape Class	Adhesion to Steel oz/in (N/100mm)	Tensile Strength lbs/in (N/100mm)	Elongation at Break (%)	Backing Thickness mils (mm)	Total Thickness mils (mm)	Available Colors/Comments
ASTM Test Method			D-3330	D-3759	D-3759	D-3652	D-3652	
Security Tapes								
373+ Printed	Polypropylene/ Synthetic Rubber	Heavy Duty	50 (55)	30 (525)	160	1.6 (0.041)	2.5 (0.064)	Tan with Red Type: IF SEAL IS BROKEN CHECK CONTENTS BEFORE ACCEPTING Adhesive contains 10% renewable components
3771		Medium Duty	40 (44)	22 (385)	160	1.2 (0.030)	1.8 (0.046)	White with Red Type: IF SEAL IS BROKEN CHECK CONTENTS BEFORE ACCEPTING
3772			40 (44)	22 (385)	160	1.2 (0.030)	1.8 (0.046)	White with Red Type: FRAGILE HANDLE WITH CARE
3775			40 (44)	22 (385)	160	1.2 (0.030)	1.8 (0.046)	White with Red Type: MIXED MERCHANDISE ENCLOSED
3779			40 (44)	22 (385)	160	1.2 (0.030)	1.8 (0.046)	Clear with Red Type: CHECK SEAL BEFORE ACCEPTING
3199	Polypropylene/ Acrylic		22 (24)	25 (701)	125	1.1 (0.028)	2.05 (0.052)	Clear with Red Type: CHECK SEAL BEFORE ACCEPTING

Scotch® Security Tapes

Deter package tampering.

Scotch® Security Box Sealing Tapes are ideal for sealing packages and securing loads with high value contents. Printed messages communicate the need for careful package inspection prior to acceptance and reduce theft during the shipping process. Available with a variety of pre-printed messages.



227

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Light Duty Packaging Tapes

Versatility with choices of film backings and adhesives for application success.

Typical Light Duty Applications

- Garment bundling
- Plastic bag closure
- Party tray closure
- Small box closure
- Document envelope closure
- Inner pack box closure



Variety of Surfaces

- Fabrics
- Molded plastics
- Metals
- Clay-coated paperboard
- Corrugated
- Vinyl and films



231

Scotch® Light Duty Packaging Tape 640+ Clean Removal

UPVC backing with clean removal acrylic adhesive for a wide variety of fabric finishes and treatments, including for tabbing shirts and underwear.



232

Scotch® Light Duty Packaging Tape 605 Cold Temperature

Polypropylene backing with acrylic adhesive for cold temperature applications, such as closing a plastic tray lid.



233

Scotch® Light Duty Packaging Tape 600 High Clarity

A transparent film tape designed for a variety of general industrial applications. The UPVC backing material is moisture, chemical and UV resistant. The acrylic adhesive provide clean removability from a wide variety of surfaces.

Scotch® Color Coding Tape 690

UPVC backing with natural rubber adhesive for sealing and color coding.



234



Light Duty Packaging Tapes

Product	Color	Backing Material	Backing Thickness mils (mm)	Total Thickness mils (mm)	Tensile Strength lb/in (N/100mm)	Adhesive Type	Adhesion to Steel oz/in (N/100mm)	Elongation (%)	Typical Use	Comments
Light Duty Packaging Tapes										
600	Clear	UPVC	1.5 (0.038)	2.3 (0.058)	28 (490)	Acrylic	32 (35)	45	L-Clip closure, attaching, tabbing and holding	Excellent handling, high clarity and long aging
605	Clear	Polypropylene	1.6 (0.041)	2.5 (0.064)	22 (385)	Acrylic	27 (30)	57	Cold temperature packaging	Cold temperature applications; Complies to FDA Regulations for indirect food contact
640	Clear	UPVC	1.2 (0.030)	1.9 (0.048)	32 (560)	Acrylic	22 (25)	65	Tabbing and holding of apparel	Clean removal from wide variety of fabrics and substrates
640+	Clear	UPVC	1.2 (0.030)	1.9 (0.048)	32 (560)	Acrylic	22 (25)	65	Tabbing and holding of apparel	Clean removal from wide variety of fabrics and substrates
681	Clear	UPVC	1.5 (0.038)	2.4 (0.061)	25 (438)	Natural Rubber	40 (44)	35	Sealing	Resists moisture and chemicals; Heat shrinkable; Complies with US FDA 21 CFR 175.105 for indirect food contact
690	Black, Blue, Green, Red, Yellow, White	UPVC	1.5 (0.038)	2.3 (0.058)	35 (613)	Natural Rubber	30 (33)	45	Color coding	Resists moisture and chemicals; Heat shrinkable
856	Transparent	Polyester	1.0 (0.025)	2.0 (0.051)	25 (438)	Acrylic	20 (22)	90	Tough backing for good tear resistance	Tough backing for good tear resistance
5910	Clear	Polypropylene	1.2 (0.030)	2.0 (0.051)	18 (315)	Acrylic	16 (17)	90	Utility grade for light duty packaging	Conforms easily
Fingerprint Lifting Tape										
8004	Clear	Polypropylene	1.4 (0.036)	2.0 (0.051)	18 (315)	Acrylic	16 (17)	90	Ultra clear tape; Handles easily	Lift and preserve physical evidence such as fingerprints


Technologies matched to the applications.

Choice of Backings

- UPVC for transparency plus moisture, chemical and UV resistance; non-staining and heat-shrinkable
- Polypropylene for transparency plus conformability and flexibility
- Cellophane for heat resistance
- Polyester for strength and abrasion resistance

Choice of Adhesives

- Acrylic for long aging and UV resistance
- Rubber for high initial bond strength and adhesion to wide variety of materials including hard-to-bond plastics



200

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.



Custom Packaging Solutions

3M™ Carry Handles

Applied at Retail Checkout

Convenience for your customer.

- Pre-cut padded carry handles for easy application
- Quickly and easily transform bulky purchases into travel-friendly packages
- Custom print! Put your BRAND in consumer's hands
- Custom size to meet your store profile
- Great alternative to large retail shopping bag. Save a bag...get a handle
- Reduce single-use plastic and plastic waste by up to 74%

*Based on the weight of a large plastic bag of 17.5 grams vs. 3M™ Carry Handle weight of 4.5 grams.



Pre-Applied By Manufacturer


Give your products a lift.

- Differentiate your on-shelf appeal — customers will associate convenience with your brand
- Easily combine two stand up pouches for a unique duo-pouch solution
- Printed handles communicate — drive brand awareness, augment or replace other package information
- Convenience: Promo packs and up-sized SKUs can be easily carried from store to car or bus to home or office
- Ask your 3M Packaging Specialist for details on automated application equipment



Range of carry handle options — pre-cut (hand applied) or in-line pre-laminated (machine applied)

3M™ Carry Handles



Weight

carry handle **4.5g**


large retail plastic bag **17.5g**

Reduce plastic waste by **74%**



Pre-cut padded carry handles for hand application.

Product	Weight Holding Capacity (lbs)	Tape Material	Total Thickness mils (mm)	Tensile Strength lb/in (N/100mm)	Adhesive Type	Adhesion oz/in (N/100mm)	Pads per Case	Handles per Case	Handle (W x L)	Tape Leg Length
ASTM Test Method			D-3652	D-3759	D-3330					
8310	10	Polypropylene	3.1 (0.079)	35 (613)	Synthetic Rubber	55 (60)	110	2750	1" x 17"	3"
8315	15	Polypropylene	3.1 (0.079)	35 (613)	Synthetic Rubber	55 (60)	80	2000	1-3/8" x 23"	6"
8320	20	Polyester	3.5 (0.089)	67 (1174)	Synthetic Rubber	78 (85)	110	2750	1" x 17"	3"
8330	30	Polyester	3.5 (0.089)	67 (1174)	Synthetic Rubber	78 (85)	80	2000	1-3/8" x 23"	6"
8350	50	Filament Tape	7.7 (0.196)	270 (4728)	Synthetic Rubber	80 (88)	80	2000	1-3/8" x 23"	6"



In-line carry handles for automated application. Enables quick change over of marketing message.

Product	Weight Holding Capacity (lbs)	Tape Material	Adhesive Type	Adhesion oz/in (N/100mm)	Tensile Strength lb/in (N/100mm)	Total Thickness mils (mm)	Roll Type	Roll (W x L)	Core Dia.
8346	20	Polyester	Natural Rubber	28 (30)	45 (786)	2.9 (0.073)	Level- wound	1" x 5470 yd	6"
8346HP	20	Polyester	Synthetic Rubber	52 (57.0)	57 (996)	3.4 (0.086)	Level- wound	1" x 5470 yd	6"
9009HP	20	Polypropylene	Synthetic Rubber	50 (55)	103 (1800)	2.55 (0.065)	Level- wound	1" x 7108 yd	6"



Pre-laminated carry handles for automated application. Perfect for long runs with limited change overs.

Product	Weight Holding Capacity (lbs)	Handle Material	Adhesive Type/Backing	Adhesion oz/in (N/100mm)	Tensile Strength lb/in (N/100mm)	Total Thickness mils (mm)	Roll Size/Format	Core Dia.	Suggested Use
8381	30	Multiple*	Synthetic Rubber/MOPP	55 (60)	97 (1709)	2.9 (0.073)	MAX OD 380mm (15")	6"	General purpose
8383	20	Multiple*	Synthetic Rubber/MOPP	48 (53)	90 (1580)	2.8 (0.071)	Plantery or Level-wound	6"	Apply on films

*Available materials include: paper (2 grades), clear polyethylene, white polyethylene, polypropylene foam or polyethylene foam.

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.



Scotch® Multipack Tapes




Economical and sustainable alternative to shrink films, banding, boxes and bags.

- Effective way to bundle consumer products into multipacks and value packs
- Clear, strong tape holds firmly and removes cleanly without damaging the primary package graphics



Discrete tape highlights primary packaging.

A Full Selection of Bundling Options



Custom carry handle option for convenience

Learn more about the Multipack Solution online. You'll find videos, and both tape and equipment details at [3M.com/Multipack](https://www.3m.com/Multipack)

Product	Color	Backing Material	Backing Thickness mils (mm)	Total Thickness mils (mm)	Tensile Strength lb/in (N/100mm)	Adhesive Type	Adhesion to Steel oz/in (N/100mm)	Elongation (%)	Comments
699	Clear	Polypropylene	1.6 (0.041)	2.6 (0.066)	30 (525)	Synthetic Rubber	46 (50)	160	Designed for bundling multi-unit primary packaging; Combine with 3M™ Carry Handles for bundling pouches; Apply manually or with automated equipment; 699CP is a custom printed version

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Tape Pads

No dispenser? No problem!

- **Portable** “peel and stick” convenience, 25 sheets per pad
- **Adheres** to bags, boxes, plastic film, powder coats, metals and glass
- **Removable tab** for easy handling
- **Stores easily** in pockets, drawers, tool boxes and part carts
- Used to repair, patch, seal, protect, reinforce, close and trap



3M™ Packaging Tape Pad 3750P



3M™ Tape Sheets 822




Product	Sheet Size(s)	Color	Tape Material	Total Thickness mil (mm)	Tensile Strength lb/in (N/100mm)	Adhesive Type	Adhesion Strength oz/in (N/100mm)	Elongation (%)	Tab
809G	Custom Size	Transparent, Red, Yellow	Polypropylene	3.1 (0.079)	35 (613)	Synthetic Rubber	55 (60)	160	Removable or Permanent
809GP	Custom Size w/Custom Print								
809S	Custom Size w/Custom Backsheet	Transparent	Polypropylene	3.1 (0.079)	35 (613)	Synthetic Rubber	55 (60)	160	Removable or Permanent
822	4" x 6"	Transparent	Polypropylene	3.1 (0.079)	35 (613)	Synthetic Rubber	55 (60)	160	Removable
3750P	2" x 6"								

3M™ Hang Tabs

- Clear, durable, polyester tabs with a pressure-sensitive adhesive for easy in-store repair of damaged packaging such as torn punches in chipboard header cards
- Clear tabs do not obscure packaging graphics — showcases existing packaging graphics and messaging
- Pre-cut, bendable tab format for convenience and ease of use
- Sticks to most product or packaging surfaces for store display applications



175

Hole Styles for Hang Tags		
 <p>J-Hook</p> <p>Consumer-friendly option, encourages item selection from anywhere on peg</p>	 <p>Round Hole</p> <p>For single-wire pegs</p>	 <p>Delta Hole</p> <p>For wider double-wire pegs or self-centers on standard pegs</p>



176

Product	Size (H x W)	Hole Style	Color	Hang Tabs per Pad	Backing Material	Total Thickness mil (mm)	Adhesive Type	Adhesion Strength oz/in (N/100mm)
1072	1-3/8" x 7/8"	J-Hook	Clear	Individual	Polyester	25.8 (0.66)	Synthetic Rubber	175 (192)
1074	1" x 2"	Round	Clear	10 per pad	Polyester	13.5 (0.34)	Synthetic Rubber	55 (60)
1075	2" x 2"	Delta	Clear	10 per pad	Polyester	13.5 (0.34)	Synthetic Rubber	55 (60)
1076	2" x 2"	Round	Clear	10 per pad	Polyester	13.5 (0.34)	Synthetic Rubber	55 (60)


Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.




Scotch® Pouch Tapes

Strong, low-profile attachment solution.

- “Trap it” with unique 3M tape construction — strong adhesive tape area on the edges frame the large, clear non-adhesive window area in the middle
- Attach documents, packing lists, invoices, literature, catalogs, brochures, or even product samples, small part packets or other merchandise
- Synthetic rubber adhesive sticks well to corrugate and many other substrates
- Custom-print option can personalize your message



Scotch® Pouch Tape Dispenser M727 with Scotch® Pouch Tape 824RCT — Available in rolls for easy dispensing at pack stations.



Scotch® Pouch Tape Sheets 830RCT are available in pads for portable back-pocket convenience. No liners help keep work areas clean of debris.

Product	Individual Pouch Size (h x w)	Printed Message	Applications	Core Size	Material Type	Total Thickness mils (mm)	Tensile Strength lb/in (N/100mm)	Adhesive Type	Adhesion Strength oz/in (N/100mm)	Dispenser Options
Pads										
830	5" x 6"	"Documents Enclosed"	25 per pad	—	Polypropylene	2.5 mil (0.064)	30 lb/in (525 N/100 mm)	Hot Melt Synthetic Rubber Resin	50 oz/in (54.7 N/100 mm)	—
830CP	5" x 6"	Custom Print	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
830RCT	5" x 6"	"Documents Enclosed"	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
	6" x 10"	"DOCUMENTS ENCLOSED"/"DOCUMENTOS ADJUNTOS"	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
	11" x 12"	"DOCUMENTS ENCLOSED"/"DOCUMENTOS ADJUNTOS"	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
830CN	5" x 6"	"DOCUMENTS ENCLOSED"/"DOCUMENTOS ADJUNTOS"	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
832	6" x 10"	"DOCUMENTS ENCLOSED"	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
832CP	6" x 10"	Custom Print	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
8240P	5" x 6"	"Packing List Enclosed"	25 per pad	—		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	—
Rolls										
824	5" x 6"	"Documents Enclosed"	333 per roll	3"	Polypropylene	2.5 mil (0.064)	30 lb/in (525 N/100 mm)	Hot Melt Synthetic Rubber Resin	50 oz/in (54.7 N/100 mm)	M727 or M797
8240	5" x 6"	"Documents Enclosed"	500 per roll	3"		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	M727 or M797
8240	5" x 8"	"Documents Enclosed"	500 per roll	3"		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	M727 or M797
	6" x 8"	"Documents Enclosed"	500 per roll	3"		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	M797
828CP	5" x 6"	Custom Print	—	3"		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	M727 or M797
	6" x 8"	Custom Print	—	3"		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	M727 or M797
829	5" x 6"	Packing List Enclosed	333 per roll	3"		2.5 mil (0.064)	30 lb/in (525 N/100 mm)		50 oz/in (54.7 N/100 mm)	M727 or M797

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Label Protection Tapes

Protect labeled shippers, mailers, envelopes, tubes, drums, tubs.

- Tape material options for use on wide range of substrates
- High clarity for sharp read-through accuracy
- Bright color tape option draws attention to important label content

Product	Roll Width(s) Available	Roll Length	Color	Backing Material	Total Thickness mils (mm)	Tensile Strength lb/in (N/100mm)	Adhesive Type	Adhesion Strength oz/in (N/100mm)	Elongation (%)	Comments
821	2", 3", 4", 5", 6"	72 yd	Pink	Acetate	2.5 (0.063)	12 (210)	Acrylic	25 (27)	15	Low-glare matte finish. Write-on surface; Hand-tearable — no dispenser needed
856	1", 1.5", 2", 3", 4", 6"	72 yd	Clear	Polyester	2.0 (0.051)	25 (438)	Acrylic	20 (22)	90	Excellent transparency and resistance to abrasion, moisture and chemicals; Go-to option for outdoor applications
3565	96mm, 120mm	100m	Clear	Polypropylene	1.9 (0.048)	22 (385)	Synthetic Rubber	40 (44)	160	Excellent transparency and conformability; Resists tearing, splitting, moisture, abrasion and smudges
3765	96mm, 120mm, 144mm	132m	Clear	Polypropylene	1.5 (0.038)	20 (350)	Acrylic	22 (24)	119	Good transparency; Recommended for cold temperature applications



242



3M™ Packing List Envelopes

Wide variety of choices for document control and protection.

- Convenient peel-and-stick document protection
- Non-printed and printed with standard messages
- Custom sizes and/or custom printed messages
- Reclosable 3M™ Zipper Closure Envelope is available in two sizes
- Polyethylene backing/synthetic rubber adhesive/paper liner
- Backing thickness: 2.0 mil; Total thickness: 5.0 mil



Easy Inspection — For cross border shipping and other inspection situations, zipper closure envelopes open easily and close securely. Tough construction resists moisture and abrasion.











Secure Adhesion — High tack pressure sensitive adhesive on the back of the envelope grabs on contact and holds securely even to curved and flexible surfaces.

T (Top Printed)

<p>T1 Packing List/ Invoice Enclosed 4.5" x 5.5" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	<p>T1 INV Invoice Enclosed 4.5" x 5.5" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	<p>T3 Packing List/ Invoice Enclosed 7" x 5.5" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>
<p>T1 PL Packing List Enclosed 4.5" x 5.5" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	<p>T2 Packing List/ Invoice Enclosed 4.5" x 6" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	<p>T4 Packing List/ Invoice Enclosed 5.5" x 10" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>

NP (Non-Printed)

<p>NP1 No Print (Clear) 4.5" x 5.5" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	<p>NP6 No Print (Clear) 9.5" x 12" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>
<p>NP2 No Print (Clear) 4.5" x 6" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	<p>NP9 No Print (Clear) 7" x 6" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">top-load</p>
<p>NP3 No Print (Clear) 5.5" x 7" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">top-load</p>	<p>FED1 No Print (Perfed) 6.75" x 10.75" 500/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">top-load</p>
<p>NP4 No Print (Clear) 5.5" x 10" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	
<p>NP5 No Print (Clear) 7" x 10" 1,000/case</p>  <p style="writing-mode: vertical-rl; transform: rotate(180deg);">side-load</p>	

F (Full Face Printed)

F1
Packing List/
Invoice Enclosed
4.5" x 5.5"
1,000/case



side-load

Zipper Closure Envelopes

<p>NPZ-L No Print (Clear) 8.5" x 11.5" 500/case</p>	<p>NPZ-XL No Print (Clear) 10" x 12.5" 500/case</p>
------------------------------------------------------------------------	------------------------------------------------------------------------



side-load



Sustainable Packaging Solutions



3M™ Sustainable
Packaging Solutions

A more responsible future for the packaging industry.

Consumers, government regulators, and corporations are all demanding more eco-friendly packaging. 3M is here to help you meet these challenges and deliver what your customers are asking for without sacrificing the performance you need and deserve.

Step by step.

We are with you on every step of your journey toward sustainability. Here are just a few of the ways our packaging solutions help you meet your goals:



We continue to develop packaging and products that are **reusable, renewable, recyclable**, or made with more recycled material.



We're creating solutions that can be **recycled after use** rather than discarded.



We offer packaging solutions that do more with less material, helping **reduce the environmental footprint** of the packaging industry.



Our manufacturing team is working to make production processes more **energy-efficient** and increase our usage of **renewable energy**.



3M™ Padded Automatable Curbside Recyclable (PACR) Mailer Material

Automatable for you. Simple for your customers.

The 3M™ Padded Automatable Curbside Recyclable (PACR) Mailer Material is a paper-based solution that delivers the protection and performance you need with the sustainability focus you want. Designed for use with automated packaging machines, it withstands the rigors of shipping while being automatable for you and simple for your customers.



184



Sustainability focused

- Certified recyclable just like paper or a cardboard box*
- Only uses a single layer of kraft paper
- Certified Repulpable by Western Michigan University with >99% fiber recovery
- Lightweight, which can help reduce carbon emissions in transit
- Supports right-sized packaging



Protective performance

- Proprietary padding technology
- Enables ISTA-3A certification
- Durable with strong protection against drops, bursts, vibration, and more
- Designed to resist moisture penetration
- Withstands the rigors of shipping



Automatable

- Facilitates fast and efficient operations
- Enables labor redeployment
- Heat sealable with potential dwell times under one second
- Compatible with a variety of printing technologies
- Available in a variety of widths

*Curbside recyclable where facilities are available

Introducing the NEW! Scotch® Performance Paper Tape 570

Striking the perfect balance between performance and sustainability.

Scotch® Performance Paper Tape 570 is an ideal alternative to conventional box sealing tapes when sustainability is a priority. Optimal for palletized and lightweight, single-parcel shipments.



Additional Features Include:

- Recycle-compatible when left on the box according to Western Michigan University (WMU) Recyclability testing.
- Features a strong backing made from responsibly sourced paper and a solvent-free hot melt adhesive.
- Reliably adheres to various surfaces, including cartons with high levels of recycled content
- Equally applicable for manual use and machine/automated processes



Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.



Glossary

This glossary is compiled by the Pressure Sensitive Tape Council (PSTC) and 3M (terms identified with an asterisk). PSTC is the North American trade association for tape manufacturers and affiliate suppliers, dedicated to helping the industry produce quality pressure sensitive adhesive tape products in the global marketplace. Visit [pstc.org](https://www.pstc.org) for more information.

Abrasion Resistance

The ability of a tape to withstand rubbing and still function satisfactorily.

Acrylic Adhesive*

A pressure sensitive, viscoelastic blend of acrylic-based materials which may be modified by tackifying additives. Acrylic adhesives are a very broad class of materials and come in many types to achieve different properties.

Adhesion to Backing

The bond produced to the backing of the same tape or another tape backing.

Adhesive Deposit or Residue

Adhesive that is pulled away from the tape upon removal and remains on the surface to which it has been applied.

Adjustable Case Sealer

A case sealer that must be manually adjusted for box width and height. Accepts runs of one box size at a time.

Article Letters*

Letters if a MSDS does not exist on a product.

Backing

A relatively thin flexible material to which the adhesive is applied. Theoretically, any material that is reasonably flat, thin and flexible can be used as a tape backing.

Backsize

An occlusive coating applied to the non-pressure sensitive side of a porous backing, such as paper, in order to provide a satisfactory surface that the pressure sensitive adhesive side can contact when the tape is wound into a roll.

Caliper

The thickness (as of a sheet of paper) measured under specified conditions. See also THICKNESS.

Co-extruded*

Refers to film extruded in individual layers with the possibility of different raw materials in each layer providing unique combined film properties.

Conformability*

The ability for a tape to make arcs, circles, go into depressions, go over protrusions and still stay in one piece without slivering or tape lifting or necking down.

Containment

To confine and hold in place.

Controlled Unwind*

When a balance is achieved between too low of an unwind, allowing the tape to prematurely unwind from its own backing, or too high, causing premature slivering or breaking when unwinding from its roll.

Elastomer

An elastic, polymeric substance, such as natural or synthetic rubber.

Elongation (Stretch, Ultimate Elongation)

The distance a tape will stretch in the machine or cross direction before breaking under controlled conditions, expressed as a percentage of original length. Elongation is not necessarily an indication of conformability.

Extruded*

A manufacturing process where material is forced through a nozzle (like extruded film or backing). Better for lay-flat than skived.

FOL

Full overlap.

Filaments

Thin, longitudinal yarns or threads of glass, polyester, nylon or other high strength materials.

Holding Power (Shear Adhesion, Shear Resistance)

The ability of a tape to resist static forces applied in the same plane as the backing. Usually expressed in a time required for a given weight and length of tape to shear free from a vertical panel.

Hot Melt (Pressure Sensitive Adhesive)

A pressure sensitive adhesive, applied to the backing in hot liquid form, which then cools to form a conventional pressure sensitive adhesive.

Humidity

The moisture content of the air. Actual humidity is the number of grams of moisture in the air at any given time. Relative humidity is the percent of moisture relative to the maximum that air at any given temperature can retain without precipitation.

Impact Resistance (Shock Resistance)

The ability of a tape to resist sudden impacts, pulls, or shocks as may sometimes be encountered by packages in transit.

L-Clip

Tape seal applied over the edge of non-RSCs with one leg down the side and the other on the top and/or bottom.

Moisture Vapor Transmission Rate

A measure of the rate of water vapor transmission through a pressure sensitive product usually measured in grams per square meter per 24 hours.

MOPP

Monoaxially-oriented polypropylene tape construction.

NPE*

An NPE number is used to designate an experimental product. NPE products are often provided to customers for evaluation purposes only, and may or may not be commercialized.

Non-RCS

All box structures other than RSC (Regular Slotted Carton).

Off-Core

A roll of tape in which the layers are in correct alignment, but the tape is displaced sideways on the core.

Opacity

The ability of a tape to prevent the transmission of light.

Pad

Pre-cut, tape strips stacked on a pad for easy one-at-a-time removal.

*Compiled by 3M.

Glossary

PE*

The abbreviation for polyethylene. Usually extruded in a single (mono) layer.

Peel Adhesion

The force per unit width required to break the bond between a pressure sensitive adhesive tape and the surface to which it has been applied when the tape is peeled back at a controlled angle at a standard rate and condition.

PLE

Packing List Envelope.

Pouch Tape

Tape with adhesive-free area within a perimeter of pressures sensitive adhesive. When applied the adhesive-free area forms a containment pouch.

PP*

Abbreviation for polypropylene. Usually manufactured as a single (mono) layer via a casting process.

Pressure Sensitive

A term commonly used to designate a distinct category of adhesive tapes and adhesives which in dry form (solvent/ water free) are aggressively and permanently tacky at room temperature and that firmly adhere to a variety of dissimilar surfaces upon mere contact without the need of more than finger or hand pressure. These products require no activation by water, solvent, or heat in order to exert a strong adhesive holding force toward such materials as paper, plastic, glass, wood, cement, and metal. They have sufficient cohesive holding power and elastic nature so that, despite their aggressive tackiness, they can be handled with the fingers and removed from smooth surfaces without leaving a residue.

Quick Stick (Finger Tack, Initial Adhesion, Wet Grab)

See TACK.

Random Case Sealer

A case sealer that automatically adjusts for case width and height. Typically used for runs of different box sizes.

Recouperage

To salvage goods within a container that has broken or opened during shipment.

Release Force

The measure of the force required to separate a unit width of pressure sensitive tape from a release coated surface at a controlled angle and speed.

Retroreflective

Surface, material, or device that reflects light back to its source.

RGT

Reinforced Gum Tape.

RSC

Regular Slotted Carton.

Rubber Adhesive*

A pressure sensitive, viscoelastic blend of polymeric rubber-based materials and tackifying resin. The rubber materials may be natural or synthetic. Rubber adhesives are a very broad class of materials and come in many types to achieve different properties.

Shear Adhesion

The time required, under specified test conditions (surface area, weight load), to slide a standard area of pressure sensitive tape from a standard flat surface in a direction parallel to the surface.

Single Faced (Coated)

A tape to which a pressure sensitive adhesive is applied to only one side of the backing.

Solvent/Chemical Resistant*

Ability to resist common solvents or chemicals.

Surface Energy (Surface Wetting Ability)

The measure of surface tension in dynes. The lower the surface energy of a substrate, the more difficult it becomes for an adhesive or coating to wet out that surface.

Tack

The property of a pressure sensitive adhesive that allows it to adhere to a surface under very slight pressure. It is determined by the ability of the adhesive to wet quickly the surface it contacts.

Tear Resistance

The force required to propagate a tear in a tape in a given direction after the tear has been initiated.

Telescoping

A sideways sliding of the tape layers, one over another, such that the roll looks like a funnel or a telescope, usually occurring over a period of time.

Tensile Strength

The force required to break a unit width of tape by controlled pulling on opposite ends of the piece.

Thickness (Caliper, Gauge)

The perpendicular distance from one surface of either a tape, backing or adhesive to the other, usually expressed in mils, thousandths of an inch or millimeters. This is usually measured under controlled slight pressure with a special gauge.

TSCA*

Toxic Substances Control Act.

U-Clip

Tape seal applied to an RSC carton with tape legs down both sides of the carton and across the center seam.

UL 723*

UL 723 deals mainly with flammability.

Unwind or Unwind Adhesion

The force required to remove tape from a roll under prescribed conditions.

Water Vapor Transmission (WVTR)

The weight of water vapor allowed through a controlled area of tape within a specified time period and under controlled conditions.

*Compiled by 3M.



Numerical Index

2000a.....	6,8	3775.....	27	HB900.....	17
2000a3.....	8	3779.....	27	HB901.....	17
302.....	23	5910.....	29	HB902.....	17
305.....	23	6141.....	27	HB903.....	17
311+.....	23, 24, 26	6142.....	27	HR80.....	17
313.....	23	6143.....	27	HR83.....	17
315.....	23	6144.....	27	HR933.....	17
351.....	23	6145.....	27	M82.....	17
353.....	23	6146.....	27	M96.....	17
355.....	23	6147.....	27	M707.....	17
355CP.....	25	7000a Pro.....	6, 8	M727.....	17
371.....	23	7000a3 Pro.....	8	M797.....	17
371+.....	23, 24	7000r HS Pro.....	7, 10	M900.....	17
371CP.....	25	7000r Pro.....	7, 10	M920.....	17
373.....	23	7000r3 HS Pro.....	10	P52.....	17
373+.....	23	7000r3 Pro.....	10	P52W.....	17
375.....	23	8000a.....	6, 9	P56.....	17
375+.....	23, 24	8000a3.....	9	P56W.....	17
375CP.....	25	8000ab.....	6, 9	P400.....	17
570.....	40	8000af.....	6, 9	P448.....	17
600.....	28, 29	8000af3.....	9	PACR.....	40
605.....	29	8000asb.....	6, 9	S634.....	17
640.....	29	8000r.....	7, 10	S867.....	7, 13
640+.....	29	8004.....	29	S867 II.....	7, 13
681.....	29	8310.....	32	W100.....	17
690.....	29	8315.....	32	W200.....	17
700a-s.....	6, 8	8320.....	32		
8000ab.....	6, 9	8330.....	32		
8000ab3.....	9	8346.....	32		
8000asb.....	6, 9	8346HP.....	32		
8000r.....	7, 10	8350.....	32		
8000r3.....	10	8381.....	32		
800rks.....	7, 10	8383.....	32		
809GP.....	34	C22.....	17		
809S.....	34	C23.....	17		
822.....	34	C25.....	17		
856.....	29, 36	H12.....	17		
1072.....	34	H121.....	17		
1074.....	34	H122.....	17		
1075.....	34	H123.....	17		
1076.....	34	H128.....	17		
3071CP.....	23	H131.....	17		
3073.....	22	H133.....	17		
3073CP.....	23	H150.....	17		
3199.....	27	H153.....	17		
3565.....	34	H180.....	17		
3750P.....	34	H183.....	17		
3765.....	36	H190.....	17		
3771.....	27	H192.....	17		
3772.....	27	H320.....	17		

Product Name Index

3M™ AccuGlide™ Taping Heads

2+	12
3	12
4	12
LHB	12
NPH	12
NPH+	12

3M-Matic™ Adjustable Case Sealers

2000a	8
7000a Pro	8
7000a3 Pro	8
700a-s	8
8000a	9
8000a3	9
8000af	9
8000ab	9
8000af3	9
8000asb	9

3M-Matic™ Random Case Sealers

8000r	12
8000r3	12
8000rks	12
7000r HS Pro	12
7000r Pro	12
7000r3 HS Pro	12
7000r3 Pro	12

3M™ Padded Automatable Curbside Recyclable (PACR) Mailer Material

PACR	40
------------	----

Box Sealing Tapes

311+	23
302	23
305	23
313	23
315	23
351	23
353	23
355	23
369	23
371	23
371+	23
373	23
375	23

Carry Handles

8310	32
8315	32
8320	32
8330	32
8346	32
8346HP	32
8350	32
8381	32
8383	32

Cold Temperature Tape

311+	26
------------	----

Custom Printed Box Sealing Tapes

355CP	25
371CP	25
373CP	25
375CP	25
3071CP	25
3073CP	25

Water Activated Tapes

6141	27
------------	----

Hang Tabs

1072	34
1074	34
1075	34
1076	34

Label Protection Tapes

821	36
856	36
3565	36
3765	36

Light Duty Packaging Tapes

600	28, 29
605	28, 29
640	28, 29
640+	28, 29
640+	28, 29
681	29
690	29
856	29
5910	29
8004	29

Manual Tape Dispensers

C22	17, 18, 19
C23	17, 18, 19
C25	17, 18, 19
H12	17, 18, 19
H121	17, 18, 19
H122	17, 18, 19
H123	17, 18, 19
H128	17, 18, 19
H131	17, 18, 19
H133	17, 18, 19
H150	17, 18, 19
H153	17, 18, 19
H180	17, 18, 19
H183	17, 18, 19
H190	17, 18, 19
H192	17, 18, 19
H320	17, 18, 19
HB900	17, 18, 19
HB901	17, 18, 19
HB902	17, 18, 19
HB903	117, 18, 19
HR80	17, 18, 19
HR83	17, 18, 19
HR933	17, 18, 19
M82	17, 18, 19
M96	17, 18, 19
M707	17, 18, 19
M727	17, 18, 19
M797	117, 18, 19
M900	17, 18, 19
M920	17, 18, 19
P52	17, 18, 19
P52W	17, 18, 19
P56	17, 18, 19
P56W	17, 18, 19
P400	17, 18, 19
P448	17, 18, 19
S634	17, 18, 19
W100	17, 18, 19
W200	17, 18, 19



Product Name Index

Non-RSC Closure Solutions

S867	13
S867II	13

Packing List Envelopes

F1	37
FED1	37
NP1	37
NP2	37
NP3	37
NP4	37
NP5	37
NP6	37
NP9	37
NPZ-L	37
NPZ-XL	37
T1	37
T1 INV	37
T1 PL	37
T2	37
T3	37
T4	37

Pouch Tapes

830RCT	35
--------------	----

Scotch® Custom Printed Box Sealing Tapes

311+	25
371+	25
3073	25

Reinforced Strapping Tapes

862	29, 33
863	33
864	33
865	33
8651	33

Scotch® Plus+ Series Tapes

311+	24
374+	24
373+	24
375+	24

Security Tapes

3199	27
3732	27
3771	27
3772	27
3775	27
3779	27

Scotch® Performance Paper Tape 570

8884	40
------------	----

Stretchable Tapes

8884	17
8886	17

Tape Pads

809G	34
809S	34
822	34
3750P	34

Water Activated Tapes

6141	27
6142	27
6143	27
6144	27
6145	27
6146	27
6147	27

We're here to help.

Need help finding the right product for your packaging needs? Contact us if you need product, technical or application advice or want to collaborate with a 3M technical specialist, or give us a call at 1-800-831-0658.

3M Custom Packaging Hotline: 1-800-253-2329

3M Industrial Technical Support: 1-888-726-8244

3M-Matic™ Application Support Helpline: 1-800-328-1390

3M-Matic™ and Tape Dispenser Replacement Parts: 1-800-344-9883

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M, 3M-Matic, AccuGlide, Scotchlite and Tartan are trademarks of 3M Company. Scotch is a registered trademark of 3M Company.



Industrial Specialties Division - Packaging
3M Center, Building 223-4NE
St. Paul, MN 55144-1000

Phone 800-362-3550
Fax 877-369-2923
Web 3M.com/Packaging

Please recycle. Printed in USA.
© 3M 2024. All rights reserved.
70-0710-0432-2 Rev Sept 2023