

INTERIOR

ARCHITECTURAL FILM

AURORA WINTER

Coloured - Dichroic — Interior Application, Cold Colour From Outside

With its dichroic and chameleon-like Aurora film changes in hue and observation. The Aurora decorative effect, bringing your windows and tones dichroic tint.

- 95% UV rejection with engineered light control
- Retains 72% visible light transmission
- Engineered and certified for professional interior installation
- 95% UV rejection helps protect interiors and furnishings from fading
- Cold Colour finish, engineered for interior application

Key Strengths

**95%**

UV Rejection

**72%**

Visible Light Transmission

**5 years**

Warranty

**M1**

Fire Resistance

Why Choose AURORA WINTER?

Coloured - Dichroic — engineered for professional interior application.

ADVANTAGES

- 95% UV protection
- Cold Colour finish
- Professional interior installation
- Improved visual comfort
- 72% visible light transmission retained

PERFORMANCE KEY — SINGLE 3MM, FILM APPLIED

95%

UV Rejection

72%

Visible Light Transmission

5 years

Warranty

M1

Fire Resistance

CHARACTERISTICS



Warranty
5 years



Fire Resistance Rating
M1



Storage (recommended conditions)
3 years



REACH / RoHS
Compliant



Widths Available
135 cm



Installation Type
Interior



Color From the Outside
Cold Colour



Length
30.5 m



Product Carbon Footprint (LCA)
1.56 kgCO₂e/m²

CONSTRUCTION — PET, 55 µm

1. Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
2. High optical quality dyed polyester
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, polymerizes with glass within 15 days
6. Protection PET release liner, disposable after installation

GLAZING RECOMMENDATIONS

Vertical situation, standard glazed surface up to 2.5 m².

Clear Single Pane	✓ Yes
Tinted Single Pane	! Caution
Reflective Tinted Single Pane	✓ Yes
Clear Double Pane	! Caution
Tinted Double Pane	! Caution
Reflective Tinted Double Pane	✓ Yes
Gas-Filled Double Pane - Low E	! Caution
Stadip Ext. Clear Double Pane	! Caution
Stadip Int. Clear Double Pane	× Not recommended

✓ Yes ! Caution × Not recommended

Advice based on glazed surface area up to 2.5 m² — contact us for confirmation or a thermal shock analysis on larger or atypical glazing.

INSTALLATION & MAINTENANCE

Use Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Learn more about FNX and our product catalog.



THERMAL COMFORT



UV PROTECTION



GLARE REDUCTION



ENERGY PERFORMANCE



SUPERIOR AESTHETICS



PROFESSIONAL INSTALL