



MADE  
IN  
FRANCE

# Safes, storage cabinets, security doors and locks...

2021 CATALOGUE

 ***Fichet-Bauché***



# Millium Duo

## BREAK-IN AND FIRE RESISTANCE

A dual-protection solution based on the Millium range, Duo safes ensure certified resistance against both fire and break-in attempts. Modular fittings enable you to define configurations always answering your specific requirements.



**+**

- Double certification
- Wide choice of locks
- Optimised weight

### PERFORMANCES

- A2P-certified break-in resistance as per EN 1143-1 (grade I/€25K cash rating).
- ECB-S certified fire resistance as per LFS 60P EN 15659 (60 min. for paper).
- A2P-certified mechanical and/or electronic locks as per EN 1300.

### SECURITE

- Door locked with a full-height bolt - operated with the central handle - and a rear bar on the hinge side.
- Wide choice of Fichet lock combinations.
- Alarm and opening management configurations can be factory fitted.

### ERGONOMIE

- Designed for easy opening operations (left hand on the handle, right hand on the key), command controls located in the upper section.
- Wide choice of interior fittings: shelves, lockable compartments, extensible frames for hanging files, etc.

Models	Millium Duo 40	Millium Duo 80	Millium Duo 120	Millium Duo 160	Millium Duo 240	Millium Duo 370
Interior capacity (litres)	43	77	107	154	235	363
Ext. height (mm)	495	615	816	1140	1135	1295
Ext. width (mm)	555	555	555	555	655	765
Ext. depth* (mm)	400	490	490	520	571	620
Int. height (mm)	405	525	725	1045	1045	1205
Int. width (mm)	460	460	460	460	560	670
Int. depth (mm)	230	320	320	320	401	450
Door opening at 90° (mm)	397	397	397	396	497	607
Grade 1 weight (kg)	109	145	165	230	270	375
Standard nb of shelves	1	1	2	3	3	3

\* Without handle and locks



# Millium

## BREAK-IN RESISTANCE

Designed for frequent functional use by retail or banking professionals, this modular range allows for customised configurations answering your technical purposes.



### CHARACTERISTICS

- Break-in resistance: EN 1143-1 certification (grades I/E to III/E for cash ratings from €25,000 to €55,000). Integrates seismic and electronic alarms.
- A2P certified locks as per EN 1300 (mechanical and/or electronic locks).
- Allows for the integration of DFX deposit heads (placed on top without compromising certification).
- Composite material allowing for reduced weight.
- RAL 7040 finish.

### SECURITE

- Door locked with a full-height bolt - operated with the central handle - and a rear bar on the hinge side.
- Wide choice of lock combinations.
- Alarm and opening management configurations can be factory fitted.
- Anchorage kit supplied for models below 1,000kg (as mandated per EN 1143-1).

### ERGONOMIE

- Designed for frequent, easy opening operations.
- Command controls located in the upper section.
- Wide choice of interior fittings: shelves, lockable compartments, extensible frames for hanging files, etc.

- Modular range
- Wide choice of locks
- Factory-fitted alarms and relockers
- Optimised weight

Models	Millium 40	Millium 80	Millium 120	Millium 150	Millium 160	Millium 240	Millium 250	Millium 370	
Interior capacity (litres)	43	77	107	157	154	235	243	363	
Exterior height (mm)	495	615	816	790	1140	1135	895	1295	
Exterior width (mm)	555	555	555	655	555	655	765	765	
Exterior depth* (mm)	400	490	490	571	520	571	620	620	
Weight (kg)	Grade I	175	245	302	376	390	480	494	684
	Grade II	190	262	328	394	440	530	543	700
	Grade III	-	288	370	432	502	600	615	810

\* Without handle and locks



# Carena

## BREAK-IN RESISTANCE

Carena safes offer sleek and elegant design—as well as reliable protection and extensive functionalities.



### CHARACTERISTICS

- Break-in resistance: EN 1143-1 certification (grades I/E to III/E for cash ratings from €25,000 to €55,000).
- A2P certified locks as per EN 1300 (mechanical and/or electronic locks).
- Patented 'Gradium' composite material compliant with European standards and allowing for an optimal weight/capacity ratio.

### SECURITY FEATURES

- Wide choice of certified locks.
- Door locked with a full-height bolt and rear bar on the hinge side.
- Thermal/seismic DOCT relockers for reinforced security (optional).
- Anchorage kit supplied for models below 1,000kg (as mandated per EN 1143-1).

### ERGONOMICS

- Door opens to 90° for full access.
- RAL 9005, leather finish and luxury fittings (optional).
- Interior lighting (optional).
- Easy opening with lateral or top-section grip.
- Wide choice of interior fittings: lockable compartments, sliding trays, extensible frames for hanging files, etc.

- Certified performance
- Wide choice of locks
- Optional 'Visio Pack' fittings
- Luxury leather finish

Models	Carena 40	Carena 80	Carena 120	Carena 160	Carena 370	
Interior capacity (litres)	43	77	107	154	363	
Exterior height (mm)	500	620	820	1140	1300	
Exterior width (mm)	555	555	555	555	765	
Exterior depth* (mm)	430	520	520	520	650	
Weight (kg)	Grade I	174	245	300	390	663
	Grade II	188	267	315	440	723
	Grade III	-	300	379	502	803

\* Without handle and locks



# Atrius

## BREAK-IN RESISTANCE

Derived from the InviKtus range and benefiting from a new and innovative barrier material, Atrius safes offer reduced weight without compromising on performance.



### CHARACTERISTICS

- Break-in resistance: EN 1143-1 certification (grades IV/E to V/E).
- Exclusive 'GradX' material (with RAL 7040 finish) allows for weight reduction while preserving high levels of resistance.

### SECURITY FEATURES

- Wide choice of certified mechanical and electronic locks as per EN 1300 (grades B or C for safe grades IV and V respectively).
- Anchorage kit supplied for models below 1,000kg (as mandated per EN 1143-1).

### ERGONOMICS

- Ergonomic positioning of locks and handles.
- Available in 5 sizes (14, 20, 30, 40 and 60 litres).

- Ergonomic use
- Wide choice of locks
- Factory-fitted alarms and relockers
- Optimised weight

Models		Atrius 14	Atrius 20	Atrius 30	Atrius 40	Atrius 60
Interior capacity (litres)		139	210	308	416	596
Exterior height (mm)		790	920	1270	1470	1850
Exterior width (mm)		730	730	730	810	880
Exterior depth* (mm)		640	740	740	740	740
Weight (kg)	Grade IV	615	775	1005	1225	1590
	Grade V	655	825	1075	1310	1695

\* Without handle and locks



# InviKtus

## BREAK-IN, FIRE AND BLAST RESISTANCE

Developed for high-risk protection, this range has been tested by leading independent European laboratories for certified resistance to the most sophisticated attacks. InviKtus safes offer maximum security.



### CHARACTERISTICS

- Break-in resistance: EN 1143-1 certification (grades III/E to VI/E).
- Fire resistance: NT Fire 017 certification for grade 60P (paper documents).
- Blast resistance: EN 1143-1 EX certification.

### SECURITY FEATURES

- Wide choice of certified mechanical and electronic locks as per EN 1300 (grades B/E or C/E depending on safe grades IV, V or VI).
- Anchorage kit supplied for models below 1,000kg (as mandated per EN 1143-1).

### ERGONOMICS

- Ergonomic positioning of locks and handles.
- Available in 6 sizes (14, 20, 30, 40, 60 and 120 litres).
- RAL 9005 finish.
- Wide choice of interior fittings: lockable drawers/compartments, sliding trays, extensible frames for hanging files, etc.



- High-risk solution
- Certified multi-resistance
- Wide choice of lock combinations
- Wide choice of interior fittings
- Superior design and finish

Models		InviKtus 14	InviKtus 20	InviKtus 30	InviKtus 40	InviKtus 60	InviKtus 120
Interior capacity (litres)		139	210	308	416	596	1117
Exterior height (mm)		790	920	1270	1470	1850	1850
Exterior width (mm)		730	730	730	810	880	1500
Exterior depth* (mm)		640	740	740	740	740	740
Weight (kg)	Grade III	600	745	970	1180	1530	2295
	Grade IV	615	775	1005	1225	1590	2380
	Grade V	655	825	1075	1310	1695	2535
	Grade VI	700	880	1150	1400	1810	2710

\* Without handle and locks