



OLA Accel XL 10 SAE 20W-50

High performance multigrade engine oil

Specification:

API SL/CF

Features and benefits:

OLA Accel XL10 reduces engine wear and protects it against rust and deposits build-up (soot, varnish, lacquer...).

Description:

OLA Accel XL10 is premium mineral multigrade oil that exceeds the last standards required in all modern engines. It is formulated with a propriety mixture of high refine base oil with additive technology that provides an excellent engine protection and cleanness.

Applications:

OLA Accel XL10 is recommended for gasoline and diesel modern engines requiring a level performance API SL/CF.

Typical properties:

	Test Method	Accel XL 10
Grade SAE		20W-50
Viscosity @ 40°C-cSt	ASTMD 445	140
Viscosity @ 100°C-cSt	ASTMD 445	17
Viscosity Index	ASTMD 2270	132
TBN - mg KOH/g	ASTMD 2896	8.4
Pour point °C	ASTMD 97	-33
Flash Point °C	ASTMD 92	236
Density @ 15°C - kg/l	ASTMD 4052	0,881

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.