

LEVEL II EV CHARGER

WALL MOUNT



5" LCD Display

Capacitive Touch
Buttons

NEMA 4X Weatherproof
Housing

16 ft Cable

J1772 Connector



LEVEL II EV CHARGER

WALL MOUNT

Quantum Unity's Level 2 AC charger is available in two powerful options: 11.5kW and 19.2kW. As the industry's premier vertically integrated manufacturer, Quantum Unity designs and builds every aspect of our chargers right here in the USA. With robust enterprise controls, seamless app integration, and user-friendly payment options, Quantum Unity sets the standard for advanced charging solutions.

EV CHARGER SPECS

- Level 2 AC Charger
- Maximum output : 11.5kw / 19.2kw
- Amperage : 48A / 80A
- Voltage : 240V Single Phase
- Management Software

ENVIRONMENTAL

- Environmental Rating : NEMA 4X
- Operating Environment : Fully Outdoor
- Operating Temperature : -22°F (-30°C) to 122°F (50°C)
- Operating Humidity : 5% to 100%
- Certifications: CSA C22.2 No. 280, CSA C22.2 No. 281.1, CSA C22.2 No. 281.2, UL 2594, UL 2231-1, UL 2231-2

USABILITY + DESIGN

- Single Port
- Connector Type : SAE J1772
- Cable Length : 16 ft
- OCPP Version : 1.6J
- Display : 5" Color LCD, 900 nits
- Payment Interface : App, Credit Card
- Capacitive Touch Buttons
- 2.4 Ghz WiFi (802.11 b/g/n)
- Dimension (WxHxD) : 8.5" x 15.5" x 6.25"
- Weight : 23 lbs (including charging cable and wall mount)
- Wall Holster Included
- Cord Management Holster (Optional)

