

SUNPOWER®



MONOLITH

REC ALPHA
PURE-RX SERIES
DATA SHEET

A New Dawn in Solar

The industry's most advanced residential solar panel. Combining SunPower's decades of solar innovation with REC's world-class manufacturing, "Monolith" marks a new dawn for residential solar performance.

470 W_P


22.6% HIGH EFFICIENCY

50 lbs SINGLE-MAN OSHA LIMIT

REC ALPHA® PURE-RX DATASHEET

Measurements in [inches] and mm

GENERAL DATA	
Cell Type	88 half-cut bifacial REC heterojunction cells, with gapless technology
Glass	0.13 in solar glass with anti-reflective surface treatment in accordance with EN12150
Backsheet	Highly resistant polymer (Black)
Frame	Anodized aluminum (Black)
Junction Box	4-part, 4 bypass diodes, IP68 rated, in accordance with IEC 62790:2020
Connectors	Stäubli MC4 PV-KBT4/KST4 (12 AWG) in accordance with IEC 62852:2014, IP68 only when connected
Cable	12 AWG solar cable, 59.1 in (1.50 m) + 59.1 in (1.50 m) in accordance with EN50618:2014
Dimensions	68.0 x 47.4 x 1.2 in (22.4 ft ²) / 1728 x 1205 x 30 mm (2.08 m ²)
Weight	50.0 lb / 22.7 kg
Origin	Made in Singapore



	PRODUCT CODE*: RECXXXAA PURE-RX		
	450	460	470
Power Output - P _{MAX} (W _p)	450	460	470
Watt Class Sorting - (W)	0/+10	0/+10	0/+10
Nominal Power Voltage - V _{MPP} (V)	54.3	54.9	55.4
Nominal Power Current - I _{MPP} (A)	8.29	8.38	8.49
Open Circuit Voltage - V _{OC} (V)	65.6	65.7	65.7
Short Circuit Current - I _{SC} (A)	8.81	8.88	8.95
Power Density (W/ft ²)	20.1	20.5	21.0
Panel Efficiency (%)	21.6	22.1	22.6
Power Output - P _{MAX} (W _p)	342	350	358
Nominal Power Voltage - V _{MPP} (V)	51.2	51.7	52.2
Nominal Power Current - I _{MPP} (A)	6.70	6.77	6.86
Open Circuit Voltage - V _{OC} (V)	61.8	61.9	61.9
Short Circuit Current - I _{SC} (A)	7.12	7.18	7.23

Values at standard test conditions (STC: air mass AM 1.5, irradiance 1000 W/m², temperature 25°C), based on a production spread with a tolerance of P_{MAX}, V_{OC} & I_{SC} ±3% within one watt class. Nominal module operating temperature (NMOD: air mass AM 1.5, irradiance 800 W/m², temperature 20°C, windspeed 1 m/s). * Where xxx indicates the nominal power class (P_{MAX}) at STC above.

TEMPERATURE COEFFICIENT*			
P _{MAX} -0.24%/°C	V _{OC} -0.24%/°C	I _{SC} 0.04%/°C	*The temperature coefficients stated are linear values

MODULE RATINGS	
Module Operating Temperature [T98]§	176°F (80°C)
Min Environmental Temperature	-40°F (-40°C)
Nominal Module Operating Temperature	44 ± 2°C
Max Hail Rating [ⓐ]	45 mm @ 30.7 m/s
System Voltage	1000 V
Max Series Fuse Rating	25 A
Max Reverse Current	25 A

§98th percentile operating temperature
[ⓐ]Based on third party testing

MAXIMUM TEST LOAD*	
Front (4-Point)*	+7000 Pa (146 lbs/ft ²)
Rear (4-Point)*	-4000 Pa (84 lbs/ft ²)
Front (6-Point)**	+10000 Pa (209 lbs/ft ²)
Rear (6-Point)**	-6000 Pa (125 lbs/ft ²)

Design load = Test load / 1.5 (safety factor)

*IEC61730/UL61730 certified. Refer to installation manual.
 **Internal testing. Refer to installation manual.


CERTIFICATIONS	
ISO 14001; ISO9001; IEC45001; IEC62941	
IEC 61215:2021; IEC 61730:2023; UL 61730	
IEC 61730	Fire Class C
ISO 11925-2	Ignitability (EN 13501-1 Class E)
IEC 62716	Ammonia Resistance
IEC 61701	Salt Mist (SM6)
IEC 61215:2021	Hailstone (35 mm)
UL 61730	Fire Type 2
IEC TS 63126	Level 1



	WARRANTY		
	Standard	REC ProTrust	
Installed by an REC Certified Professional	No	Yes	Yes
System Size	All	<25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%

REC ProTrust Warranty applies only for i) REC panels installed by an REC Certified Solar Professional, and ii) panels have been registered by the installer with REC. Subject to System Size and further conditions. See www.recgroup.com for details.

DELIVERY INFORMATION	
Panels per Pallet	33
Panels per 40 ft GP/high cube container	594 (18 Pallets)
Panels per 53 ft truck	792 (24 Pallets)



Available from:



Founded in 1996, REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power. As Solar's Most Trusted, REC is committed to high quality, innovation, and a low carbon footprint in the solar materials and solar panels it manufactures. Headquartered in Norway with operational headquarters in Singapore, REC also has regional hubs in North America, Europe, and Asia-Pacific.

Specifications subject to change without notice.