







WOOD INSERTS

ZINC DIE CAST

TYPE	DESCRIPTION	PART NUMBER	IMPERIAL THREAD SIZE	PART NUMBER	METRIC THREAD SIZE	LENGTH
<p>Low Profile</p>  <p>Knock-In Insert</p>	<p>Type I Knock-In inserts have low profile decorative heads which is ideal for applications where the head of the nut is exposed. Has a closed end and sharp barbs designed for easy driving yet undercut design holds firmly. Can be plated in a variety of finishes for a decorative finish.</p>	WS291212 WS291213 WS291214 WS291219	8-32 10-24 10-32 1/4-20	TBD TBD TBD TBD	M4 x .5 M4.5 x .75 M4.5 x .5 M6 x .75	13MM 13MM 13MM 18MM
<p>Flush Tapered Shank</p>  <p>Screw-In Insert</p>	<p>Type E Screw-In inserts have hex recess drives and can be set just below the mounting surface. External threads are tapered and are sharp and clean with axial flutes to prevent jamming. Has high retention and has the benefit of economy.</p>	WS291110 WS291111 WS291112 WS291115 WS291210	10-24 10-32 1/4-20 1/4-20 5/16-18	TBD TBD WS291028 WS291116 WS112800	M4.5 x .75 M4.5 x .5 M6 x 1.0 M6 X 1.0 M8 X 1.25	13MM 13MM 13MM 20MM 20MM
<p>Flush Straight Shank</p>  <p>Screw-In Insert</p>	<p>Type SIT Screw-In inserts with hex drives and straight shanks is similar to the tapered shank insert except the external threads are not tapered making centering and starting easy. It has the benefit of economy and requires a smaller pilot hole, which is beneficial in edge and end grain use.</p>	WS291101 WS291100 WS291102 WS291117 WS291103 WS291113	10-24 10-32 1/4-20 5/16-18 1/4-20 5/16-18	TBD TBD WS291026 TBD TBD TBD	M4.5 x .75 M4.5 x .5 M6 x 1.0 M8 x 1.25 M6 X 1.0 M8 X 1.0	13MM 13MM 13MM 13MM 25MM 25MM
<p>Flanged Tapered Shank</p>  <p>Screw-In Insert</p>	<p>Type D Screw-In hex drive tapered shank inserts are designed for rapid engagement into the material. The flanged head design provides controlled depth and straight driving. The external thread design provides high retention and meets industry torque and tensile standards.</p>	WS115586 WS291303 WS291308 WS291310 WS291301 WS291302 WS291311 WS291312	10-32 1/4-20 10-24 10-32 1/4-20 1/4-20 1/4-20 5/16-18	TBD WS291029 TBD TBD WS291027 TBD TBD TBD	TBD M6 x 1.0 M4.5 x .75 M4.5 x .5 M6 x 1.0 M6 X 1.0 M6 X 1.0 M8 x 1.25	10MM 10MM 13MM 13MM 13MM 20MM 25MM 25MM
<p>Flanged Straight Shank</p>  <p>Screw-In Insert</p>	<p>Type SIS Screw-In hex drive straight shank inserts have a low profile flat head configuration which allows easy centering and driving. This insert can be used with a smaller pilot hole than most other inserts.</p>	WS291201 WS291202 WS291203 WS291204	10-24 10-32 1/4-20 1/4-20	TBD TBD TBD WS291030	M4.5 x .75 M4.5 x .5 M6 x 1.0 M6 x 1.0	13MM 13MM 13MM 25MM
<p>Connector Nut</p>  <p>Truss Head</p>	<p>Type JZN - The truss head provides a low profile and excellent bearing surface. Threads are deep allowing for ample adjustment. The slot is clean and precisely formed providing no-slip screw driver assembly.</p>	WS291022 WS291023 WS291024 WS291025 WS291026 TBD	8-32 10-24 10-32 1/4-20 5/16-18 TBD	TBD TBD TBD TBD TBD WS291027	TBD TBD TBD TBD TBD M6 x 1.0	.625" .625" .625" .625" .625" .625"

Please visit our website to request a quote.

www.wscustomcomponents.com

