

VACUUM LIFTER FOR MOUNTING



Technical specifications

[Inquire now](#)



[» Back to overview](#)

DSKE2 - 12V

Short description	Meets the requirements for site operation according to DIN EN 13155. The DSKE2 - 12V can be combined with many of our mounting devices.
Filter area	up to 450 kg
Dual circuit system	2 vacuum circuits, independent of each other
Suction pad	6 pieces, type 150K
Extensions	2 piece
Load capacity	300 kg with 4 suction cups 450 kg with 6 suction cups, with extensions
Turn	360° manual, lockable every 45
Sway	90° manual, stepless, with lowering cylinder
Power supply	12 V battery mains-independent with integrated charger
Furnishing	• Voltage indicator, shows the battery charge level • Vacuum display, shows the current vacuum level • Acoustic warning signal when vacuum is undershot
Service	Hand valves, suction/ release valves
Own weight	approx. 55 kg
Options	• Cable or radio remote control for suction, release with quick release function • Suspension for rotating/slewing electric

Our expertise: Made to measure

Do you have special requirements due to your particular elements or a demanding environment? Here, too, we can help: In addition to our ready-made solutions, we are also happy to work out a custom-made product exactly for your requirements. In doing so, you can successfully continue your projects with vacuum lifters that have been specially designed for you. Just give us a call and we will discuss the details.