

# BUFFALO

# UTILITY S2

2 SPEED

TECHNICAL SPECIFICATIONS



| FRAMESET |                                                                                |
|----------|--------------------------------------------------------------------------------|
| Frame    | Rear-facing horizonatal dropout, 130 OLD (Over Locknut Distance), carbon steel |
| Fork     | 1" threaded with internally tapered steerer, carbon steel                      |
| Size     | 19" universal fit with dipping top tube                                        |



| WHEELS |                                                             |
|--------|-------------------------------------------------------------|
| Hubs   | Rear, threaded, 125 OLD                                     |
| Rims   | 26", 36 hole, aluminum, Box section durable nylon rim strip |
| Spokes | 13G high-carbon steel, Spoke Pattern 255mm 3-cross          |
| Tires  | Kenda Buffalo, 26x1.95, anti-puncture layer                 |
| Tubes  | 1.2mm butyl, schrader valve                                 |



| DRIVETRAIN     |                                                                               |
|----------------|-------------------------------------------------------------------------------|
| Freewheel      | 2-speed drivetrain, 19/18T                                                    |
| Crank          | Square taper, 45/27T, 170mm, steel                                            |
| Pedals         | 9/16" thread, nylon body, cold forging spindle                                |
| Chains         | 1/2"x1/8" single-speed with quick link, inboard 100 links, outboard 110 links |
| Bottom Bracket | Sealed cartridge, square taper, 113 mm spindle                                |



| COCKPIT     |                                                                        |
|-------------|------------------------------------------------------------------------|
| Saddle      | Reinforced base and rails UV-resistant cover                           |
| Seatpost    | 25.4mmx250mm, steel                                                    |
| Handlebar   | 25.4mm clamp, 600mm width, 20mm rise, 6 degree sweep, steel            |
| Grips       | PVC with reinforced ends                                               |
| Stem        | 60mm reach, 15 degree rise, 200m quill length, 40mm clamp width, steel |
| Headset     | JIS 1" threaded, steel                                                 |
| Brake set   | Front and rear caliper brake                                           |
| Brake Lever | Steel core with plastic cover                                          |



| EXTRAS      |                                            |
|-------------|--------------------------------------------|
| Mudguards   | Increased tire clearance with flares steel |
| Carrier     | Rated to 100 kg, 142 OLD, steel            |
| Stand       | Locking center stand, steel                |
| Reflectors  | Attached to spokes and rear mudguard       |
| Accessories | Bell, lock, pump, mini-tool, tire lever    |