

### Information

The SafeTest MultiTool Pro is designed to connect and monitor up to 12 SafeTest sensors simultaneously from up to 100m (328ft).

Data-logging, graphing and comprehensive reports can all be generated and exported seamlessly via in-built cloud connectivity.

### Features

1. Up to 12 channels simultaneously
2. Data exporting
3. Graphing
4. Charger included
5. IP68 display and case



MultiTool Pro

1. Press the middle button on the right side of the MultiTool Pro to turn it on.
2. The sensors will already be paired to the device. Remove the sensors from the kit's charging plugs. They will become powered. Tap on the sensor box to connect.



### Quick Setup

3. The test name and details can be edited by selecting them at the top of the screen.
4. Select **Save Template** on the bottom of the home page to save the current configuration. New templates can be created or loaded on demand.
5. Press 'Start Test' to get to the test page. Switch the view type by selecting **Graph** or **Dig** on the bottom left. Zoom can also be changed between 1x or 2x.
6. Press the **Function** button to access additional features for each separate sensor, including **Zero**, **Travel** and **Set Tolerance**.
7. Press **End Test** at the bottom of the screen once complete. Select **Save As PDF** to generate the report.
8. Select email and enter the email ID and details and select **Send** to export the report.  
*Ensure the device is connected to the internet.*
9. All generated reports can be viewed in the reports page, accessible from the home page.



If you have any questions or concerns with the usability of SafeGauge products, please don't hesitate to reach out to us on 1300 222 392. We appreciate your feedback to help improve our products and our customers satisfaction and safety when completing live work.