




Pump Curve



Overview

- Heavy duty cast iron submersible water pump
- High maximum submersion depth due to mechanical seal resistant to high pressure.
- Semi-open impeller made of high chrome alloy matched with ductile iron wear plate achieves superior durability.
- Effective motor cooling due to discharge channel cast as part of the motor housing.
- Thermally protected motor
- Approved control panel recommended
- Available with bare end or plug

Applications



- Mine & quarry dewatering
- Lagoon transfer
- Washplant feed
- Reservoir & pond dewatering
- Water discharge

About Audex

Audex are respected manufacturers of industrial submersible and vac-prime self-priming dewatering pumps. Our pumps have been specifically developed for use in the toughest and most abrasive of applications and environments. Trusted by operators of quarries, mines and recycling facilities, Audex pumps represent quality and reliability giving you superior performance and reduced downtime. Pumps that suit your application better because they have been designed with your industry in mind.

Specification

Model	AS 6-1100 TC
Discharge Size	6" / 150mm
Volts / Phases / Hertz	575 / 3 / 60
Motor Power	15HP / 11kW
Shaft Speed	3450 RPM
Max Head	104ft / 32m
Max Flow Capacity	647 gpm / 2450 lpm
Strainer Hole Size	25/32nds / 19.5mm
Solids Passage	25/32nds / 19.5mm
Max Water Temperature	104°F / 40°C
Cable Length	66ft / 20m
Cable Type	Servoflex 584
FLA / LRA	14.7A / 80A
Recommended Generator Size	66kW
Electrical Tolerance	+/- 10% V
Net Weight (N.W)	306.0lbs / 139kg
Gross Weight (G.W)	330.0lbs / 150kg
Unit Dimensions	33.6 x 16.3 x 17.1" / 855 x 415 x 435mm
Product Code	P15394



Materials of Construction

Upper cover	Cast iron
Motor body	Cast iron
Volute	Cast iron
Impeller	High chrome
Inlet plate	Ductile iron
Strainer	Steel
Shaft	420 Stainless Steel
Mechanical seal	SiC/SiC//SiC/SiC

Dimensions

d	5.90"	150mm
A	14.6"	373mm
A1	10.03"	255mm
B	31.77"	807mm
D	13.77"	350mm
H	27.36"	695mm
W1	7.48"	190mm
N.W	306lbs	139kg
G.W	330lbs	150kg
Packing Dimension	33.6 x 16.33 x 17.12"	855 x 415 x 435mm

C.W.L Continuous running water level