SYMPHONY FILTRATION SYSTEMS

Symphony CS-SYM-2-UF

Hard Water Scale, Corrosion, Chlorine Tastes & Odors. Addresses Bacteria, Cysts, Viruses, Turbidity and more, up to 15 gpm flow.



- Active Armour® protects from hard water scale and corrosion
- High Capacity 10 micron pre filter clarifies water and protects Ultrafilter from clogging for up to 150,000 gallons
- 99.99% (four log) reduction of any solid objects larger than 0.015 micron including bacteria, cysts and viruses at up to 15 gpm
- Addresses colloidal clay, turbidity, and high molecular weight organic contaminants
- Self-cleaning Ultrafilter, lasts up to 1,000,000 gallons
- Extreme High Capacity Carbon Block removes Chlorine, Organics, Herbicides, and Pesticides from the water, improving tastes and odors. Each cartridge is rated up to 265,000 gallons for a total capacity of 530,000 gallons
- Low operating cost and flexible programming to handle City, Well, Spring, and Rain water

SYSTEM SPECIFICATIONS

Dimensions	30" × 7" × 56"
Operating Pressure	30–80 psi
Water Temperature	40°–80° F
Electrical Requirement	110VAC
Drain Flow Rate	3 gpm
Drain Discharge Size	¾" FNPT
Connection Size	1" MNPT
Peak Flow Rate	15 gpm
Stage 1	**1x FLT-4B16P**
Stage 2	**1x FLT-SYM-UF**
Stage 3	**2x FLT-4B25XHC**

NSF 42 – Chlorine Taste and Odor Reduction

NSF 53 – Cyst Reduction

MADE IN THE USA