

INTERIOR

ARCHITECTURAL FILM

BLACK OPAQUE

Privacy - Blackout — Interior Application, Black From Outside

The Black Opaque blackout film privacy. Blocking almost all light immediate and effective privacy stock, a storage area, etc.

- 99% UV rejection with engineered light control
- Retains 0.5% visible light transmission
- Engineered and certified for professional interior installation
- 99% UV rejection helps protect interiors and furnishings from fading
- Black finish, engineered for interior application

Key Strengths

**99%**

UV Rejection

**0.5%**

Visible Light Transmission

**10 years**

Warranty

**M1**

Fire Resistance

Why Choose BLACK OPAQUE?

Privacy - Blackout — engineered for professional interior application.

ADVANTAGES

- 99% UV protection
- Black finish
- Professional interior installation
- Improved visual comfort
- 0.5% visible light transmission retained

PERFORMANCE KEY — SINGLE 3MM, FILM APPLIED

99%

UV Rejection

0.5%

Visible Light Transmission

10 years

Warranty

M1

Fire Resistance

CHARACTERISTICS



Warranty
10 years



Fire Resistance Rating
M1



Storage (recommended conditions)
3 years



REACH / RoHS
Compliant



Widths Available
152 cm, 183 cm



Installation Type
Interior



Color From the Outside
Black



Length
30.5 m



Product Carbon Footprint (LCA)
1.60 kgCO₂e/m²

CONSTRUCTION — PET, 60 µm

1. Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
2. High optical quality dyed polyester
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, polymerizes with glass within 15 days
6. Protection PET release liner, disposable after installation

GLAZING RECOMMENDATIONS

Vertical situation, standard glazed surface up to 2.5 m².

Clear Single Pane	! Caution
Tinted Single Pane	× Not recommended
Reflective Tinted Single Pane	✓ Yes
Clear Double Pane	! Caution
Tinted Double Pane	× Not recommended
Reflective Tinted Double Pane	✓ Yes
Gas-Filled Double Pane - Low E	× Not recommended
Stadip Ext. Clear Double Pane	× Not recommended
Stadip Int. Clear Double Pane	× Not recommended

✓ Yes ! Caution × Not recommended

Advice based on glazed surface area up to 2.5 m² — contact us for confirmation or a thermal shock analysis on larger or atypical glazing.

INSTALLATION & MAINTENANCE

Use Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Learn more about FNX and our product catalog.



THERMAL COMFORT



UV PROTECTION



GLARE REDUCTION



ENERGY PERFORMANCE



SUPERIOR AESTHETICS



PROFESSIONAL INSTALL