

INTERIOR

ARCHITECTURAL FILM

RED C

Coloured - Transparent — Interior Application, Red From Outside

Applied to a clear glazing, the transparent hue to the glass without diminishing perfect way to enliven any interior screens, etc.) with a touch of colour.

- 99% UV rejection with engineered light control
- Retains 25% visible light transmission
- Engineered and certified for professional interior installation
- 99% UV rejection helps protect interiors and furnishings from fading
- Red finish, engineered for interior application

Key Strengths



99%

UV Rejection



25%

Visible Light Transmission



5 years

Warranty



M1

Fire Resistance

Why Choose RED C?

Coloured - Transparent — engineered for professional interior application.

ADVANTAGES

- 99% UV protection
- Red finish
- Professional interior installation
- Improved visual comfort
- 25% visible light transmission retained

PERFORMANCE KEY — SINGLE 3MM, FILM APPLIED

99%

UV Rejection

25%

Visible Light Transmission

5 years

Warranty

M1

Fire Resistance

CHARACTERISTICS



Warranty
5 years



Fire Resistance Rating
M1



Storage (recommended conditions)
3 years



REACH / RoHS
Compliant



Widths Available
152 cm



Installation Type
Interior



Color From the Outside
Red



Length
30.5 m



Product Carbon Footprint (LCA)
1.56 kgCO₂e/m²

CONSTRUCTION — PET, 40 µm

1. Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
2. High optical quality dyed polyester
3. PS adhesive, polymerizes with glass within 15 days
4. Protection PET release liner, disposable after installation

GLAZING RECOMMENDATIONS

Vertical situation, standard glazed surface up to 2.5 m².

Clear Single Pane	✓ Yes
Tinted Single Pane	✗ Not recommended
Reflective Tinted Single Pane	✓ Yes
Clear Double Pane	! Caution
Tinted Double Pane	✗ Not recommended
Reflective Tinted Double Pane	✓ Yes
Gas-Filled Double Pane - Low E	✗ Not recommended
Stadip Ext. Clear Double Pane	✗ Not recommended
Stadip Int. Clear Double Pane	✗ Not recommended

✓ Yes ! Caution ✗ Not recommended

Advice based on glazed surface area up to 2.5 m² — contact us for confirmation or a thermal shock analysis on larger or atypical glazing.

INSTALLATION & MAINTENANCE

Use Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Learn more about FNX and our product catalog.