



OLA Agrol 15W-40

High performance oil for 2-stroke engines

Specification:

- API CD
- API GL-4
- CAT TO-2

Description:

OLA Agrol 15W-40 is a multifunctional oil for the lubrication of most agricultural equipment. This oil is intended for diesel and petrol engines, transmissions, hydraulic circuits, differentials and submerged brakes for agricultural machinery. OLA Agrol 15W-40 is recommended for various applications and in all weathers to meet the needs of agricultural activities.

Applications:

- Natural aspirated and turbo-charged diesel engines.
- On-highway light and heavy-duty.
- Off highway industries including :construction, mining, quarrying, and agriculture ...

Features and benefits:

Farmers use a wide range of equipment that requires oil multifunctional performance. It has the following advantages:

- Limitation of deposits and sludge formation.
- Better longevity of seals.
- Fewer products and less risk of errors.

- Reduced wear.
- Oil for petrol and diesel engines of agricultural materials and equipment.
- Use in transmissions of the same equipment when a product is required multifunction.

Typical properties:

	Test Method	Agrol 15W-40
Grade SAE		15W-40
Viscosity @ 40°C-cSt	ASTM D 445	110.5
Viscosity @ 100°C-cSt	ASTM D 445	14.3
Viscosity Index	ASTM D 2270	136
Sulphated ash content% m	ASTM D 874	1.2
TBN - mg KOH/g	ASTM D 2896	10
Pour point °C	ASTM D 97	-33
Flash Point °C	ASTM D 92	228
Density @ 20°C - kg/l	ASTM D 4052	0.88

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.