



OLA ATF III H

High performance automatic transmission fluid

Specification:

GM Dexron III H

Description:

OLA ATF III H is a high performance fluid for automatic transmissions vehicles specifying dexron III H. It is also used as a hydraulic fluid in unique applications.

Applications:

- OLA ATF III H is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying dexron III H level performance as well as the related power steering systems.
- OLA ATF III H is also suitable for off-highway transmissions power steering and other hydraulic systems requiring a dexron III H.

Features and benefits:

OLA ATF III H is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antioxidants, and defoamers providing outstanding performance:

- Good thermal and oxidation stability.
- Good anti-wear properties.
- Meets the wear requirement to promote longer transmission life.

- Excellent low-temperature fluidity.
- Effective foam control properties.
- Compatible with all common seal materials used in type III G transmissions.

Typical properties:

	Test Method	ATF III H
Viscosity @ 100°C-cSt	ASTM D 445	7.5
Viscosity Index	ASTM D 2270	Min 170
Pour point °C	ASTM D 97	-44
Flash Point °C	ASTM D 92	200
Density @ 15°C - kg/l	ASTM D 4052	0.870

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.