


Pump Curve



Overview

- Heavy duty cast iron submersible water pump
- High maximum submersion depth due to mechanical seal resistant to high pressure.
- Semi-open impeller made of high chrome alloy matched with ductile iron wear plate achieves superior durability.
- Effective motor cooling due to discharge channel cast as part of the motor housing.
- Thermally protected motor when used with approved control panel
- Approved control panel recommended
- Available with bare end or plug

Applications



- Mine & quarry dewatering
- Lagoon transfer
- Washplant feed
- Reservoir & pond dewatering
- Water discharge

About Audex

Audex are respected manufacturers of industrial submersible and vac-prime self-priming dewatering pumps. Our pumps have been specifically developed for use in the toughest and most abrasive of applications and environments. Trusted by operators of quarries, mines and recycling facilities, Audex pumps represent quality and reliability giving you superior performance and reduced downtime. Pumps that suit your application better because they have been designed with your industry in mind.

Specification

Model	AS 4-2200 TC
Discharge Size	4" / 100mm
Volts / Phases / Hertz	575 / 3 / 60
Motor Power	29HP / 22kW
Shaft Speed	3450 RPM
Max Head	223ft / 68m
Max Flow Capacity	608 gpm / 2300 lpm
Strainer Hole Size	1/4" / 6mm
Solids Passage	1/4" / 6mm
Max Water Temperature	104°F / 40°C
Cable Length	66ft / 20m
Cable Type	Servoflex 584
FLA / LRA	29.5 / 177
Recommended Generator Size	132kW
Electrical Tolerance	+/- 10% V
Net Weight (N.W)	815 lbs / 370kg
Gross Weight (G.W)	903 lbs / 410g
Unit Dimensions	58.8 x 19.2 x 27.5" / 1495 x 490 x 700mm
Product Code	



Materials of Construction

Upper cover	Cast iron
Motor body	Cast iron
Outer casing	Steel
Volute	Cast iron
Impeller	High chrome
Inlet plate	Ductile iron
Strainer	Steel
Shaft	304 Stainless Steel
Mechanical seal	TC/SiC//SiC/SiC

Dimensions

D	16.5"	420mm
H1	42.2"	1072mm
W1	9.44"	240mm
N.W	815 lbs	370kg
G.W	903 lbs	410g
Dimensions	58.8 x 19.2 x 27.5"	1495 x 490 x 700mm

C.W.L Continuous running water level