STOLTZ

SITE SPREADER

LEADER IN LOW DUST APPLICATION OF SOIL STABILIZATION MATERIALS



325 ft³ Open Top

Open Top Trailer Models

The perfect compliment to portable reclaimers and milling machines



200 ft³ Open Top


Road building
Commercial site prep
Public works
Mine reclamation

Spreaders for cement, fly ash, quicklime and other dry, flowable binding agents

Open Top Features




Walking Beam
Heavy duty walking beam suspension can handle the load and the toughest terrain (spring suspension on road legal model).



30" Drag Chain
Carbon steel slat style chain keeps material flowing at rates up to 120 lbs. per sq. yd. (at 1 mph).



Calibration Kit
Convenient tarp and scale calibration kit, so you are always prepared at the job site.



Fill-for-Life Gearbox
Proven PTO drivetrain backed by a heavy duty Fill-for-Life gearbox designed for hard use is standard ("plug-to" hydraulics for road legal model).







8 ft. Hydraulic Auger with adjustable pattern
The hydraulic auger is equipped with a 2 part gate allowing for pattern adjustment to ensure even spread across the auger width (8, 10, 12 ft available).

Unibody Construction
Unibody strength and construction eliminates flexing and cracking, ensuring dependable uptime and less maintenance. Even the supporting ribs are welded every inch forming one solid weldment.

Standard Features

- Reinforced 7-ga steel hopper
- 30" hardened D667KC conveyor chain
- PTO conveyor drive (1000 rpm, 21 spline)
- Rack and pinion metering gate
- 8 ft Hydraulic spreading auger w/dust curtains
- Walking beam suspension
- 19 L x 16.1 (10 ply) tires (200 ft^3)
  21.5 L x 16.1 (14 ply) tires (325 ft^3)
- Spread rate: up to 60 lb. / yd^2 @ 2mph, 120 lb. / yd^2 @ 1mph



Open top loading perfect for silo, bucket or super sacks. (shown with optional roll top tarp)



Full dust curtains help control application and ground impact dust.



Multiple power options are available including PTO, hydraulic and self contained powerpacks.



SSOT-8016RL Road Legal Model

Popular Options

- 10 ft. or 12 ft. auger
- Hydraulic rear gate with front indicator
- Selectable 4, 6, 8 ft pattern auger
- Plug to tractor hydraulic conveyor
- Full PTO hydraulics
- Roll top tarp
- Diesel powerpack
- Left/right pattern adjustment

Overall Dimensions	Length	Height	Width	Volume	Max Load
SSOT-8010	18.5 ft.	88 in.	98 in.	200 ft^3	8 Ton
SSOT-1516	24 ft.	89 in.	102 in.	325 ft^3	15 Ton
SSOT-8016RL	25 ft.	92 in.	102 in.	250 ft^3	8 Ton

Custom sizes available upon request

Decrease labor and liability: no more lifting heavy bags



STOLTZ

SITE SPREADER

1-800-843-8731

CementSpreaders.com

Stoltz Mfg., LLC
Morgantown, PA 19543