




















FLAT WEBBING SLINGS

DUPLEX FLAT STROP

COLOUR CODED

ALL WEBBING SLINGS COMPLY TO A 7-1

SAFETY FACTOR / AND SANS 94 /EN 1492

CAPACITY IN TON	COLOUR	WORKING LOAD LIMIT FOR 1 LIFTING SLING					WORKING LOAD LIMIT FOR 2 LIFTING SLINGS				
		STRAIGHT	CHOKED	0° - 7°	7° - 45°	45° - 60°	7° - 45°	7° - 45°	45° - 60°	45° - 60°	
											
FACTOR		1.0	0.8	2.0	1.4	1.0	1.4	1.12	1	0.8	
1 Ton		1 Ton	0.8 Ton	2 Ton	1.4 Ton	1 Ton	1.4 Ton	1.12 Ton	1 Ton	0.8 Ton	
2 Ton		2 Ton	1.6 Ton	4 Ton	2.8 Ton	2 Ton	2.8 Ton	2.24 Ton	2 Ton	1.6 Ton	
3 Ton		3 Ton	2.4 Ton	6 Ton	4.2 Ton	3 Ton	4.2 Ton	3.36 Ton	3 Ton	2.4 Ton	
4 Ton		4 Ton	3.2 Ton	8 Ton	5.6 Ton	4 Ton	5.6 Ton	4.48 Ton	4 Ton	3.2 Ton	
5 Ton		5 Ton	4 Ton	10 Ton	7 Ton	5 Ton	7 Ton	5.6 Ton	5 Ton	4 Ton	
6 Ton		6 Ton	4.8 Ton	12 Ton	8.4 Ton	6 Ton	8.4 Ton	6.72 Ton	6 Ton	4.8 Ton	
8 Ton		8 Ton	6.4 Ton	16 Ton	11.2 Ton	8 Ton	11.2 Ton	8.96 Ton	8 Ton	6.4 Ton	
10 Ton		10 Ton	8 Ton	20 Ton	14 Ton	10 Ton	14 Ton	11.2 Ton	10 Ton	8 Ton	
15 Ton		15 Ton	12 Ton	30 Ton	21 Ton	15 Ton	21 Ton	16.8 Ton	15 Ton	12 Ton	
20 Ton		20 Ton	16 Ton	40 Ton	28 Ton	20 Ton	28 Ton	22.4 Ton	20 Ton	16 Ton	

FEATURES

- Double ply lifting sling made from high tenacity
- Temperature range of -40°C to 100°C
- Available in any length



























PROTECTION DOUBLE PU COATED SLEEVES

- Extreme conditions – steel plates/ coils, polyurethane, bonded and sleeve.
- Hard conditions – concrete/granite , polyester sleeve
- Moderate conditions “PVC” – wood , PVC layflat sleeve, webbing sleeve

ENDLESS ROUND SLINGS

COLOURED CODED

HIGH STRENGTH , LIGHTWEIGHT POLYESTER SLINGS

CAPACITY IN TON	COLOUR	WORKING LOAD LIMIT FOR 1 LIFTING SLING					WORKING LOAD LIMIT FOR 2 LIFTING SLINGS			
		STRAIGHT	CHOKED	0° - 7°	7° - 45°	45° - 60°	7° - 45°	7° - 45°	45° - 60°	45° - 60°
										
FACTOR		1.0	0.8	2.0	1.4	1.0	1.4	1.12	1	0.8
1 Ton		1 Ton	0.8 Ton	2 Ton	1.4 Ton	1 Ton	1.4 Ton	1.12 Ton	1 Ton	0.8 Ton
2 Ton		2 Ton	1.6 Ton	4 Ton	2.8 Ton	2 Ton	2.8 Ton	2.24 Ton	2 Ton	1.6 Ton
3 Ton		3 Ton	2.4 Ton	6 Ton	4.2 Ton	3 Ton	4.2 Ton	3.36 Ton	3 Ton	2.4 Ton
4 Ton		4 Ton	3.2 Ton	8 Ton	5.6 Ton	4 Ton	5.6 Ton	4.48 Ton	4 Ton	3.2 Ton
5 Ton		5 Ton	4 Ton	10 Ton	7 Ton	5 Ton	7 Ton	5.6 Ton	5 Ton	4 Ton
6 Ton		6 Ton	4.8 Ton	12 Ton	8.4 Ton	6 Ton	8.4 Ton	6.72 Ton	6 Ton	4.8 Ton
8 Ton		8 Ton	6.4 Ton	16 Ton	11.2 Ton	8 Ton	11.2 Ton	8.96 Ton	8 Ton	6.4 Ton
10 Ton		10 Ton	8 Ton	20 Ton	14 Ton	10 Ton	14 Ton	11.2 Ton	10 Ton	8 Ton
15 Ton		15 Ton	12 Ton	30 Ton	21 Ton	15 Ton	21 Ton	16.8 Ton	15 Ton	12 Ton
20 Ton		20 Ton	16 Ton	40 Ton	28 Ton	20 Ton	28 Ton	22.4 Ton	20 Ton	16 Ton
25 Ton		25 Ton	20 Ton	50 Ton	35 Ton	25 Ton	35 Ton	28 Ton	25 Ton	20 Ton
30 Ton		30 Ton	24 Ton	60 Ton	42 Ton	30 Ton	42 Ton	33.6 Ton	30 Ton	24 Ton
40 Ton		40 Ton	32 Ton	80 Ton	56 Ton	40 Ton	56 Ton	44.8 Ton	40 Ton	32 Ton
50 Ton		50 Ton	40 Ton	100 Ton	70 Ton	50 Ton	70 Ton	56 Ton	50 Ton	40 Ton
60 Ton		60 Ton	48 Ton	120 Ton	84 Ton	60 Ton	84 Ton	67.2 Ton	60 Ton	48 Ton
80 Ton		80 Ton	64 Ton	160 Ton	112 Ton	80 Ton	112 Ton	89.6 Ton	80 Ton	64 Ton
100 Ton		100 Ton	80 Ton	200 Ton	140 Ton	100 Ton	140 Ton	112 Ton	100 Ton	80 Ton



- ▶ Easy to handle – light, flexible, soft
- ▶ High strength –to– weight ration
- ▶ Ideal for delicate surfaces
- ▶ Suitable for choker applications reduces WLL with 2%
- ▶ Colour coded for quick capacity identification
- ▶ Various capacities up to 300 ton S.W.L
- ▶ Wide range of lengths
- ▶ Safe working load indicated on each sling