

3 AAA BATTERIES

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

XPP-5454G


NIGHTSTICK[®]
Life Depends on Light™






Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



Dual Body Switches. High/Low Spotlight, High/Low Floodlight, Dual-Light



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing



160 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

3 AAA BATTERIES

ITEM NUMBER/UPC

- XPP-5454G, UPC 0 17398 80427 1

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, InMetro, UKCA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 115L, 5 hrs. runtime
- LOW: 60L, 16.25 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH: 120L, 5.25 hrs. runtime
- LOW: 60L, 16.75 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- HIGH: 160L, 3.5 hrs. runtime

CANDELA

- HIGH: 1,668
- LOW: 882

BEAM DISTANCE

- HIGH: 82m
- LOW: 60m

DUST/WATER RATING

ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.1 in (53 mm)
- WIDTH: 2.6 in (66 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.3 oz (94 g)

BATTERY







- AAA

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
- 3 AAA batteries
- Elastic non-slip headband
- Rubber hardhat strap

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	115 LUMENS	60 LUMENS	160 LUMENS
	5h	16h	3h 30min
	82m		
	1668cd		
	2m		
	1m		

NIGHTSTICK

CLASS I DIV 1 GRPS A-D T3
CLASS II & III GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T3 Ga
Ex ia IIC T3 Ga
Ex II 1 G Ex ia op is IIC T3 Ga
Ex ia op is IIC T3 Ga
Intertek ITS 13 ATEX27928X
ITS21UKEX0266X
IECEx ITS 18.0030X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell E92 or EN92
SEE INSTRUCTION MANUAL



Intertek
ID 5012927
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

XPP-5454G

Bayco Products, Inc.
640 S. Sanden Blvd.
Wylie, TX 75098

UK
CA 0359
CE 2575

US Patent 9,713,217
MFG MM-YY

CERTIFIED

