

TEST REPORT

1. Applicant

* Client Name : FEELUX Co. Ltd.
* Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea
* Date of Receipt : 200604

2. Purpose of Report :

3. Number of Report : 200604

4. Test Standard / Item : / 200604 NMP5 30K-24V-CI-BK

5. Test Period : 200604 ~ 200604

6. Test Environment

* Ambient Temp. : 24.8 +- 3 °C
* Relative Humidity : 66.3 +- 10 % RH

7. Test Item

* Name of Product : FEELUX
* Rating :
* Model :

8. Test Result : Refer to the attachment

Confirmation	Test by		Technical manager	
	CGR	Sign	MKOH	Sign

- * The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
- * This report cannot be reporduced, except in full.
- * This report is for reference only. It cannot replace the report by standard organization(s).

Result

Report Number	Sample Name	Sample Number	Test Standard
200604	FEELUX	FEELUX	

Test Item	Unit	Result	Notice
Beam Distribution Test		See Attachement	
ATHD	%	0.0	
CIE 1931 Cx, Cy		0.4330 , 0.3989	
Correlated Color Temperature	K	3041	
Ra		93.63	
Power Factor		1.000	
Input Voltage	V	24.000	
Input Current	A	0.211	
Input Watt	W	5.07	
Lamp Flux	lm	274.8	
Efficient	lm/W	54.27	
luminous Intensity (Max , Center)	cd	65 , 48	
Illuminance	lx	48	1 m
		12	2 m
		5	3 m

* This test result is for the sample provided by the client.

* Sample photo

Click to load image

Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Lamp flux (lm) 275

Current (A) 0.211

Total flux (lm) 275

Power Factor 1

Report

200604

Filename 200604 NMP5 30K-24V-CI-BK.jdt


Operator

CGR

Date

2020-06-04 오후 4:58:55

Luminous Intensity Distribution



Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

200604

Lamp flux (lm) 275

Current (A) 0.211

Filename 200604 NMP5 30K-24V-CI-BK.jdt

Total flux (lm) 275

Power Factor 1


Operator

CGR

Date

2020-06-04 오후 4:58:55

Luminous Intensity Distribution (Lowest 10%)



Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report	200604
Lamp flux (lm)	275	Current (A)	0.211	Filename	200604 NMP5 30K-24V-CI-BK.jdt
Total flux (lm)	275	Power Factor	1	Operator	CGR
				Date	2020-06-04 오후 4:58:55

Luminous Intensity Data

Maximum (cd) : 65

Minimum (cd) : 0

G/C	0	30	60	90	120	150	180	210	240	270	300	330	360
0	48.26	47.28	46.86	46.01	46.29	46.23	48.26	47.28	46.86	46.01	46.29	46.23	48.26
10	47.55	44.93	41.23	37.58	38.69	43.73	47.87	50.93	53.35	54.17	52.99	49.84	47.55
20	46.49	42.82	37.82	27.49	34.98	42.03	46.92	53.37	58.3	59.33	57.09	50.81	46.49
30	44.69	39.92	34.93	17.14	32.76	40.66	45.01	54.47	61.2	63.17	59.47	52.22	44.69
40	40.4	36.48	31.13	6.27	29.39	37.03	42.16	54.13	62.85	65.09	61.61	50.8	40.4
50	35.61	31.4	26.22	2.32	25.25	32.7	37.43	51.89	62.58	65.07	60.97	48.64	35.61
60	28.47	25.26	19.98	1.73	21.06	27.35	31.37	48.54	59.8	64.12	58.07	44.92	28.47
70	21	18.27	13.88	0.92	15.03	20.89	24.86	43.16	55.98	61.48	54.22	39.13	21
80	14.19	11.74	8.05	0.54	8.67	14.28	17.35	36.02	49.45	57.11	47.27	31.61	14.19
90	12.12	8.49	5.54	0.17	5.7	9.4	12.18	30.47	44.95	46.48	42.82	29.5	12.12
100	10.22	8.32	4.1	0.45	5.58	8.78	11.64	28.74	42.76	1.63	40.28	27.02	10.22
110	10.47	8.24	4.05	0.91	4.66	8.94	10.32	26.93	28.56	0.93	36.88	25.57	10.47
120	6.42	7.48	1.97	0.99	1.99	8.07	5.67	23.44	25.79	0.25	24.53	21.78	6.42
130	0.8	2.36	2.31	1.04	3.18	3.11	0.52	14.82	9.29	0.28	6.72	14.07	0.8

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report	200604
Lamp flux (lm)	275	Current (A)	0.211	Filename	200604 NMP5 30K-24V-CI-BK.jdt
Total flux (lm)	275	Power Factor	1	Operator	CGR
				Date	2020-06-04 오후 4:58:55

Luminous Flux Table

Total Lamp Lumens:	275
Luminaire Efficiency (lm/W):	274.76
CIE Classification:	Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	1.12	1.12	0.41	0.41
10	8.92	10.04	3.65	3.65
20	17.40	27.44	9.99	9.99
30	24.90	52.34	19.05	19.05
40	30.35	82.69	30.09	30.10
50	33.57	116.26	42.31	42.31
60	34.04	150.30	54.69	54.70
70	31.63	181.93	66.20	66.21
80	26.63	208.56	75.89	75.91
90	22.62	231.18	84.13	84.14
100	17.04	248.21	90.33	90.34
110	14.28	262.49	95.52	95.54
120	10.15	272.64	99.21	99.23
130	2.12	274.76	99.99	100.00

Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

200604

Lamp flux (lm) 275

Current (A) 0.211

Filename 200604 NMP5 30K-24V-CI-BK.jdt


Total flux (lm) 275

Power Factor 1

Operator CGR

Date 2020-06-04 오후 4:58:55

IsoCandela (Type C)



Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

200604

Lamp flux (lm) 275

Current (A) 0.211

Filename 200604 NMP5 30K-24V-CI-BK.jdt

Total flux (lm) 275

Power Factor 1


Operator

CGR

Date

2020-06-04 오후 4:58:55

IsoLux Diagram (Ground)



Pole Height (m): 2.7

Area Width (m): 12

Total Optical Solution Provider

Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

200604

Lamp flux (lm) 275

Current (A) 0.211

Filename 200604 NMP5 30K-24V-CI-BK.jdt

Total flux (lm) 275


Power Factor 1

Operator

CGR

Date 2020-06-04 오후 4:58:55

IsoLux Diagram (Wall)



Pole Height (m): 2.7

Wall Distance (m): 2.7

Aiming Plane: 0

Wall Height (m): 12

Total Optical Solution Provider



Luminaire

Lamp

No. of lamps	1	Voltage (V)	24
Lamp flux (lm)	275	Current (A)	0.211
Total flux (lm)	275	Power Factor	1

Report 200604

Filename 200604 NMP5 30K-24V-CI-BK.jdt

Operator CGR

Date 2020-06-04 오후 4:58:55

Illuminance Levels (Ground)


6.00	0.04	0.04	0.02	0.10	0.09	0.11	0.01	0.05	0.15	0.14	0.09	0.10	0.10
5.00	0.12	0.05	0.05	0.02	0.22	0.23	0.03	0.15	0.34	0.17	0.14	0.13	0.13
4.00	0.12	0.17	0.14	0.11	0.36	0.28	0.05	0.26	0.48	0.39	0.33	0.18	0.12
3.00	0.12	0.24	0.44	0.25	0.23	0.62	0.13	1.11	0.89	0.61	0.49	0.25	0.14
2.00	0.16	0.32	0.42	1.03	0.69	1.69	0.71	2.26	1.59	1.13	0.50	0.38	0.18
1.00	0.24	0.48	0.71	1.06	1.90	2.52	4.21	4.09	2.32	1.25	0.88	0.60	0.33
0.00	0.26	0.54	0.81	1.58	3.07	5.41	6.62	5.38	2.98	1.50	0.75	0.51	0.23
-1.00	0.23	0.47	0.70	1.75	3.31	4.75	6.15	5.78	3.78	2.11	0.86	0.55	0.27
-2.00	0.31	0.58	0.89	1.25	2.07	3.45	4.59	3.88	2.85	1.52	1.08	0.70	0.41
-3.00	0.30	0.29	0.59	0.87	1.82	2.11	2.67	2.35	1.91	1.31	0.75	0.43	0.38
-4.00	0.16	0.26	0.47	0.88	0.95	1.41	1.55	1.41	1.12	0.94	0.68	0.36	0.24
-5.00	0.17	0.22	0.43	0.58	0.66	0.90	0.96	0.89	0.76	0.64	0.48	0.36	0.23
-6.00	0.15	0.27	0.32	0.33	0.41	0.56	0.59	0.54	0.48	0.40	0.36	0.30	0.23
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.) : 6.62

Illum. (Min.) : 0.01

Illum. (Avg.) : 0.98

All illuminance level values are in lux.




Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report	200604
Lamp flux (lm)	275	Current (A)	0.211	Filename	200604 NMP5 30K-24V-CI-BK.jdt
Total flux (lm)	275	Power Factor	1	Operator	CGR
				Date	2020-06-04 오후 4:58:55

Illuminance Cone Diagram





Luminaire

Lamp

No. of lamps	1	Voltage (V)	24
Lamp flux (lm)	275	Current (A)	0.211
Total flux (lm)	275	Power Factor	1

Report 200604

Filename 200604 NMP5 30K-24V-CI-BK.jdt

Operator CGR

Date 2020-06-04 오후 4:58:55

Coefficient of Utilization

Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

